



LARSONELECTRONICS.COM
LARSON ELECTRONICS LLC



MAGNETIC MOUNT
EXPLOSION PROOF
LOW PROFILE LINEAR LED LIGHT
Class I Division 2
Class II Divisions 1 & 2
Voltage: Universal 120-277VAC
50/60 hz
IP66 Rated
78 Watts - 7,250 Lumens
Dimensions: 47.81"L X 6.40"W x 3.10"H
Beam Angle: 150°
Part # EPLC2-48-100LED-AMB



Larson Electronics LLC

9419 E US HWY 175

Kemp, TX 75143

www.larsonelectronics.com

sales@larsonelectronics.com

Phone: 1-800-369-6671

Phone: 903-498-3363

Fax: 903-498-3364

CAGE Code: 41TLO

DUNS: 078373685

TID: 16-1541123



FOOD SAFE
SHATTER PROOF
INSPECTION LIGHT
Voltage: 120 Volts,
60 Hz - US voltages
50' SOOW 16/3 AWG cord
26 Watts - 1,740 Lumens
14.5"L X 3.5"D
Polycarbonate Lens
Part # FSFL-26-50



SUGAR REFINERIES
FOOD PROCESSING PLANTS
WINERIES
GRAIN PROCESSING PLANTS

FOOD GRADE LIGHTING

FOOD GRADE INSPECTION LIGHTS
ULTRAVIOLET FOOD GRADE LIGHTS
EXPLOSION PROOF HANDHELD LIGHTS
EXPLOSION PROOF LED FIXTURES



Larson Electronics provides the best lighting solutions for food processing plants, sugar refineries, breweries, wineries and other processing establishments. Those who are relying on their lights to be waterproof, rugged and able to handle the rigors of the processing industry need to look no further.

From light bars and spotlights to docklights, we provide a complete line of rugged and waterproof spotlights and floodlights that weather the test of time.

With a ample stock and quick delivery, whether you're equipping a large food processing center or a small winery, we can have you up and running in no time.



FOOD SAFE INSPECTION LAMP
Glass Free - Shock Resistant
IP67 Rated Waterproof
28 Watts - 3,500 Lumens
Voltage: 120-277 Volts AC, 50/60Hz
or 11-25V AC/DC
50' SOOW Cable w/ Cord Cap
and Cord Reel
Dimensions: 60"L x 3"D (lamp only)
Part # FTL-5-LED-CR50



LARSON ELECTRONICS LLC



EXPLOSION PROOF LOW PROFILE LED FIXTURE
 Class I Divisions 1 & 2
 Class II Divisions 1 & 2
 104 Watts - 13,520 Lumens
 Voltage: Universal 100-277 VAC, 50/60Hz or 11-25V AC/DC 240V-60hz 277V-60hz
 Dimensions: 50"L x 5"W x 3"H
 Factory Sealed - Paint Spray Booth Approved
 Part # EPL-LP-48-LED



LOW VOLTAGE LED FIXTURE
 Class I Division 2
 31 Watts - Lumens: Spot: 2334
 Flood: 1996
 Voltage: 12-28V DC
 Lamp Dimensions (w/ Bracket): 7.25"W x 4.63"H
 UL 844, UL 1598
 IP66 Ingress Protection
 Part # HAL-31L-LV



MAGNETIC MOUNT LOW VOLTAGE LED FIXTURE
 Class I Division 2, Class II Division 2
 31 Watts - Lumens: Spot: 2334
 Flood: 1996
 Voltage: 12-28V DC
 Lamp Dimensions (w/ Bracket): 8"W x 5.5"H
 UL 844, UL 1598
 IP66 Ingress Protection
 Beam Type: 30° Spot or 100° Flood
 Part # HAL-31L-LV-MB-50



INDUSTRIAL ULTRAVIOLET LED LIGHT FIXTURE
 Class I Division 2, Class II Division 2
 100 Watts - Color: Ultraviolet- 365NM
 Voltage: 100-277 Volts AC, 50/60Hz or 11-25 Volts AC/DC
 Dimensions: 16"W x 14"H x 5"D
 IP67 Rated Waterproof
 Part # GAU-HB-100LED-RT-UVA



EXPLOSION PROOF FLUORESCENT UV LIGHT FIXTURE
 Class I Divisions 1 & 2, Class II Divisions 1 & 2
 160 Watts - Color: Ultraviolet- 400nm-315nm,315nm-280nm, 280nm-100nm
 Voltage: Multi- 120V-60hz 220V-50hz 240V-60hz 277V-60hz
 Dimensions: 52.26"L x 25.24"W x 9.82"H x 9.82" H
 UL 595 Outdoor Marine Type
 UL 1598 Marine Type
 Part # EPL-48-4L-UV

VAPOR PROOF LED HANDHELD INSPECTION LIGHT
 Impact/Vibration Resistant
 12 Watts
 Voltage: 120/240VAC 50/60hz
 50' SJOW cord, 5-15 Straight Blade Plug
 Dimensions: 12.5"L x 2.75"D
 Food Safe Polycarbonate Lens
 Vapor Proof/Waterproof
 Part # VPHLED-12W-50



FOOD GRADE LIGHTING

