

UL Product **iQ**[™]



FTEV7.E119451 - Emergency Lighting and Power Equipment for Use in Hazardous Locations Certified for Canada

Emergency Lighting and Power Equipment for Use in Hazardous Locations Certified for Canada

See General Information for Emergency Lighting and Power Equipment for Use in Hazardous Locations Certified for Canada

RIG-A-LITE PARTNERSHIP LTD

E119451

8500 HANSEN RD

HOUSTON, TX 77075-1006 USA

Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Groups F and G; Class III Hazardous Locations, emergency lighting units, Model(s) CHL or EXCHL followed by 04 or 07; followed by L; followed by C or D; followed by 2 or 4; followed by A, B, C, or U; may be followed by FB, SC, SMK, WMB, ADJ, EM, 30, 35 or 50; followed by any six alpha digits A through Z for commercial purposes. +

Class I, Groups A, B, C and D, Division 2, emergency lighting equipment, Model(s) HZALJ followed by 04, 06, 08, 10, 11, 13, AM5 or AM4; followed by L; followed by U; followed by CG, FG, or CP; may be followed by 1, 3 or W; may be followed by G; may be followed by P, P1, C, C1, W, W1, T, T1, S, S1, L, or L1; may be followed by SC, 30, 40; followed by EM; may be followed by four additional alpha-numeric characters.+

Class I, Groups C and D, Class II, Groups E, F and G; and Class III Hazardous Locations., Model(s) Cat. No. XML or EXML followed by 04, 05, 06, 07, 09, 11 or 14; followed by L; followed by C or D; followed by 2 or 4; followed by A, B, C, or U; followed by EM, MB, PB, RIG, SC, 30, 35 or 50.

Class I, Groups C and D, Division 1, Class II, Groups E, F and G, Division 1, and Class III, emergency exit light, Model(s) XPEH, followed by 1 or 2, followed by G or R, followed by DT or 24, followed by 0, 1, or 2, followed by 0, 1 or 2, may be followed by M, N or W, may be followed by X+ or SD.

Class I, Groups C and D, Division 1, Class II, Groups E, F and G, Division 1, and Class III, emergency exit light, Model(s) XPEL, followed by U, followed by 0, 1, or 2, followed by 0, 1 or 2, may be followed by M, N or W, may be followed by XX+ or SD.

Class I, Groups C and D, Division 1, Class II, Groups E, F and G, Division 1, and Class III, emergency exit light, Model(s) XPEX, followed by 1 or 2, followed by R or G, may be followed by AR, AL, AA or LR, followed by DT, followed by WP or EB, may be followed by EM+ or SD.

Class I, Groups C and D, Division 1, Class II, Groups E, F and G, Division 1, and Class III, unit equipment, Model(s) Class I, Groups C and D, Division 1; Class I, Groups A, B, C and D, Division 2; Class II, Groups E, F and G, Division 1; and Class III, emergency LED luminaire, XP, followed by 30L, 50L, 70L, 75L, 100L, 105L or 140L, followed by 2 or 4, followed by 2L, 3L or 4L, followed by U, followed by EM or EMO, followed by OB and/or F, the use of a dash - is optional.

+ - Complimentary Listed Under IGTC.

Last Updated on 2020-11-03

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"