



POWER
DISTRIBUTION

CATALOG 2020



The **Larson Electronics** Power Distribution series consists of portable power distribution products for industrial locations, combustible work sites and temporary projects with limited electrical infrastructure. These units make power management efficient and safe by providing access to panels, transformers, breakers, receptacles, cords and other electrical equipment at rugged job sites. Operators can use the power distribution systems in this series to rectify voltages (step up or step down), extend main or temporary power sources and power remote equipment. For seamless deployment around facilities, we offer several portable solutions that range from enclosed power distribution stations mounted on TGIC powder coated cubes to compact spider boxes with convenient handles and stands. Our standard models are finished with a durable polyester powder coated finish for protection from scratches, debris, moisture and mild corrosion. This allows our NEMA-rated power distribution units to be used in outdoor and rugged locations.

These industrial power systems are recommended for the following: construction, aerospace, stage, studio, recording sets, military, air force, mining, emergency sites, infrastructure projects, hazardous locations, oil fields, offshore rigs and refineries.

In this catalog, temporary power distribution units mounted on dolly carts are designed for quick deployment of power distribution equipment, such as

panels, transformers, receptacles and cords. With all system components secured on a two-wheel, powder coated dolly cart with a weatherproof flip cover, operators can easily move the unit from location to location. Powder coated cube frames with four wheels are available for enclosed power distribution stations. We also offer trailer-mounted and skid-mounted models, which are suitable for seamless transportation to remote locations.

Temporary, explosion proof power distribution units are for Class I, II and III, Divisions 1 and 2 rated hazardous locations and flammable environments. These products make power distribution possible in combustible work sites. For robust protection, the power distribution systems consist of non-sparking materials, such as copper-free aluminum, and explosion proof components. Our portable explosion proof power distribution units are also secured on powder coated carts with wheels for mobility.

For extending power connections and access to outlets in industrial sites, we offer mini power distribution systems and portable spider boxes. The compact units feature accessible handles for transportation, as well as for wrapping cords during storage. Our portable spider boxes are equipped with legs to keep the devices above ground and for extra stability on rough terrain. Additionally, power distribution products secured on standard ATA cases with wheels, racks and sturdy suitcases with handles are designed for

stage, studios and recording sets. These sites have demanding requirements due to numerous temporary equipment that need power and electrical connections.

As a one-stop shop for portable power distribution solutions, our offerings include extension cords for general areas and hazardous locations. Customers may choose their preferred cord type and length in the catalog to ensure compatibility with their equipment at the site.

Larson Electronics offers customization services for the power distribution units in this catalog (at additional costs). Our customization services are designed for businesses with specific power distribution requirements or needs. Examples of features available for customization include: primary and/or secondary voltages, transformer capacity, panels, cords (type and length), cord caps, receptacles (type and quantity), mount, finish, color and more. We can also add devices to power distribution systems, such as meters, variable frequency drives, manual transfer switches, pilot lights and more. Contact us today at 1-800-369-6671 for more information about customization services for our power distribution products.



SKU Example: MPD-CD2-309.60AB-DE75YT-LN-10.N10

MPD - **CD2** - **309.60AB** - **DE75YT** - **LN** - **2.L08** - **10.N10**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 13 14

(1) Series	
MPD	

(2) Application	
C	Construction
A	Aerospace
S	Stage/Studio
M	Military
F	Airforce
B	Consumer
E	Commercial Panel
X	Explosion Proof (C1D1)
H	Hazardous Location (C1D2)

(3) Frame Type / Model	
C1	Open Steel Frame Cube, Skid Mount, Configuration 1
C2	Open Steel Frame Cube, Skid Mount, Configuration 2
C3	Open Steel Frame Cube, Skid Mount, Configuration 3
C4	Open Steel Frame Cube, Skid Mount, Configuration 4
C5	Open Steel Frame Cube, Skid Mount, Configuration 5
D1	Upright Steel Dolly, Standard
D2	Upright Steel Dolly, XLarge
D3	Upright Steel Dolly, Configuration 3
D4	Upright Steel Dolly, Configuration 4
D5	Upright Steel Dolly, Small
W1	Enclosed Steel Cube (Casters), 1:1 Configuration
W2	Enclosed Steel Cube (Casters), 1:2 Configuration
W3	Enclosed Steel Cube (Casters), 2:1 Configuration
W1.1	Enclosed Steel Dual Cube (Casters), 1:2 Configuration
W1.2	Enclosed Steel Dual Cube (Casters), 2:1 Configuration
W1.3	Enclosed Steel Dual Cube (Casters), 1:1 Configuration
W11	Open Frame Steel Cube (Casters), Large
W12	Open Frame Steel Cube (Casters), XLarge
W13	Open Frame Steel Cube (Casters), XXL
W14	Open Frame Steel Cube (Casters), Small
W20	304 Stainless N4 Enclosed Cube (Casters), 1:1 Configuration
W21	304 Stainless N4 Enclosed Cube (Casters), 1:2 Configuration
W22	304 Stainless N4 Enclosed Cube (Casters), 2:1 Configuration
W25	304 Stainless Open Cube (Casters), Standard
W26	304 Stainless Open Cube (Casters), Large
W27	304 Stainless Open Cube (Casters), XLarge
W28	304 Stainless Open Cube (Casters), XXL
W29	304 Stainless Open Cube (Casters), Small
W30	Aluminum Enclosed Cube (Casters), 1 Sec xfmr, 1 set devices
W31	Aluminum Enclosed Cube (Casters), 1 Sec xfmr, 2 set devices
W32	Aluminum Enclosed Cube (Casters), 2 Sec xfmr, 1 set devices
W35	Aluminum Open Cube (Casters), Standard
W36	Aluminum Open Cube (Casters), Large
W37	Aluminum Open Cube (Casters), XLarge
W38	Aluminum Open Cube (Casters), XXL
W39	Aluminum Open Cube (Casters), Small

SKU Example: MPD-CD2-309.60AB-DE75YT-LN-10.N10

MPD - **CD2** - **309.60AB** - **DE75YT** - **LN** - **2.L08** - **10.N10**

1
2
3
4
5
6
7
8
9
10
11
12
13
14
13
14

(4) Input Wiring	
CS	California Standard
NTL	NEMA, Twist Lock
NSB	NEMA, Straight Blade
309	IEC 60309, IP67
308	IEC 60309, IP44
861	UL 1686, Style I
862	UL 1686, Style II
863	UL 1686, Style I, Corrosion Resistant
864	UL 1686, Style I, Reverse Service
865	UL 1686, Style II, Reverse Service
866	UL 1686, Style I, Corrosion Resistant, Reverse Service
867	UL 1686, Style I, Polarized
868	UL 1686, Style II, Polarized
869	UL 1686, Style I, Corrosion Resistant, Polarized
BW	Type W Cord, Blunt Cut
BS	Type SO Cord, Blunt Cut
T	Wiring Terminal
CLP5	15 Sereis Single Pole (Camlock), Panel Mount, Straight
CLP6	16 Sereis Single Pole (Camlock), Panel Mount, Straight
CLP7	17 Sereis Single Pole (Camlock), Panel Mount, Straight
CLP8	18 Sereis Single Pole (Camlock), Panel Mount, Straight
CLP9	19 Sereis Single Pole (Camlock), Panel Mount, Straight
CLP2	22 Sereis Single Pole (Camlock), Panel Mount, Straight
CLP3	23 Sereis Single Pole (Camlock), Panel Mount, Straight
CLR5	15 Sereis Single Pole (Camlock), Panel Mount, 45°
CLR6	16 Sereis Single Pole (Camlock), Panel Mount, 45°
CLR7	17 Sereis Single Pole (Camlock), Panel Mount, 45°
CLR8	18 Sereis Single Pole (Camlock), Panel Mount, 45°
CLR9	19 Sereis Single Pole (Camlock), Panel Mount, 45°
CLR2	22 Sereis Single Pole (Camlock), Panel Mount, 45°
CLR3	23 Sereis Single Pole (Camlock), Panel Mount, 45°
CLT5	15 Sereis Single Pole (Camlock), Panel Mount, 30°
CLT6	16 Sereis Single Pole (Camlock), Panel Mount, 30°
CLT7	17 Sereis Single Pole (Camlock), Panel Mount, 30°
CLT8	18 Sereis Single Pole (Camlock), Panel Mount, 30°
CLT9	19 Sereis Single Pole (Camlock), Panel Mount, 30°
CLT2	22 Sereis Single Pole (Camlock), Panel Mount, 30°
CLT3	23 Sereis Single Pole (Camlock), Panel Mount, 30°

(5) Feed Thru	
F	Yes
B	No

(6) Primary Phase	
D	3-Phase, Delta
Y	3-Phase, Wye
S	1-Phase
L	Low Voltage, AC
C	Low Voltage, DC
H	High Voltage DC
J	400 Hz, 1-Phase
K	400 Hz, 3-Phase, Delta
L	400 Hz, 3-Phase, Wye

SKU Example: MPD-CD2-309.60AB-DE75YT-LN-10.N10

MPD - **CD2** - **309.60AB** - **DE75YT** - **LN** - **2.L08** - **10.N10**

1 2 3 4 5 6 7 8 9 10 11 12 13 14 13 14

(7) Primary Voltage	
A	690V
B	660V
C	600V
D	575V
E	480V
F	460V
G	440V
H	420V
J	415V
K	400V
L	380V
ZA	347V
M	277V
N	250V
P	240V
Q	230V
R	220V
T	208V
U	200V
V	125V
W	120V
X	115V
Y	110V
Z	120/240V
LA	12V
LB	16V
LC	18V
LD	20V
LE	24V
LF	30V
LG	36V
LH	40V
LJ	48V
LK	50V
LL	60V
LM	72V
LN	80V
LP	100V
LQ	150V

(8) KVA	
0	N/A
1	1 KVA
2	2 KVA
2.5	2.5 KVA
3	3 KVA
3.5	3.5 KVA
4	4 KVA
4.5	4.5 KVA
5	5 KVA
6	6 KVA
6.5	6.5 KVA
7	7 KVA
7.5	7.5 KVA
8	8 KVA
9	9 KVA
10	10 KVA
12	12 KVA
15	15 KVA
18	18 KVA
20	20 KVA
24	24 KVA
25	25 KVA
26	26 KVA
28	28 KVA
30	30 KVA
34	34 KVA
35	35 KVA

(8) KVA	
37.5	37.5 KVA
40	40 KVA
45	45 KVA
50	50 KVA
60	60 KVA
70	70 KVA
75	75 KVA
80	80 KVA
90	90 KVA
100	100 KVA
112.5	112.5 KVA
125	125 KVA
150	150 KVA
167	167 KVA
200	200 KVA
225	225 KVA
250	250 KVA
300	300 KVA
350	350 KVA
400	400 KVA
450	450 KVA
500	500 KVA
750	750 KVA
1000	1000 KVA

(9) Secondary Phase	
D	3-Phase, Delta
Y	3-Phase, Wye
S	1-Phase
L	Low Voltage, AC
C	Low Voltage, DC
H	High Voltage DC
J	400 Hz, 1-Phase
K	400 Hz, 3-Phase, Delta
L	400 Hz, 3-Phase, Wye

(10) Secondary Voltage	
A	690V
B	660V
C	600V
D	575V
E	480V
F	460V
G	440V
H	420V
J	415V
K	400V
L	380V
ZA	347V
M	277V
N	250V
P	240V
Q	230V
R	220V
T	208V
U	200V
V	125V
W	120V
X	115V
Y	110V
Z	120/240V
LA	12V
LB	16V
LC	18V
LD	20V
LE	24V
LF	30V
LG	36V
LH	40V
LJ	48V
LK	50V
LL	60V
LM	72V
LN	80V
LP	100V
LQ	150V

SKU Example: MPD-CD2-309.60AB-DE75YT-LN-10.N10

MPD - **CD2** - **309.60AB** - **DE75YT** - **LN** - **2.L08** - **10.N10**

1
2
3
4
5
6
7
8
9
10
11
12
13
14
13
14

(11) Primary Main Breaker	
A	10
B	15
C	20
D	30
E	40
F	50
G	60
H	70
J	80
K	90
L	100
M	125
N	150
P	200
Q	225
R	250
T	300
U	350
V	400
W	450
X	600
Z	N/A

(12) Secondary Main Breaker	
A	10
B	15
C	20
D	30
E	40
F	50
G	60
H	70
J	80
K	90
L	100
M	125
N	150
P	200
Q	225
R	250
T	300
U	350
V	400
W	450
X	600
Z	N/A

(13) Receptacle Qty
1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40

(14) NEMA Straight Blade Receptacles	
N01	NEMA 1-15R
N02	NEMA 2-20R
N03	NEMA 5-15R
N04	NEMA 5-15R GFCI
N05	NEMA 5-15R Duplex
N06	NEMA 5-15R Duplex gfci
N07	NEMA 5-20R
N08	NEMA 5-20R GFCI
N09	NEMA 5-20R Duplex
N10	NEMA 5-20R Duplex GFCI
N11	NEMA 5-30R
N12	NEMA 5-50R
N13	NEMA 6-15R
N14	NEMA 6-15R Duplex
N15	NEMA 6-15R Duplex GFCI
N16	NEMA 6-20R
N17	NEMA 6-20R Duplex
N18	NEMA 6-20R Duplex GFCI
N19	NEMA 6-30R
N20	NEMA 6-50R
N21	NEMA 7-15R
N22	NEMA 7-20R
N23	NEMA 7-50R
N24	NEMA 10-20R
N25	NEMA 10-30R
N26	NEMA 10-50R
N27	NEMA 14-15R
N28	NEMA 14-20R
N29	NEMA 14-30R
N30	NEMA 14-50R
N31	NEMA 14-60R
N32	NEMA 15-15R
N33	NEMA 15-20R
N34	NEMA 15-30R
N35	NEMA 15-50R
N36	NEMA 15-60R
N37	NEMA 18-15R
N38	NEMA 18-20R
N39	NEMA 18-30R
N40	NEMA 18-50R
N41	NEMA 18-60R

(14) NEMA Twist Lock Receptacles	
L01	NEMA L1-15R
L02	NEMA L2-20R
L03	NEMA L5-15R
L04	NEMA L5-20R
L05	NEMA L5-30R
L06	NEMA L25-30R
L07	NEMA L6-15R
L08	NEMA L6-20R
L09	NEMA L6-30R
L10	NEMA L7-15R
L11	NEMA L7-20R
L12	NEMA L7-30R
L13	NEMA L24-20R
L14	NEMA L8-20R
L15	NEMA L8-30R
L16	NEMA L9-20R
L17	NEMA L9-30R
L18	NEMA L10-20R
L19	NEMA L10-30R
L20	NEMA L26-30R
L21	NEMA L14-20R
L22	NEMA L14-30R
L23	NEMA L15-20R
L24	NEMA L15-30R
L25	NEMA L16-20R
L26	NEMA L16-30R
L27	NEMA L17-30R
L28	NEMA L18-20R
L29	NEMA L18-30R
L30	NEMA L19-20R
L31	NEMA L19-30R
L32	NEMA L20-20R
L33	NEMA L20-30R
L34	NEMA L21-20R
L35	NEMA L21-30R
L36	NEMA L22-20R
L37	NEMA L22-30R
L38	NEMA L23-20R
L39	NEMA L23-30R

SKU Example: MPD-CD2-309.60AB-DE75YT-LN-10.N10

MPD - CD2 - 309.60AB - DE75YT - LN - 2.L08 - 10.N10

1 2 3 4 5 6 7 8 9 10 11 12 13 14 13 14

(14) NEMA Midget Twist Lock Receptacles	
L50	ML-1R
L51	ML-2R
L52	ML-3R

(14) NEMA FSL Twist Lock Receptacles	
L53	FSL1FR
L54	FSL2FR
L55	FSL3FR
L56	FSL4FR

(14) NEMA Ship-to-Shore Twist Lock Receptacles	
L57	SS1-50R
L58	SS2-50R

(14) NEMA Travel Trailer Straight Blade Receptacles	
N99	TT-30R

(14) California Standard 50A Twist Lock Receptacles	
C01	CS6370
C02	CS8269
C03	CS8469
C04	CS6369
C05	CS8369
C06	CS8169
C07	CS6360C
C08	CS8264C
C09	CS8464C
C10	CS6364C
C11	CS8364C
C12	CS8164C

(14) IEC 60309 IP67 Receptacles, North American Std.	
E01	320R4W
E02	320R6W
E03	320R7W
E04	420R12W
E05	420R9W
E06	420R7W
E07	420R5W
E08	520R9W
E09	520R7W
E10	520R5W
E11	330R4W
E12	330R6W
E13	330R7W
E14	430R12W
E15	430R9W
E16	430R7W
E17	430R5W
E18	530R9W
E19	530R7W
E20	530R5W
E21	360R4W
E22	360R6W
E23	360R7W
E24	460R12W
E25	460R9W
E26	460R7W
E27	460R5W
E28	560R9W
E29	560R7W
E30	560R5W
E31	3100R4W
E32	3100R6W
E33	3100R7W
E34	4100R12W
E35	4100R9W
E36	4100R7W
E37	4100R5W
E38	5100R9W
E39	5100R7W
E40	5100R5W

(14) IEC 60309 IP67 Receptacles, International Std.	
E71	316R4W
E72	316R6W
E73	416R6W
E74	516R6W
E75	332R6W
E76	432R6W
E77	432R3W
E78	532R6W
E79	363R6W
E80	463R6W
E81	563R6W
E82	3125R6W
E83	4125R6W
E84	5125R6W

(14) International Standard Receptacles	
K01	Schuko (Type E/F)
K02	BS1363 Type G
K03	AS3112 (Type I)
K04	Schuko (Type C)
K05	Schuko (Type E)
K06	Schuko (Type F)
K07	SI32 (Type H)
K08	SEV1011 T13 (Type J)
K09	SEV1011 T23 (Type J)
K10	CEI 23-50 10A (Type L)
K11	CEI 23-50 16A (Type L)
K12	BS546 6A (Type D)
K13	BS546 16A (Type M)
K14	NBR14136 10A (Type N)
K15	NBR14136 20A (Type N)

(14) UL 1686 Receptacles, Style I	
U01	330RS1W
U02	430RS1W
U03	530RS1W
U04	360RS1W
U05	460RS1W
U06	560RS1W
U07	3100RS1W
U08	4100RS1W
U09	5100RS1W
U10	4150RS1W
U11	4200RS1W
U12	5200RS1W

(14) UL 1686 Receptacles, Style II	
U13	330RS2W
U14	430RS2W
U15	360RS2W
U16	460RS2W
U17	3100RS2W
U18	4100RS2W
U19	4150RS2W
U20	3200RS2W
U21	4200RS2W

(14) UL 1686 Receptacles, Style I, Corrosion Resistant	
U22	M5200RS1

(14) UL 1686 Receptacles, Style I, Reverse Service	
U23	330RS1WR
U24	430RS1WR
U25	530RS1WR
U26	360RS1WR
U27	460RS1WR
U28	560RS1WR
U29	3100RS1WR
U30	4100RS1WR
U31	5100RS1WR
U32	4150RS1WR
U33	4200RS1WR
U34	5200RS1WR

Dolly Carts

Larson Electronics portable power distribution systems on dolly carts provide voltage rectification, extend power connections and protect equipment in remote sites with limited access to infrastructure. To enhance mobility, all system components, such as transformers, panels, receptacles, breakers and cords, are secured to a steel, dolly cart style frame. Two run-flat tires enable movement around the work site. A curved, top-located handle offers seamless control during transportation, allowing deployment to be carried out by a single person. A center-point lifting eye can be accessed for lifting with cables or chain hooks. Standard power distribution stations on dolly carts feature a polyester powder coated blue finish for durability in rugged outdoor locations. This TGIC coating offers protection from bumps, scratches, sunlight, corrosion and moisture.

An accessible weatherproof flip cover with a handle (located at the front of the unit) protects primary/secondary breakers and receptacles from damage, debris, moisture and tampering. This flip cover can be locked in an open position when accessing system components. To achieve a NEMA 3R rating, the panels on these power distribution units come with a drain plug. Protecting the transformer and exterior jacket of wiring components are vibration isolators, which are also found on the breakers. Vibration isolators reduce noise during operation and prevents loose bolts.



UL 1640

BENEFITS

- All system components mounted on portable dolly cart
- NEMA 3R rated for indoor or outdoor use
- Top-located handle, two run-flat tires & center-point lifting eye
- Powder coated finish
- Weatherproof flip cover
- Vibration isolators
- Customization available



SKU	Pri. Volts	Pri. Ø	Sec. Volts	Sec. Ø	KVA	Input Plug	Input Cord	Pri. Recpt.	Sec. Recpt.
MPD-CD1-309B-SR10SY-GB-8.E71	220V	1PH	110V	1PH	10	363P6W	20'	N/A	(8) 316R4W
MPD-CD1-309.125AB-SQ20SP-ZDC-1.L22-1.N07-M2	230V	1PH	120/240V	1PH	20	3125P6W	25'	N/A	(1) L14-30R, (1) 5-20R
MPD-CD1-BSB-SP7.5SW-EZ-4.N10-M1	240V	1PH	120V	1PH	7.5	N/A	20'	N/A	(4) 5-20R
MPD-CD1-BSB-SZA15SP-EZ-1.C04-1.N20-3.N10-M1	347V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SZA15SP-EZ-2.L09-10.N10-M1	347V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SZA15SP-EZ-3.N10-1.N20-M1	347V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-BSB-SZA25SV-GZ-8.L05-2.L04-M1	347V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD1-BSB-SL15SP-EZ-1.C04-1.N20-3.N10-M1	380V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SL15SP-EZ-2.L09-10.N10-M1	380V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SL15SP-EZ-3.N10-1.N20-M1	380V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-BSB-SL25SV-GZ-8.L05-2.L04-M1	380V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD1-BSB-SK15SP-EZ-1.C04-1.N20-3.N10-M1	400V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SK15SP-EZ-2.L09-10.N10-M1	400V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SK15SP-EZ-3.N10-1.N20-M1	400V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-BSB-SK25SV-GZ-8.L05-2.L04-M1	400V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD1-BSB-SJ15SP-EZ-1.C04-1.N20-3.N10-M1	415V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SJ15SP-EZ-2.L09-10.N10-M1	415V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SJ15SP-EZ-3.N10-1.N20-M1	415V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-BSB-SJ25SV-GZ-8.L05-2.L04-M1	415V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD1-BSB-SH15SP-EZ-1.C04-1.N20-3.N10-M1	420V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SH15SP-EZ-2.L09-10.N10-M1	420V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SH15SP-EZ-3.N10-1.N20-M1	420V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-BSB-SH25SV-GZ-8.L05-2.L04-M1	420V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD1-BSB-SG15SP-EZ-1.C04-1.N20-3.N10-M1	440V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SG15SP-EZ-2.L09-10.N10-M1	440V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SG15SP-EZ-3.N10-1.N20-M1	440V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-BSB-SG25SV-GZ-8.L05-2.L04-M1	440V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD1-BSB-SG15SP-EZ-2.L09-M1	440V	1PH	220V	3PH	15	N/A	25'	N/A	(2) L6-30R
MPD-CD1-BSB-SF15SP-EZ-1.C04-1.N20-3.N10-M1	460V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SF15SP-EZ-2.L09-10.N10-M1	460V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SF15SP-EZ-3.N10-1.N20-M1	460V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-BSB-SF25SV-GZ-8.L05-2.L04-M1	460V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD1-BSB-SE15SP-EZ-1.C04-1.N20-3.N10-M1	480V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SE15SP-EZ-2.L09-10.N10-M1	480V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SE15SP-EZ-3.N10-1.N20-M1	480V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-NTL.50AB-SE15SP-EG-1.C13-1.C04-M1	480V	1PH	120/240V	1PH	15	CS6369	N/A	N/A	(1) CS6369
MPD-CD5-NTL.30AB-SE15SP-1.CG-1.C02-2.N09-M1	480V	1PH	120/240V	1PH	15	L16-30P	25'	N/A	(1) CS8269, (2) 5-20R
MPD-CD1.SS-ZB-SE25SP-GL-10.L03-2.L09	480V	1PH	120/240V	1PH	25	N/A	N/A	N/A	(2) L6-30R, (10) L5-15R
MPD-CD1-BSB-SE25SV-GZ-8.L05-2.L04-M1	480V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD1-BSB-SE5SW-BZ-3.N06-M1	480V	1PH	120V	1PH	5	N/A	10'	N/A	(3) 5-15R
MPD-CD4-BSB-SE30SV-HZ-8.L05-2.L04-M1	480V	1PH	120V	1PH	30	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD5-NTL.30AB-SE15SP-ZG-1.C02-M1	480V	1PH	240V	1PH	15	L16-30P	25'	N/A	(1) CS8269

SKU	Pri. Volts	Pri. Ø	Sec. Volts	Sec. Ø	KVA	Input Plug	Input Cord	Pri. Recpt.	Sec. Recpt.
MPD-CD1-BSMTS-SE15SP-EG-1.C02-1.L09-6.N10-M1	480V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS8269, (1) L6-30R, (6) 5-20R
MPD-CD1-BSB-SD15SQ-DZ-1.L09-2.N06-M1	575V	1PH	115/230V	1PH	15	N/A	275'	N/A	(1) L6-30R, (2) 5-20R
MPD-CD1-BSB-SD15SP-EZ-1.C04-1.N20-3.N10-M1	575V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SD15SP-EZ-2.L09-10.N10-M1	575V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SD15SP-EZ-3.N10-1.N20-M1	575V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-BSB-SD25SV-GZ-8.L05-2.L04-M1	575V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD1-BSB-SC15SP-EZ-1.C04-1.N20-3.N10-M1	600V	1PH	120/240V	1PH	15	N/A	10'	N/A	(1) CS6369, (1) 6-30R, (3) 5-20R
MPD-CD1-BSB-SC15SP-EZ-2.L09-10.N10-M1	600V	1PH	120/240V	1PH	15	N/A	25'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD1-BSB-SC15SP-EZ-3.N10-1.N20-M1	600V	1PH	120/240V	1PH	15	N/A	10'	N/A	(2) 6-50R, (3) 5-20R
MPD-CD1-BSB-SC25SV-GZ-8.L05-2.L04-M1	600V	1PH	120/240V	1PH	25	N/A	25'	N/A	(8) L5-30R, (2) L5-20R
MPD-CD2-BSB-SC25SP-GZ-2.L09-12.N10-M1	600V	1PH	120/240V	1PH	25	N/A	50'	N/A	(2) L6-30R, (12) 5-20R
MPD-CD5-BSB-DT6YL-CZ-BS-M1	208V	3PH	380Y/220	3PH	6	N/A	20'	N/A	N/A
MPD-CD1-BSB-DK25SP-JZ-1.C02-6.N10-M1	400V	3PH	120/240V	1PH	25	N/A	20'	N/A	(1) CS8269, (6) 5
MPD-CD2-BSB-50.DJ30SP.60-ZZ-2.L09-6.N07-M1	415V	3PH	120/240V	1PH	30	N/A	25'	N/A	(2) L6-30R, (6) 5-20R
MPD-CD1-BSB-DJ15YT-DC2-M1	415V	3PH	208Y/120	3PH	15	N/A	25'	N/A	N/A
MPD-CD1-BSB-DE9YT-BZ-2.L24-6.N10-M1	480V	3PH	120/240V	1PH	9	N/A	20'	N/A	(6) 5-20R, (2) L15-30R
MPD-CD2-86B-DE37SP-L-3.N09-2.L05-3.L08-1.L09-1.C02	480V	3PH	120/240V	1PH	37.5	100A 3W4P (UL 1686)	20'	N/A	(1) CS8269, (1) L6-30R, (3) L6-20R, (2) L5-30R, (3) 5-20R
MPD-CD3-86B-DE45SP-L-3.N09-2.L05-3.L08-1.L09-1.C02	480V	3PH	120/240V	1PH	45	100A 3W4P (UL 1686)	20'	N/A	(1) CS8269, (1) L6-30R, (3) L6-20R, (2) L5-30R, (3) 5-20R
MPD-CD1-309.100AF-DE15YT-LZ-5.S10-1.D13-M1	480V	3PH	208Y/120	3PH	15	4100B7W	N/A	(1) CS8169	(1) DN20c
MPD-CD1-BSB-DE15YT-CF-10.N06	480V	3PH	208Y/120	3PH	15	N/A	25'	N/A	(10) 5-15R
MPD-CD1-BSB-DE15YT-CF-20.N10	480V	3PH	208Y/120	3PH	15	N/A	25'	N/A	(20) 5-20R
MPD-CD1-BSB-DE15YT-DG-12.N10-M1	480V	3PH	208Y/120	3PH	15	N/A	20'	N/A	(12) 5-20R
MPD-CD1-BSB-DE20YT-DZ-2.L24-1.N09-M1	480V	3PH	208Y/120	3PH	20	N/A	15'	N/A	(2) L15-30R, (1) 5-20R
MPD-CD2-309.60AB-DE30YT-FZ-4.C04-M1	480V	3PH	208Y/120	3PH	30	460P7W	20'	N/A	(4) CS6369
MPD-CD2-BSB-DE30YT-EZ-24.N10-M1	480V	3PH	208Y/120	3PH	30	N/A	20'	N/A	(24) 5-20R
MPD-CD2-BSB-DE30YT-FL-2.L09-10.N10-M1	480V	3PH	208Y/120	3PH	30	N/A	20'	N/A	(2) L6-30R, (10) 5-20R
MPD-CD2-CLPF-DE30YT-FG-CLP-M1	480V	3PH	208Y/120	3PH	30	15 Series Cam- locks	N/A	N/A	16 Series Camlocks
MPD-CD2-CSB-DE30YT-FL-2.L22-10.N10-M1	480V	3PH	208Y/120	3PH	30	CS8165C	20'	N/A	(2) L14-30R, (10) 5-20R
MPD-CD3-BSB-DE30YT-LZ-6.L21-M1	480V	3PH	208Y/120	3PH	30	N/A	25'	N/A	(6) L14-20R
MPD-CD2-BSB-DE45YT-GZ-2.L24-6.N10-M1	480V	3PH	208Y/120	3PH	45	N/A	20'	N/A	(6) 5-20R, (2) L15-30R
MPD-CD2-BSB-DE45YT-HZ-20.N10-M1	480V	3PH	208Y/120	3PH	45	N/A	20'	N/A	(20) 5-20R
MPD-CD2-BSB-DE45YT-HZ-4.N10-M1	480V	3PH	208Y/120	3PH	45	N/A	20'	N/A	(4) 5-20R
MPD-CD1-BSB-DF15DQ-DF-1.C05-2.C02-12.N07-M1	480V	3PH	230V/115	3PH	15	L16-30R	25'	N/A	(1) CS8369, (6) 5-20R
MPD-CD2-NTL.30AB-DE30DP-ZZ-2.E92-2.L09-8.N10-M1	480V	3PH	240V/120	3PH	30	L16-30P	25'	N/A	(2) 460R9W, (2) L6-30R, (8) 5-20R
MPD-CD2-BSF-YE45YT-GC-12.N10-M1	480Y/277	3PH	208Y/120	3PH	45	N/A	150'	(1) 520R7W	(1) 4100R12W, (1) 530R9W, (12) 5-20R
MPD-CD1-BSB-SD15SQ-DZ-1.L09-2.N06-M2	575V	3PH	115/230V	1PH	15	N/A	5'	N/A	(1) L6-30R, (2) 5-20R
MPD-CD1-BSB-DC15YT-CC10-10.N10	600V	3PH	208Y/120	3PH	15	N/A	25'	N/A	(10) 5-20R

Cube Carts

Larson Electronics portable power distribution systems on cube carts provide voltage rectification, extend power connections and protect equipment in remote sites with limited access to infrastructure. All system components, such as transformers, panels, receptacles, breakers and cords, are enclosed and secured on a cube-style frame. Four locking casters enable movement around the work site. A curved, side-located handle offers seamless control during transportation, allowing deployment to be carried out by a single person. Skid pockets and four lifting eyes facilitate lifting with forklifts, cables or chain hooks. Standard power distribution stations on cube carts feature a polyester powder coated blue finish for durability in rugged outdoor locations. This TGIC coating offers protection from bumps, scratches, sunlight, corrosion and moisture.

Steel walls provide protection for system components in industrial environments. The walls are ventilated to promote natural cooling. Four lockable doors (two on each side) provide access to system components. Breakers are accessible on one side of the mobile station, while primary/secondary receptacles are available on the other side. Openings at the bottom of the receptacle enclosure allow operators to pass cords and wiring under the frame for organized and safe operation. Breakers and receptacles are labeled to prevent wrong connections.



UL 1640

BENEFITS

- All system components mounted inside an enclosed cube-style frame
- NEMA 3R rated for indoor or outdoor use
- Side-located handle, four locking casters, skid pockets and four lifting eyes
- Powder coated finish
- Separate breaker and receptacle enclosures
- Customization available



Spider Boxes

Larson Electronics portable spider boxes extend power connections and protect equipment in remote sites with limited access to infrastructure. All system components, such as receptacles with weatherproof covers, inlets and breakers, are secured on a compact, heavy-duty enclosure. Standard units feature a bright yellow finish for high visibility in rugged outdoor locations. Models with angled legs are recommended for keeping the power distribution devices above ground or stable on uneven, rough surfaces. Constructed of steel, our temporary spider boxes offer overload, short circuit, open neutral, reverse phasing and GFCI protection. Should circuit overload occur, the power distribution device automatically turns off to preserve the unit. These industrial spider boxes are NEMA 3R rated for use in both indoor and outdoor locations, as well as approved for wet locations.

BENEFITS

- All system components secured inside a steel, compact enclosure
- NEMA 3R rated for indoor or outdoor use, approved for wet locations
- Angled legs
- Safety yellow finish
- Overload, short circuit, open neutral, reverse phasing and GFCI protection
- Customization available



Mini PDU

Larson Electronics mini power distribution devices extend power connections and protect equipment in remote sites with limited access to infrastructure. All system components, such as receptacles with weatherproof covers, camlocks, inlets and breakers, are secured on a compact, heavy-duty enclosure. A flat or padded base ensures stability during use. Devices with a top-located handle allows operators to carry the device around work sites. This feature doubles as a cord wrap for space-saving storage.

Standard units feature a glossy blue, polyester powder coated finish for durability in rugged outdoor locations. This TGIC coating offers protection from bumps, scratches, sunlight, corrosion and moisture. Mini power distribution units with a bright yellow finish offer high visibility in work sites. Constructed of steel, our temporary spider boxes come with overload, short circuit, open neutral, reverse phasing and GFCI protection (depends on selected model). Should circuit overload occur, the power distribution device automatically turns off. These industrial units are NEMA 3R rated for use in both indoor and outdoor locations.



BENEFITS

- All system components secured inside a steel, compact enclosure
- NEMA 3R rated for indoor or outdoor use
- Flat or padded base
- Safety yellow or standard blue powder coated finish
- Automatically turns off upon sensing circuit overload
- Customization available

Trailer Mount Power Distribution



and reliable access to power systems in remote locations. These power stations are mounted to a heavy-duty trailer with wheels for seamless transportation and deployment around work sites. Bottom-located skid pockets and 4-corner pick eyes, which allows easy lifting with cable or chain hooks, are also available as alternative transport options. System components, such as the transformer, panel, receptacles and circuit breakers, are protected by an enclosure and are accessible via hinged wing doors. The doors “wing” in an upward direction and can be used in tight spaces when powering equipment and machines at the outdoor site. For storing power cords and tools, operators may access side-located troffers on the unit. Standard trailer mount power distribution stations feature a powder coated finish for durability in rugged locations. This TGIC coating offers protection from bumps, scratches, sunlight, corrosion and moisture.





BENEFITS

- All power distribution stations mounted to a trailer for portability
- Heavy-duty wheels promote mobility around remote sites
- Bottom-located skid pockets and 4-corner pick eyes
- Enclosure protects system components from outdoor elements
- Hinged wing doors promote access in tight spaces
- Powder coated finish offers long-term protection
- Customization available





Extension Cords

Larson Electronics standard extension cords ensure access to out-of-reach power sources in industrial locations. These heavy-duty power accessories can be used with the power distribution products in this catalog, as well as with compatible equipment at job sites. Our flexible extension cords are offered in various AWG ratings to match amperage, circuit type or length requirements. For increased reliability in rugged facilities, our SOOW extension cords are resistant to water, extreme temperatures, oil, debris and sunlight. The selection of industrial extension cables in this catalog are rated up to 600 volts and can be used to comply with safety standards.

BENEFITS

- **AWG rated, copper wiring**
- **Indoor or outdoor applications**
- **Suitable for use with Larson Electronics power distribution systems**
- **Customization available**



NEMA Straight Blade Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-16.3-13A-5.15	125V	1PH	2P3W	5-15P	5-15C	13A	16/3
EXC-*-14.3-15A-5.15	125V	1PH	2P3W	5-15P	5-15C	15A	14/3
EXC-*-12.3-15A-5.15	125V	1PH	2P3W	5-15P	5-15C	15A	12/3
EXC-*-12.3-20A-5.20	125V	1PH	2P3W	5-20P	5-20C	20A	12/3
EXC-*-10.3-30A-5.30	125V	1PH	2P3W	5-30P	5-30C	30A	10/3
EXC-*-6.3-50A-5.50	125V	1PH	2P3W	5-50P	5-50R	50A	8/3
EXC-*-16.3-13A-6.15	250V	1PH	2P3W	6-15P	6-15C	13A	16/3
EXC-*-14.3-15A-6.15	250V	1PH	2P3W	6-15P	6-15C	15A	14/3
EXC-*-12.3-15A-6.15	250V	1PH	2P3W	6-15P	6-15C	15A	12/3
EXC-*-12.3-20A-6.20	250V	1PH	2P3W	6-20P	6-20C	20A	12/3
EXC-*-10.3-30A-6.30	250V	1PH	2P3W	6-30P	6-30C	30A	10/3
EXC-*-6.3-50A-6.50	250V	1PH	2P3W	6-50P	6-50R	50A	8/3
EXC-*-14.3-15A-7.15	277V	1PH	2P3W	7-15P	7-15C	15A	14/3
EXC-*-12.3-15A-7.15	277V	1PH	2P3W	7-15P	7-15C	15A	12/3
EXC-*-12.3-20A-7.20	277V	1PH	2P3W	7-20P	7-20C	20A	12/3
EXC-*-10.3-30A-7.30	277V	1PH	2P3W	7-30P	7-30C	30A	10/3
EXC-*-6.3-50A-7.50	277V	1PH	3P3W	7-50P	7-50R	50A	8/3
EXC-*-12.4-20A-10.20	125/250V	1PH	3P3W	10-20P	10-20C	20A	12/4
EXC-*-10.4-30A-10.30	125/250V	1PH	3P3W	10-30P	10-30C	30A	10/4
EXC-*-6.4-50A-10.50	125/250V	1PH	3P3W	10-50P	10-50R	50A	8/4
EXC-*-14.4-15A-14.15	125/250V	1PH	3P4W	14-15P	14-15C	15A	14/4
EXC-*-12.4-15A-14.15	125/250V	1PH	3P4W	14-15P	14-15C	15A	12/4
EXC-*-12.4-20A-14.20	125/250V	1PH	3P4W	14-20P	14-20C	20A	12/4
EXC-*-10.4-30A-14.30	125/250V	1PH	3P4W	14-30P	14-30C	30A	10/4
EXC-*-6.4-50A-14.50	125/250V	1PH	3P4W	14-50P	14-50R	50A	8/4
EXC-*-15.4-15A-15.15	250V	3PH	3P4W	15-15P	15-15C	15A	14/4
EXC-*-12.4-15A-15.15	250V	3PH	3P4W	15-15P	15-15C	15A	12/4
EXC-*-12.4-20A-15.20	250V	3PH	3P4W	15-20P	15-20C	20A	12/4
EXC-*-10.4-30A-15.30	250V	3PH	3P4W	15-30P	15-30C	30A	10/4
EXC-*-6.4-50A-15.50	250V	3PH	3P4W	15-50P	15-50R	50A	8/4

*Replace * with desired cord length*

NEMA Twist Lock Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-16.3-13A-L5.15	125V	1PH	2P3W	L5-15P	L5-15C	13A	16/3
EXC-*-14.3-15A-L5.15	125V	1PH	2P3W	L5-15P	L5-15C	15A	14/3
EXC-*-12.3-15A-L5.15	125V	1PH	2P3W	L5-15P	L5-15C	15A	12/3
EXC-*-12.3-20A-L5.20	125V	1PH	2P3W	L5-20P	L5-20C	20A	12/3
EXC-*-10.3-30A-L5.30	125V	1PH	2P3W	L5-30P	L5-30C	30A	10/3
EXC-*-16.3-13A-L6.15	250V	1PH	2P3W	L6-15P	L6-15C	13A	16/3
EXC-*-14.3-15A-L6.15	250V	1PH	2P3W	L6-15P	L6-15C	15A	14/3
EXC-*-12.3-15A-L6.15	250V	1PH	2P3W	L6-15P	L6-15C	15A	12/3
EXC-*-12.3-20A-L6.20	250V	1PH	2P3W	L6-20P	L6-20C	20A	12/3
EXC-*-10.3-30A-L6.30	250V	1PH	2P3W	L6-30P	L6-30C	30A	10/3
EXC-*-14.3-15A-L7.15	277V	1PH	2P3W	L7-15P	L7-15C	15A	14/3
EXC-*-12.3-15A-L7.15	277V	1PH	2P3W	L7-15P	L7-15C	15A	12/3
EXC-*-12.3-20A-L7.20	277V	1PH	2P3W	L7-20P	L7-20C	20A	12/3
EXC-*-10.3-30A-L7.30	277V	1PH	2P3W	L7-30P	L7-30C	30A	10/3
EXC-*-12.3-20A-L24.20	347V	1PH	2P3W	L24-20P	L24-20C	20A	12/3
EXC-*-12.3-20A-L8.20	480V	1PH	2P3W	L8-20P	L8-20C	20A	12/3
EXC-*-10.3-30A-L8.30	480V	1PH	2P3W	L8-30P	L8-30C	30A	10/3
EXC-*-12.3-20A-L9.20	600V	1PH	2P3W	L9-20P	L9-20C	20A	12/3
EXC-*-10.3-30A-L9.30	600V	1PH	2P3W	L9-30P	L9-30C	30A	10/3
EXC-*-12.4-20A-L10.20	125/250V	1PH	3P3W	L10-20P	L10-20C	20A	12/4
EXC-*-10.4-30A-L10.30	125/250V	1PH	3P3W	L10-30P	L10-30C	30A	10/4
EXC-*-12.4-20A-L14.20	125/250V	1PH	3P4W	L14-20P	L14-20C	20A	12/4
EXC-*-10.4-30A-L14.30	125/250V	1PH	3P4W	L14-30P	L14-30C	30A	10/4
EXC-*-12.4-20A-L15.20	250V	3PH	3P4W	L15-20P	L15-20C	20A	12/4
EXC-*-10.4-30A-L15.30	250V	3PH	3P4W	L15-30P	L15-30C	30A	10/4
EXC-*-12.4-20A-L16.20	480V	3PH	3P4W	L16-20P	L16-20C	20A	12/4
EXC-*-10.4-30A-L16.30	480V	3PH	3P4W	L16-30P	L16-30C	30A	10/4
EXC-*-10.4-30A-L17.30	600V	3PH	3P4W	L17-30P	L17-30C	30A	10/4
EXC-*-12.5-20A-L18.20	208Y/120	3PH	4P4W	L18-20P	L18-20C	20A	12/5
EXC-*-10.5-30A-L18.30	208Y/120	3PH	4P4W	L18-30P	L18-30C	30A	10/5
EXC-*-12.5-20A-L19.20	480Y/277	3PH	4P4W	L19-20P	L19-20C	20A	12/5
EXC-*-10.5-30A-L19.30	480Y/277	3PH	4P4W	L19-30P	L19-30C	30A	10/5
EXC-*-12.5-20A-L20.20	600Y/347	3PH	4P4W	L20-20P	L20-20C	20A	12/5
EXC-*-10.5-30A-L20.30	600Y/347	3PH	4P4W	L20-30P	L20-30C	30A	10/5
EXC-*-12.5-20A-L21.20	208Y/120	3PH	4P4W	L21-20P	L21-20C	20A	12/5
EXC-*-10.5-30A-L21.30	208Y/120	3PH	4P4W	L21-30P	L21-30C	30A	10/5
EXC-*-12.5-20A-L22.20	480Y/277	3PH	4P4W	L22-20P	L22-20C	20A	12/5
EXC-*-10.5-30A-L22.30	480Y/277	3PH	4P4W	L22-30P	L22-30C	30A	10/5
EXC-*-12.5-20A-L23.20	600Y/347	3PH	4P4W	L23-20P	L23-20C	20A	12/5
EXC-*-10.5-30A-L23.30	600Y/347	3PH	4P4W	L23-30P	L23-30C	30A	10/5

Replace * with desired cord length

NEMA Straight Blade Weatherproof Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*.16.3-13A-5.15-WP	125V	1PH	2P3W	5-15P	5-15C	13A	16/3
EXC-*.14.3-15A-5.15-WP	125V	1PH	2P3W	5-15P	5-15C	15A	14/3
EXC-*.12.3-15A-5.15-WP	125V	1PH	2P3W	5-15P	5-15C	15A	12/3
EXC-*.12.3-20A-5.20-WP	125V	1PH	2P3W	5-20P	5-20C	20A	12/3
EXC-*.16.3-13A-6.15-WP	250V	1PH	2P3W	6-15P	6-15C	13A	16/3
EXC-*.14.3-15A-6.15-WP	250V	1PH	2P3W	6-15P	6-15C	15A	14/3
EXC-*.12.3-15A-6.15-WP	250V	1PH	2P3W	6-15P	6-15C	15A	12/3
EXC-*.12.3-20A-6.20-WP	250V	1PH	2P3W	6-20P	6-20C	20A	12/3

Replace * with desired cord length

NEMA Twist Lock Weatherproof Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*.16.3-13A-L5.15-WP	125V	1PH	2P3W	L5-15P	L5-15C	13A	16/3
EXC-*.14.3-15A-L5.15-WP	125V	1PH	2P3W	L5-15P	L5-15C	15A	14/3
EXC-*.12.3-15A-L5.15-WP	125V	1PH	2P3W	L5-15P	L5-15C	15A	12/3
EXC-*.12.3-20A-L5.20-WP	125V	1PH	2P3W	L5-20P	L5-20C	20A	12/3
EXC-*.10.3-30A-L5.30-WP	125V	1PH	2P3W	L5-30P	L5-30C	30A	10/3
EXC-*.16.3-13A-L6.15-WP	250V	1PH	2P3W	L6-15P	L6-15C	13A	16/3
EXC-*.14.3-15A-L6.15-WP	250V	1PH	2P3W	L6-15P	L6-15C	15A	14/3
EXC-*.12.3-15A-L6.15-WP	250V	1PH	2P3W	L6-15P	L6-15C	15A	12/3
EXC-*.12.3-20A-L6.20-WP	250V	1PH	2P3W	L6-20P	L6-20C	20A	12/3
EXC-*.10.3-30A-L6.30-WP	250V	1PH	2P3W	L6-30P	L6-30C	30A	10/3
EXC-*.14.3-15A-L7.15-WP	277V	1PH	2P3W	L7-15P	L7-15C	15A	14/3
EXC-*.12.3-15A-L7.15-WP	277V	1PH	2P3W	L7-15P	L7-15C	15A	12/3
EXC-*.12.3-20A-L7.20-WP	277V	1PH	2P3W	L7-20P	L7-20C	20A	12/3
EXC-*.10.3-30A-L7.30-WP	277V	1PH	2P3W	L7-30P	L7-30C	30A	10/3
EXC-*.12.4-20A-L14.20-WP	125/250V	1PH	3P4W	L14-20P	L14-20C	20A	12/4
EXC-*.10.4-30A-L14.30-WP	125/250V	1PH	3P4W	L14-30P	L14-30C	30A	10/4
EXC-*.12.4-20A-L15.20-WP	250V	3PH	3P4W	L15-20P	L15-20C	20A	12/4
EXC-*.10.4-30A-L15.30-WP	250V	3PH	3P4W	L15-30P	L15-30C	30A	10/4
EXC-*.12.4-20A-L16.20-WP	480V	3PH	3P4W	L16-20P	L16-20C	20A	12/4
EXC-*.10.4-30A-L16.30-WP	480V	3PH	3P4W	L16-30P	L16-30C	30A	10/4
EXC-*.10.4-30A-L17.30-WP	600V	3PH	3P4W	L17-30P	L17-30C	30A	10/4
EXC-*.10.5-30A-L18.30-WP	208Y/120	3PH	4P4W	L18-30P	L18-30C	30A	10/5
EXC-*.12.5-20A-L21.20-WP	208Y/120	3PH	4P4W	L21-20P	L21-20C	20A	12/5
EXC-*.10.5-30A-L21.30-WP	208Y/120	3PH	4P4W	L21-30P	L21-30C	30A	10/5

Replace * with desired cord length

NEMA Ship-to-Shore 50A Twist Lock Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-6.3-50A-SS1.50-125V	125V	1PH	2P3W	SS1-50P	SS1-50C	50A	6/3
EXC-*-4.3-50A-SS1.50-125V	125V	1PH	2P3W	SS1-50P	SS1-50C	50A	4/3
EXC-*-6.4-50A-SS2.50-125.250V	120/250V	1PH	3P4W	SS2-50P	SS2-50C	50A	6/3
EXC-*-4.4-50A-SS2.50-125.250V	120/250V	1PH	3P4W	SS2-50P	SS2-50C	50A	4/3

*Replace * with desired cord length*

NEMA Travel Trailer Straight Blade Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-10.3-30A-TT.30-125V	125V	1PH	2P3W	TT-30P	TT-30R	30A	10/3

*Replace * with desired cord length*

NEMA Midget Twist Lock Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-16.3-13A-ML.1-125V	125V	1PH	2P3W	ML-1P	ML-1C	13A	16/3
EXC-*-14.3-15A-ML.1-125V	125V	1PH	2P3W	ML-1P	ML-1C	15A	14/3
EXC-*-12.3-15A-ML.1-125V	125V	1PH	2P3W	ML-1P	ML-1C	15A	12/3
EXC-*-12.3-20A-ML.2-125V	125V	1PH	2P3W	ML-2P	ML-2C	20A	12/3
EXC-*-12.3-30A-ML.3-125V	125V	1PH	2P3W	ML-3P	ML-3C	30A	10/3

*Replace * with desired cord length*

NEMA 400 Hz Twist Lock Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-10.3-30A-FSL1-28VDC	28V	DC	2P3W	FSL1NP	FSL1NC	30A	10/3
EXC-*-10.3-30A-FSL2-120V.400HZ	120V	1PH (400 HZ)	2P3W	FSL2NP	FSL2NC	30A	10/3
EXC-*-10.4-30A-FSL3-120V.400HZ	120V	3PH (400 HZ)	3P4W	FSL3NP	FSL3NC	30A	10/4
EXC-*-10.5-30A-FSL4-208Y.120.400HZ	208Y/120	3PH (400 HZ)	4P5W	FSL4NP	FSL4NC	30A	10/5

*Replace * with desired cord length*

California Standard 50A Twist Lock Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-6.3-50A-CS63-125V	125V	1PH	2P3W	CS6361C	CS6360C	50A	6/3
EXC-*-4.3-50A-CS63-125V	125V	1PH	2P3W	CS6361C	CS6360C	50A	4/3
EXC-*-6.3-50A-CS82-250V	250V	1PH	2P3W	CS8265C	CS8264C	50A	6/3
EXC-*-4.3-50A-CS82-250V	250V	1PH	2P3W	CS8265C	CS8264C	50A	4/3
EXC-*-6.3-50A-CS84-480V	480V	1PH	2P3W	CS8465C	CS8464C	50A	6/3
EXC-*-4.3-50A-CS84-480V	480V	1PH	2P3W	CS8465C	CS8464C	50A	4/3
EXC-*-6.3-50A-CS63-125.250V	125/250V	1PH	3P4W	CS6365C	CS6364C	50A	6/4
EXC-*-4.3-50A-CS63-125.250V	125/250V	1PH	3P4W	CS6365C	CS6364C	50A	4/4
EXC-*-6.3-50A-CS83-250V	250V	3PH	3P4W	CS8365C	CS8364C	50A	6/4
EXC-*-4.3-50A-CS83-250V	250V	3PH	3P4W	CS8365C	CS8364C	50A	4/4
EXC-*-6.3-50A-CS81-480V	480V	3PH	3P4W	CS8165C	CS8164C	50A	6/4
EXC-*-4.3-50A-CS81-480V	480V	3PH	3P4W	CS8165C	CS8164C	50A	4/4

*Replace * with desired cord length*

IEC 60309 Pin/Sleeve IP67 Waterproof Extension Cords (North American Standard)

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-20A-IP67-309.NA-1PH-125V-2P3W	125V	1PH	2P3W	320P4W	320C4W	20A	12/3
EXC-*-30A-IP67-309.NA-1PH-125V-2P3W	125V	1PH	2P3W	330P4W	330C4W	30A	10/3
EXC-*-60A-IP67-309.NA-1PH-125V-2P3W	125V	1PH	2P3W	360P4W	360C4W	60A	4/3
EXC-*-100A-IP67-309.NA-1PH-125V-2P3W	125V	1PH	2P3W	3100P4W	3100C4W	100A	4/3
EXC-*-20A-IP67-309.NA-1PH-250V-2P3W	250V	1PH	2P3W	320P6W	320C6W	20A	12/3
EXC-*-30A-IP67-309.NA-1PH-250V-2P3W	250V	1PH	2P3W	330P6W	330C6W	30A	10/3
EXC-*-60A-IP67-309.NA-1PH-250V-2P3W	250V	1PH	2P3W	360P6W	360C6W	60A	4/3
EXC-*-100A-IP67-309.NA-1PH-250V-2P3W	250V	1PH	2P3W	3100P6W	3100C6W	100A	4/3
EXC-*-20A-IP67-309.NA-1PH-480V-2P3W	480V	1PH	2P3W	320P7W	320C7W	20A	12/3
EXC-*-30A-IP67-309.NA-1PH-480V-2P3W	480V	1PH	2P3W	330P7W	330C7W	30A	10/3
EXC-*-60A-IP67-309.NA-1PH-480V-2P3W	480V	1PH	2P3W	360P7W	360C7W	60A	4/3
EXC-*-100A-IP67-309.NA-1PH-480V-2P3W	480V	1PH	2P3W	3100P7W	3100C7W	100A	4/3
EXC-*-20A-IP67-309.NA-1PH-125.250V-3P4W	125/250V	1PH	3P4W	420P12W	420C12W	20A	12/4
EXC-*-30A-IP67-309.NA-1PH-125.250V-3P4W	125/250V	1PH	3P4W	430P12W	430C12W	30A	10/4
EXC-*-60A-IP67-309.NA-1PH-125.250V-3P4W	125/250V	1PH	3P4W	460P12W	460C12W	60A	4/4
EXC-*-100A-IP67-309.NA-1PH-125.250V-3P4W	125/250V	1PH	3P4W	4100P12W	4100C12W	100A	4/4
EXC-*-20A-IP67-309.NA-3PH-250V-3P4W	250V	3PH	3P4W	420P9W	420C9W	20A	12/4
EXC-*-30A-IP67-309.NA-3PH-250V-3P4W	250V	3PH	3P4W	430P9W	430C9W	30A	10/4
EXC-*-60A-IP67-309.NA-3PH-250V-3P4W	250V	3PH	3P4W	460P9W	460C9W	60A	4/4
EXC-*-100A-IP67-309.NA-3PH-250V-3P4W	250V	3PH	3P4W	4100P9W	4100C9W	100A	4/4
EXC-*-20A-IP67-309.NA-3PH-480V-3P4W	480V	3PH	3P4W	420P7W	420C7W	20A	12/4
EXC-*-30A-IP67-309.NA-3PH-480V-3P4W	480V	3PH	3P4W	430P7W	430C7W	30A	10/4
EXC-*-60A-IP67-309.NA-3PH-480V-3P4W	480V	3PH	3P4W	460P7W	460C7W	60A	4/4
EXC-*-100A-IP67-309.NA-3PH-480V-3P4W	480V	3PH	3P4W	4100P7W	4100C7W	100A	4/4
EXC-*-20A-IP67-309.NA-3PH-600V-3P4W	600V	3PH	3P4W	420P5W	420C5W	20A	12/4
EXC-*-30A-IP67-309.NA-3PH-600V-3P4W	600V	3PH	3P4W	430P5W	430C5W	30A	10/4
EXC-*-60A-IP67-309.NA-3PH-600V-3P4W	600V	3PH	3P4W	460P5W	460C5W	60A	4/4
EXC-*-100A-IP67-309.NA-3PH-600V-3P4W	600V	3PH	3P4W	4100P5W	4100C5W	100A	4/4
EXC-*-20A-IP67-309.NA-3PH-208Y.120-4P5W	208Y/120	3PH	4P5W	520P9W	520C9W	20A	12/5
EXC-*-30A-IP67-309.NA-3PH-208Y.120-4P5W	208Y/120	3PH	4P5W	530P9W	530C9W	30A	10/5
EXC-*-60A-IP67-309.NA-3PH-208Y.120-4P5W	208Y/120	3PH	4P5W	560P9W	560C9W	60A	4/5
EXC-*-100A-IP67-309.NA-3PH-208Y.120-4P5W	208Y/120	3PH	4P5W	5100P9W	5100C9W	100A	4/5
EXC-*-20A-IP67-309.NA-3PH-480Y.277-4P5W	480Y/277	3PH	4P5W	520P7W	520C7W	20A	12/5
EXC-*-30A-IP67-309.NA-3PH-480Y.277-4P5W	480Y/277	3PH	4P5W	530P7W	530C7W	30A	10/5
EXC-*-60A-IP67-309.NA-3PH-480Y.277-4P5W	480Y/277	3PH	4P5W	560P7W	560C7W	60A	4/5
EXC-*-100A-IP67-309.NA-3PH-480Y.277-4P5W	480Y/277	3PH	4P5W	5100P7W	5100C7W	100A	4/5
EXC-*-20A-IP67-309.NA-3PH-600Y.347-4P5W	600Y/347	3PH	4P5W	520P5W	520C5W	20A	12/5
EXC-*-30A-IP67-309.NA-3PH-600Y.347-4P5W	600Y/347	3PH	4P5W	530P5W	530C5W	30A	10/5
EXC-*-60A-IP67-309.NA-3PH-600Y.347-4P5W	600Y/347	3PH	4P5W	560P5W	560C5W	60A	4/5
EXC-*-100A-IP67-309.NA-3PH-600Y.347-4P5W	600Y/347	3PH	4P5W	5100P5W	5100C5W	100A	4/5

*Replace * with desired cord length*

IEC 60309 Pin/Sleeve IP44 Drip Proof Extension Cords (North American Standard)

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-20A-IP44-309.NA-1PH-125V-2P3W	125V	1PH	2P3W	320P4	320C4	20A	12/3
EXC-*-30A-IP44-309.NA-1PH-125V-2P3W	125V	1PH	2P3W	330P4	330C4	30A	10/3
EXC-*-60A-IP44-309.NA-1PH-125V-2P3W	125V	1PH	2P3W	360P4	360C4	60A	4/3
EXC-*-100A-IP44-309.NA-1PH-125V-2P3W	125V	1PH	2P3W	3100P4	3100C4	100A	8/3
EXC-*-20A-IP44-309.NA-1PH-250V-2P3W	250V	1PH	2P3W	320P6	320C6	20A	12/3
EXC-*-30A-IP44-309.NA-1PH-250V-2P3W	250V	1PH	2P3W	330P6	330C6	30A	10/3
EXC-*-60A-IP44-309.NA-1PH-250V-2P3W	250V	1PH	2P3W	360P6	360C6	60A	4/3
EXC-*-100A-IP44-309.NA-1PH-250V-2P3W	250V	1PH	2P3W	3100P6	3100C6	100A	8/3
EXC-*-20A-IP44-309.NA-1PH-480V-2P3W	480V	1PH	2P3W	320P7	320C7	20A	12/3
EXC-*-30A-IP44-309.NA-1PH-480V-2P3W	480V	1PH	2P3W	330P7	330C7	30A	10/3
EXC-*-60A-IP44-309.NA-1PH-480V-2P3W	480V	1PH	2P3W	360P7	360C7	60A	4/3
EXC-*-100A-IP44-309.NA-1PH-480V-2P3W	480V	1PH	2P3W	3100P7	3100C7	100A	8/3
EXC-*-20A-IP44-309.NA-1PH-125.250V-3P4W	125/250V	1PH	3P4W	420P12	420C12	20A	12/4
EXC-*-30A-IP44-309.NA-1PH-125.250V-3P4W	125/250V	1PH	3P4W	430P12	430C12	30A	10/4
EXC-*-60A-IP44-309.NA-1PH-125.250V-3P4W	125/250V	1PH	3P4W	460P12	460C12	60A	4/4
EXC-*-100A-IP44-309.NA-1PH-125.250V-3P4W	125/250V	1PH	3P4W	4100P12	4100C12	100A	8/4
EXC-*-20A-IP44-309.NA-3PH-250V-3P4W	250V	3PH	3P4W	420P9	420C9	20A	12/4
EXC-*-30A-IP44-309.NA-3PH-250V-3P4W	250V	3PH	3P4W	430P9	430C9	30A	10/4
EXC-*-60A-IP44-309.NA-3PH-250V-3P4W	250V	3PH	3P4W	460P9	460C9	60A	4/4
EXC-*-100A-IP44-309.NA-3PH-250V-3P4W	250V	3PH	3P4W	4100P9	4100C9	100A	8/4
EXC-*-20A-IP44-309.NA-3PH-480V-3P4W	480V	3PH	3P4W	420P7	420C7	20A	12/4
EXC-*-30A-IP44-309.NA-3PH-480V-3P4W	480V	3PH	3P4W	430P7	430C7	30A	10/4
EXC-*-60A-IP44-309.NA-3PH-480V-3P4W	480V	3PH	3P4W	460P7	460C7	60A	4/4
EXC-*-100A-IP44-309.NA-3PH-480V-3P4W	480V	3PH	3P4W	4100P7	4100C7	100A	8/4
EXC-*-20A-IP44-309.NA-3PH-600V-3P4W	600V	3PH	3P4W	420P5	420C5	20A	12/4
EXC-*-30A-IP44-309.NA-3PH-600V-3P4W	600V	3PH	3P4W	430P5	430C5	30A	10/4
EXC-*-60A-IP44-309.NA-3PH-600V-3P4W	600V	3PH	3P4W	460P5	460C5	60A	4/4
EXC-*-100A-IP44-309.NA-3PH-600V-3P4W	600V	3PH	3P4W	4100P5	4100C5	100A	8/4
EXC-*-20A-IP44-309.NA-3PH-208Y.120-4P5W	208Y/120	3PH	4P5W	520P9	520C9	20A	12/5
EXC-*-30A-IP44-309.NA-3PH-208Y.120-4P5W	208Y/120	3PH	4P5W	530P9	530C9	30A	10/5
EXC-*-60A-IP44-309.NA-3PH-208Y.120-4P5W	208Y/120	3PH	4P5W	560P9	560C9	60A	4/5
EXC-*-100A-IP44-309.NA-3PH-208Y.120-4P5W	208Y/120	3PH	4P5W	5100P9	5100C9	100A	8/5
EXC-*-20A-IP44-309.NA-3PH-480Y.277-4P5W	480Y/277	3PH	4P5W	520P7	520C7	20A	12/5
EXC-*-30A-IP44-309.NA-3PH-480Y.277-4P5W	480Y/277	3PH	4P5W	530P7	530C7	30A	10/5
EXC-*-60A-IP44-309.NA-3PH-480Y.277-4P5W	480Y/277	3PH	4P5W	560P7	560C7	60A	4/5
EXC-*-100A-IP44-309.NA-3PH-480Y.277-4P5W	480Y/277	3PH	4P5W	5100P7	5100C7	100A	8/5
EXC-*-20A-IP44-309.NA-3PH-600Y.347-4P5W	600Y/347	3PH	4P5W	520P5	520C5	20A	12/5
EXC-*-30A-IP44-309.NA-3PH-600Y.347-4P5W	600Y/347	3PH	4P5W	530P5	530C5	30A	10/5
EXC-*-60A-IP44-309.NA-3PH-600Y.347-4P5W	600Y/347	3PH	4P5W	560P5	560C5	60A	4/5
EXC-*-100A-IP44-309.NA-3PH-600Y.347-4P5W	600Y/347	3PH	4P5W	5100P5	5100C5	100A	8/5

*Replace * with desired cord length*

IEC 60309 Pin/Sleeve IP67 Waterproof Extension Cords (International Standard)

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-16A-IP67-309.INTL-1PH-130V-2P3W	100-130V	1PH	2P3W	316P4W	316C4W	16A	12/3
EXC-*-32A-IP67-309.INTL-1PH-130V-2P3W	100-130V	1PH	2P3W	332P4W	332C4W	32A	10/3
EXC-*-63A-IP67-309.INTL-1PH-130V-2P3W	100-130V	1PH	2P3W	363P4W	363C4W	63A	4/3
EXC-*-125A-IP67-309.INTL-1PH-130V-2P3W	100-130V	1PH	2P3W	3125P4W	3125C4W	125A	8/3
EXC-*-16A-IP67-309.INTL-1PH-240V-2P3W	220-240V	1PH	2P3W	316P6W	316C6W	16A	12/3
EXC-*-32A-IP67-309.INTL-1PH-240V-2P3W	220-240V	1PH	2P3W	332P6W	332C6W	32A	10/3
EXC-*-63A-IP67-309.INTL-1PH-240V-2P3W	220-240V	1PH	2P3W	363P6W	363C6W	63A	4/3
EXC-*-125A-IP67-309.INTL-1PH-240V-2P3W	220-240V	1PH	2P3W	3125P6W	3125C6W	125A	8/3
EXC-*-16A-IP67-309.INTL-3PH-415V-3P4W	380-415V	3PH	3P4W	416P6W	416C6W	16A	12/4
EXC-*-32A-IP67-309.INTL-3PH-415V-3P4W	380-415V	3PH	3P4W	432P6W	432C6W	32A	10/4
EXC-*-63A-IP67-309.INTL-3PH-415V-3P4W	380-415V	3PH	3P4W	463P6W	463C6W	63A	4/4
EXC-*-125A-IP67-309.INTL-3PH-415V-3P4W	380-415V	3PH	3P4W	4125P6W	4125C6W	125A	8/4
EXC-*-16A-IP67-309.INTL-3PH-380V-3P4W	380V 50 Hz	3PH	3P4W	416P3W	416C3W	16A	12/4
EXC-*-32A-IP67-309.INTL-3PH-380V-3P4W	380V 50 Hz	3PH	3P4W	432P3W	432C3W	32A	10/4
EXC-*-16A-IP67-309.INTL-3PH-440V-3P4W	440V 60 Hz	3PH	3P4W	416P3W	416C3W	16A	12/4
EXC-*-32A-IP67-309.INTL-3PH-440V-3P4W	440V 60 Hz	3PH	3P4W	432P3W	432C3W	32A	10/4
EXC-*-16A-IP67-309.INTL-3PH-415Y.240-4P5W	"380Y/220 - 415Y/240"	3PH	4P5W	516P6W	516C6W	16A	12/5
EXC-*-32A-IP67-309.INTL-3PH-415Y.240-4P5W	"380Y/220 - 415Y/240"	3PH	4P5W	532P6W	532C6W	32A	10/5
EXC-*-63A-IP67-309.INTL-3PH-415Y.240-4P5W	"380Y/220 - 415Y/240"	3PH	4P5W	563P6W	563C6W	63A	4/5
EXC-*-125A-IP67-309.INTL-3PH-415Y.240-4P5W	"380Y/220 - 415Y/240"	3PH	4P5W	5125P6W	5125C6W	125A	8/5

*Replace * with desired cord length*

IEC 60309 Pin/Sleeve IP44 Drip Proof Extension Cords (International Standard)

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-16A-IP67-309.INTL-1PH-130V-2P3W	100-130V	1PH	2P3W	316P4	316C4	16A	12/3
EXC-*-32A-IP67-309.INTL-1PH-130V-2P3W	100-130V	1PH	2P3W	332P4	332C4	32A	10/3
EXC-*-63A-IP67-309.INTL-1PH-130V-2P3W	100-130V	1PH	2P3W	363P4	363C4	63A	4/3
EXC-*-125A-IP67-309.INTL-1PH-130V-2P3W	100-130V	1PH	2P3W	3125P4	3125C4	125A	8/3
EXC-*-16A-IP67-309.INTL-1PH-240V-2P3W	220-240V	1PH	2P3W	316P6	316C6	16A	12/3
EXC-*-32A-IP67-309.INTL-1PH-240V-2P3W	220-240V	1PH	2P3W	332P6	332C6	32A	10/3
EXC-*-63A-IP67-309.INTL-1PH-240V-2P3W	220-240V	1PH	2P3W	363P6	363C6	63A	4/3
EXC-*-125A-IP67-309.INTL-1PH-240V-2P3W	220-240V	1PH	2P3W	3125P6	3125C6	125A	8/3
EXC-*-16A-IP67-309.INTL-3PH-415V-3P4W	380-415V	3PH	3P4W	416P6	416C6	16A	12/4
EXC-*-32A-IP67-309.INTL-3PH-415V-3P4W	380-415V	3PH	3P4W	432P6	432C6	32A	10/4
EXC-*-63A-IP67-309.INTL-3PH-415V-3P4W	380-415V	3PH	3P4W	463P6	463C6	63A	4/4
EXC-*-125A-IP67-309.INTL-3PH-415V-3P4W	380-415V	3PH	3P4W	4125P6	4125C6	125A	8/4
EXC-*-16A-IP67-309.INTL-3PH-380V-3P4W	380V 50 Hz	3PH	3P4W	416P3	416C3	16A	12/4
EXC-*-32A-IP67-309.INTL-3PH-380V-3P4W	380V 50 Hz	3PH	3P4W	432P3	432C3	32A	10/4
EXC-*-16A-IP67-309.INTL-3PH-440V-3P4W	440V 60 Hz	3PH	3P4W	416P3	416C3	16A	12/4
EXC-*-32A-IP67-309.INTL-3PH-440V-3P4W	440V 60 Hz	3PH	3P4W	432P3	432C3	32A	10/4
EXC-*-16A-IP67-309.INTL-3PH-415Y.240-4P5W	"380Y/220 - 415Y/240"	3PH	4P5W	516P6	516C6	16A	12/5
EXC-*-32A-IP67-309.INTL-3PH-415Y.240-4P5W	"380Y/220 - 415Y/240"	3PH	4P5W	532P6	532C6	32A	10/5
EXC-*-63A-IP67-309.INTL-3PH-415Y.240-4P5W	"380Y/220 - 415Y/240"	3PH	4P5W	563P6	563C6	63A	4/5
EXC-*-125A-IP67-309.INTL-3PH-415Y.240-4P5W	"380Y/220 - 415Y/240"	3PH	4P5W	5125P6	5125C6	125A	8/5

*Replace * with desired cord length*

UL 1686 C1 Style II Pin/Sleeve NEMA 4X Weatherproof Extension Cords

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-*-N4X-1686-1PH-30A-600V-2P3W	"600V AC / 250V DC"	1PH	2P3W	330PS2W	330CS2W	30A	10/3
EXC-*-N4X-1686-1PH-60A-600V-2P3W	"600V AC / 250V DC"	1PH	2P3W	360PS2W	360CS2W	60A	4/3
EXC-*-N4X-1686-1PH-100A-600V-2P3W	"600V AC / 250V DC"	1PH	2P3W	3100PS2W	3100CS2W	100A	8/3
EXC-*-N4X-1686-1PH-200A-600V-2P3W	"600V AC / 250V DC"	1PH	2P3W	3100PS2W	3100CS2W	200A	6/3
EXC-*-N4X-1686-3PH-30A-600V-3P4W	"600V AC / 250V DC"	3PH	3P4W	430PS2W	430CS2W	30A	10/4
EXC-*-N4X-1686-3PH-60A-600V-3P4W	"600V AC / 250V DC"	3PH	3P4W	460PS2W	460CS2W	60A	4/4
EXC-*-N4X-1686-3PH-100A-600V-3P4W	"600V AC / 250V DC"	3PH	3P4W	4100PS2W	4100CS2W	100A	8/4
EXC-*-N4X-1686-3PH-200A-600V-3P4W	"600V AC / 250V DC"	3PH	3P4W	4100PS2W	4100CS2W	200A	6/4
EXC-*-N4X-1686-3PH-30A-600V-4P5W	"600V AC / 250V DC"	3PH	4P5W	530PS2W	530CS2W	30A	10/5
EXC-*-N4X-1686-3PH-60A-600V-4P5W	"600V AC / 250V DC"	3PH	4P5W	560PS2W	560CS2W	60A	4/5
EXC-*-N4X-1686-3PH-100A-600V-4P5W	"600V AC / 250V DC"	3PH	4P5W	5100PS2W	5100CS2W	100A	8/5
EXC-*-N4X-1686-3PH-200A-600V-4P5W	"600V AC / 250V DC"	3PH	4P5W	5100PS2W	5100CS2W	200A	6/5

*Replace * with desired cord length*

Spliiter Cords - 2-Way Y-Splitter Cables (2fers)

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-Y-18.3-BCE	300V	1PH	2P3W	N/A	N/A	10A	18/3
EXC-Y-16.3-BCE	300V	1PH	2P3W	N/A	N/A	13A	16/3
EXC-Y-16.4-BCE	300V	1PH	3P4W	N/A	N/A	10A	16/4
EXC-Y-14.3-BCE	300V	1PH	2P3W	N/A	N/A	18A	14/3
EXC-Y-14.4-BCE	300V	1PH	3P4W	N/A	N/A	15A	14/4
EXC-Y-12.3-BCE	300V	1PH	2P3W	N/A	N/A	25A	12/4
EXC-Y-12.4-BCE	300V	1PH	3P4W	N/A	N/A	20A	12/3
EXC-Y-10.3-BCE	600V	1PH	2P3W	N/A	N/A	30A	10/3
EXC-Y-10.4-BCE	600V	1PH	3P4W	N/A	N/A	25A	10/4
EXC-Y-8.3-BCE	600V	1PH	2P3W	N/A	N/A	40A	8/3
EXC-Y-8.4-BCE	600V	1PH	3P4W	N/A	N/A	35A	8/4
EXC-Y-6.3-BCE	600V	1PH	2P3W	N/A	N/A	55A	6/3
EXC-Y-6.4-BCE	600V	1PH	3P4W	N/A	N/A	45A	6/4
EXC-Y-4.3-BCE	600V	1PH	2P3W	N/A	N/A	70A	4/3
EXC-Y-4.4-BCE	600V	1PH	3P4W	N/A	N/A	60A	4/4
EXC-Y-2.3-BCE	600V	1PH	2P3W	N/A	N/A	80A	2/3
EXC-Y-2.4-BCE	600V	1PH	3P4W	N/A	N/A	80A	2/4

Spliiter Cord - 3-Way W-Splitter Cables (3fers)

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-W-18.3-BCE	300V	1PH	2P3W	N/A	N/A	10A	18/3
EXC-W-16.3-BCE	300V	1PH	2P3W	N/A	N/A	13A	16/3
EXC-W-16.4-BCE	300V	1PH	3P4W	N/A	N/A	10A	16/4
EXC-W-14.3-BCE	300V	1PH	2P3W	N/A	N/A	18A	14/3
EXC-W-14.4-BCE	300V	1PH	3P4W	N/A	N/A	15A	14/4
EXC-W-12.3-BCE	300V	1PH	2P3W	N/A	N/A	25A	12/4
EXC-W-12.4-BCE	300V	1PH	3P4W	N/A	N/A	20A	12/3
EXC-W-10.3-BCE	600V	1PH	2P3W	N/A	N/A	30A	10/3
EXC-W-10.4-BCE	600V	1PH	3P4W	N/A	N/A	25A	10/4
EXC-W-8.3-BCE	600V	1PH	2P3W	N/A	N/A	40A	8/3
EXC-W-8.4-BCE	600V	1PH	3P4W	N/A	N/A	35A	8/4
EXC-W-6.3-BCE	600V	1PH	2P3W	N/A	N/A	55A	6/3
EXC-W-6.4-BCE	600V	1PH	3P4W	N/A	N/A	45A	6/4
EXC-W-4.3-BCE	600V	1PH	2P3W	N/A	N/A	70A	4/3
EXC-W-4.4-BCE	600V	1PH	3P4W	N/A	N/A	60A	4/4
EXC-W-2.3-BCE	600V	1PH	2P3W	N/A	N/A	80A	2/3
EXC-W-2.4-BCE	600V	1PH	3P4W	N/A	N/A	80A	2/4

Replace * with desired cord length

Spliiter Cords - 4-Way X-Splitter Cables (4fers)

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-W-18.3-BCE	300V	1PH	2P3W	N/A	N/A	10A	18/3
EXC-W-16.3-BCE	300V	1PH	2P3W	N/A	N/A	13A	16/3
EXC-W-16.4-BCE	300V	1PH	3P4W	N/A	N/A	10A	16/4
EXC-W-14.3-BCE	300V	1PH	2P3W	N/A	N/A	18A	14/3
EXC-W-14.4-BCE	300V	1PH	3P4W	N/A	N/A	15A	14/4
EXC-W-12.3-BCE	300V	1PH	2P3W	N/A	N/A	25A	12/4
EXC-W-12.4-BCE	300V	1PH	3P4W	N/A	N/A	20A	12/3
EXC-W-10.3-BCE	600V	1PH	2P3W	N/A	N/A	30A	10/3
EXC-W-10.4-BCE	600V	1PH	3P4W	N/A	N/A	25A	10/4
EXC-W-8.3-BCE	600V	1PH	2P3W	N/A	N/A	40A	8/3
EXC-W-8.4-BCE	600V	1PH	3P4W	N/A	N/A	35A	8/4
EXC-W-6.3-BCE	600V	1PH	2P3W	N/A	N/A	55A	6/3
EXC-W-6.4-BCE	600V	1PH	3P4W	N/A	N/A	45A	6/4
EXC-W-4.3-BCE	600V	1PH	2P3W	N/A	N/A	70A	4/3
EXC-W-4.4-BCE	600V	1PH	3P4W	N/A	N/A	60A	4/4
EXC-W-2.3-BCE	600V	1PH	2P3W	N/A	N/A	80A	2/3
EXC-W-2.4-BCE	600V	1PH	3P4W	N/A	N/A	80A	2/4

Spliiter Cord Sets - 2-Way Y-Splitter Cables (2fers) NEMA Straight Blade Cord Caps

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-Y-12.3-5.15	125V	1PH	2P3W	(1) 5-15P	(2) 5-15C	15A	12/3
EXC-Y-12.3-5.20	125V	1PH	2P3W	(1) 5-20P	(2) 5-20C	20A	12/3
EXC-Y-10.3-5.30	125V	1PH	2P3W	(1) 5-30P	(2) 5-30C	30A	10/3
EXC-Y-8.3-5.50	125V	1PH	2P3W	(1) 5-50P	(2) 5-50R	50A	8/3
EXC-Y-12.3-6.15	250V	1PH	2P3W	(1) 6-15P	(2) 6-15C	15A	12/3
EXC-Y-12.3-6.20	250V	1PH	2P3W	(1) 6-20P	(2) 6-20C	20A	12/3
EXC-Y-10.3-6.30	250V	1PH	2P3W	(1) 6-30P	(2) 6-30C	30A	10/3
EXC-Y-8.3-6.50	250V	1PH	2P3W	(1) 6-50P	(2) 6-50R	50A	8/3
EXC-Y-12.3-7.15	277V	1PH	2P3W	(1) 7-15P	(2) 7-15C	15A	12/3
EXC-Y-12.3-7.20	277V	1PH	2P3W	(1) 7-20P	(2) 7-20C	20A	12/3
EXC-Y-10.3-7.30	277V	1PH	2P3W	(1) 7-30P	(2) 7-30C	30A	10/3
EXC-Y-8.3-7.50	277V	1PH	2P3W	(1) 7-50P	(2) 7-50R	50A	8/3
EXC-Y-12.4-14.15	125/250V	1PH	3P4W	(1) 14-15P	(2) 14-15C	15A	12/4
EXC-Y-12.4-14.20	125/250V	1PH	3P4W	(1) 14-20P	(2) 14-20C	20A	12/4
EXC-Y-10.4-14.30	125/250V	1PH	3P4W	(1) 14-30P	(2) 14-30C	30A	10/4
EXC-Y-8.4-14.50	125/250V	1PH	3P4W	(1) 14-50P	(@) 14-50R	50A	8/4

Replace * with desired cord length

Splitter Cord Sets - 2-Way Y-Splitter Cables (2fers) NEMA Twist Lock Cord Caps

SKU	Voltage	Phase	Config.	Male Cord Cap	Female Cord Cap	Amperage	Wire Gauge
EXC-Y-12.3-L5.15	125V	1PH	2P3W	(1) L5-15P	(2) L5-15C	15A	12/3
EXC-Y-12.3-L5.20	125V	1PH	2P3W	(1) L5-20P	(2) L5-20C	20A	12/3
EXC-Y-12.3-L6-15	250V	1PH	2P3W	(1) L6-15P	(2) L6-15C	15A	12/3
EXC-Y-12.3-L6-20	250V	1PH	2P3W	(1) L6-20P	(2) L6-20C	20A	12/3

*Replace * with desired cord length*



Explosion Proof Extension Cords

Larson Electronics explosion proof extension cords are essential accessories that extend access to main or temporary sources of power in Class I, II or III/Divisions 1 & 2 rated combustible sites, as well as hazardous locations. When an inline switch is available on the cord, the devices may also be used to turn connected equipment (without switches) on and off. Explosion proof extension cords in this series are recommended for use with compatible Larson Electronics explosion proof power distribution systems and explosion proof equipment, such as lights, control stations, cameras and more. Examples of hazardous locations that require Class rated extension cords include the following: oil and gas, chemical processing, wastewater treatment plants, refineries, shipyards, petrol stations, grain storage, mining sites and more.

These devices are offered in a wide selection of cable types, lengths, voltage and amp ratings, cord caps and receptacles in order to meet the electrical requirements of the site. Extension cord models with SOOW ratings are heavy-duty units that are resistant against water, debris, oil, acid, chemical and fluctuating temperatures. Explosion proof extension cords with cord caps and/or receptacles utilize copper-free aluminum or non-metallic materials with non-sparking protection.

BENEFITS

- **Suitable for Class I, II or III/Divisions 1 & 2 rated hazardous locations**
- **Extend access to power in remote, combustible sites**
- **Selection of cord types, lengths and ratings**
- **Non-sparking cord caps and receptacles**
- **Customization available**

Suitcase Power Distribution

Larson Electronics suitcase power distribution offers portable and convenient electrical management for stages, concerts, outdoor venues, recording sets, tours and more. These heavy-duty units feature a top-located handle, which makes transportation from location to location seamless. For scaling power requirements at work sites, the ultra-low profile distribution boxes can be stacked in a horizontal position. Stacking the devices also helps maximize space during deployment on flat surfaces or carts. Input and output connections, as well as circuit breakers and other protective components, are all accessible on the suitcase. This integrated design keeps wiring organized and more manageable. Additionally, connections and circuit breakers are labeled and/or colored to ensure proper and safe use. Multiple configurations of plugs, inlets, camlocks, receptacles and outlets are available and can be selected based on the power requirements of the project.

BENEFITS

- **All system components secured on a low-profile suitcase**
- **Accessible handle for easy transportation**
- **Fully stackable in a horizontal position**
- **Color coded and/or labeled input and output connections**
- **Customization available**

ATA Stage/Studio Power Distribution

Larson Electronics ATA stage/studio power distribution provides portable access to essential power connections in remote sites, venues and locations with limited electrical infrastructure. Protected by a durable road case that meets the size requirements and general configuration standards of the Air Transport Association, these units are designed for rugged applications. Wheels at the base facilitate mobility when the power distribution box is being used at the site. Metal knuckle-ball corners and lining help minimize shock, while handles at the side and top make transportation seamless. As the power units meet ATA sizes, multiple power distribution boxes can be stored together closely in order to maximize space in trucks, containers, pods and more. All input and output connections, including inlets, camlocks, receptacles, outlets and breakers are accessible on the cover (input and output configurations may vary depending on selected model).

BENEFITS

- **All system components secured on a standard ATA-style road case**
- **Durable base with wheels for easy transportation**
- **Metal knuckle-ball corners and lining reduces impact**
- **Input and output connections accessible on front cover**
- **Customization available**



Rack Mount Power Distribution

Larson Electronics rack mount power distribution offer space-saving access to electrical connections, switches and power monitoring. Suitable for standalone distribution via a padded or wheeled base, the devices can be used to allocate power to nearby equipment safely. The cube distribution boxes also make system start up less time consuming by making power activation accessible on the equipment rack. For models with a wheeled base, operators may access two swivel casters and two locking casters for extra stability on sloped or uneven surfaces. All system components are protected by a standard ATA-style case. Metal knuckle-ball corners and lining help minimize shock, while handles at the side and top make transportation seamless. With outlets, camlocks, inlets and power switches available at the front of the box, operators can easily make connections with cords or cables. These rack mount distribution units feature power monitoring via highly visible indicator lights and LCD monitors.

BENEFITS

- **Standard ATA-style rack mount configuration**
- **Padded or wheeled base for standalone use**
- **Metal knuckle-ball corners and lining reduces impact**
- **Power monitoring via indicator lights and LCD monitors**
- **Customization available**

Explosion Proof Power Distribution

Larson Electronics explosion proof power distribution provides portable and safe electrical management in Class I, II or III/Divisions 1 & 2 rated combustible sites, as well as hazardous locations. These NEMA-rated stations offer heavy-duty construction and an enclosed design for superior protection during use. Copper-free aluminum panels and non-metallic parts (depending on selected model) feature non-sparking properties, which reduces fire-related and flammable risks on surfaces. Intricate, carefully designed flame paths promote cooling and contains explosive interactions inside the units. This feature prevents the spread of sparks and combustible elements to outside atmospheres or the surrounding facility, where it can cause catastrophic damage and compromise the safety of operators.

Standard explosion proof power distribution systems feature a polyester powder coated blue finish for enhanced durability. This TGIC coating offers protection from bumps, scratches, sunlight, corrosion and moisture. Seamless mobility is facilitated by locking casters located at the base of the unit. Skid pockets and four lifting eyes are also available for lifting with forklifts, cables or chain hooks.

BENEFITS

- **Suitable for Class I, II or III/Divisions 1 & 2 rated hazardous locations**
- **All system components mounted inside an enclosed frame**
- **Side-located handle, four locking casters, skid pockets and four lifting eyes**
- **Powder coated finish**
- **Separate breaker and receptacle enclosures**
- **Customization available**



Custom Power Distribution

Need a custom power distribution unit for your business?

Larson Electronics provides custom power distribution unit request sheets to streamline the purchasing process, making it faster and more accurate. Fill out our request sheets with your requirements and let us work with you on making a superior and reliable power distribution unit for your next project.

These custom power distribution request sheets allow you to include the following information:

- **Primary and secondary voltages**
- **Transformer capacity**
- **Primary and/or secondary panel types (MCB, MLO, etc.)**
- **Circuit breaker quantities and types**
- **Line-in cords, camlocks or inlets**
- **Primary and/or secondary receptacle types and quantities**
- **Automatic transfer switch or manual transfer switch requirements**
- **Accessory devices (meters, VFDs, indicator lights, etc.)**
- **Rating requirements**
- **Dimensions**
- **Mounting style**
- **Finish and color**
- **Special features or requests**



Customization Services

As a leading manufacturer of industrial power distribution systems and equipment, Larson Electronics offers customization services for power distribution units in this catalog at an additional cost. We have waterjets, laser tables, mills and lathes, as well as fabrication shops for adding special features to our power distribution products. Customization services are recommended for meeting specific site, operating, safety or project requirements.

- Primary and/or secondary voltages (single-phase and three-phase available)
- Transformer capacity and requirements
- Primary/secondary panel types
- Circuit breaker type and quantity
- Output receptacle type, quantity and configuration
- Line-in cord (length and type), camlock inputs or inlets
- Additional devices (meters, indicator lights, VFDs, etc.)
- Mounting style
- Finish and color
- Materials
- And more!

*Use the custom power distribution request sheet in this catalog to let us know your custom requirements.

Our on-site engineers are available for custom designs and rapid engineering. We also have a warehouse of inventory to ensure timely production and order fulfillment. Contact us today at 1-800-369-6671 or sales@larsonelectronics.com for more information about our customization services. Visit our website at LarsonElectronics.com to see all of our industrial lighting and power distribution products.

LARSON ELECTRONICS LLC
9419 E US HWY 175
KEMP, TX 75143

Web: larsonelectronics.com
Email: sales@larsonelectronics.com
Phone: 1-800-369-6671
Intl: +1-214-616-6180
Fax: 903-498-3364

FOLLOW US

facebook.com/LarsonElectronics
twitter.com/LarsonLights
youtube.com/LEMagnalight
instagram.com/LarsonLights

