IES COMPARE REPORT
REPORT FORMAT: DARK SKY

	EPL-MJ-50W-LED-XX-CM.IES
[MANUFAC] keyword	LARSON ELECTRONICS LLC
[LUMINAIRE] keyword	CLASS 1 DIV 1 EXPLOSION PROOF LED MASON JAR FIXTURE
[LAMP] keyword	missing
Total Luminaire Watts	49.9
Total Lamp Lumens	7471
IES Classification	Type VS
Longitudinal Classification	Very Short
Cutoff Classification (deprecated)	Non-Cutoff
Maximum Candela	1105.366
Maximum Candela Angle	247.5 H x 46.5 V
Max. Candela At 90 Degrees Vert.	789.724 (10.57% Lamp Lms.)
Max. Candela 80 to < 90 Vert.	863.724 (11.56% Lamp Lms.)
Zonal Lumens: 80-90	845.22
Zonal Lumens 90-180	2016.99
Luminaire Lumens	7469
Total Luminaire Efficiency	100 %
Downward Total Efficiency	73 %
Upward Waste Light Ratio	0.27
Avg. Glare Zone Max. Luminous Intensity 80-90	11.56 %Lamp Luminous Flux
Avg. Glare Zone Flux 80-90	11.31 %Lamp Luminous Flux
Luminance Data 85v, 0h:	67929
Luminance Data 85v, 45h:	53717
Luminance Data 85v, 90h:	69601
LCS: Front-Low (0-30) Lumens	289.0
LCS: Front-Low (0-30) %Lamp	3.9
LCS: Front-Medium (30-60) Lumens	1121.1

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.


IES COMPARE REPORT
REPORT FORMAT: DARK SKY

	EPL-MJ-50W-LED-XX-CM.IES
LCS: Front-Medium (30-60) %Lamp	15.0
LCS: Front-High (60-80) Lumens	915.8
LCS: Front-High (60-80) %Lamp	12.3
LCS: Front-Very High (80-90) Lumens	423.7
LCS: Front-Very High (80-90) %Lamp	5.7
LCS: Back-Low (0-30) Lumens	286.7
LCS: Back-Low (0-30) %Lamp	3.8
LCS: Back-Medium (30-60) Lumens	1086.8
LCS: Back-Medium (30-60) %Lamp	14.5
LCS: Back-High (60-80) Lumens	907.5
LCS: Back-High (60-80) %Lamp	12.1
LCS: Back-Very High (80-90) Lumens	421.6
LCS: Back-Very High (80-90) %Lamp	5.6
LCS: Uplight-Low (90-100) Lumens	730.6
LCS: Uplight-Low (90-100) %Lamp	9.8
LCS: Uplight-High (100-180) Lumens	1286.4
LCS: Uplight-High (100-180) %Lamp	17.2
LCS: Total Lumens	7469
BUG Rating	B2-U5-G3

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES COMPARE REPORT
REPORT FORMAT: DARK SKY

CANDELA DISPLAY



1 EPL-MJ-50W-LED-... - Vertical Plane Through Horizontal Angles (247.5 - 67.5) Max. Candela

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.