I. Installation & Operation - LEDHCL-900

This LED wall pack is universal voltage, not multi-tap, and operates on any voltage ranging from 100 volts to 277 volts AC 50/60Hz.

I. Installation

1. Cut off all power before attempting to perform any maintenance.

2. Make sure to cap off any unused wires.

3. Activate Fixture



II. Maintenance

This LED light provides low maintenance service with no bulbs to change. Clean surfaces with a mild soap and water. Do not use abrasive materials such as scouring pads or powders, steel wool or abrasive paper.

LARSON ELECTRONICS LLC · 9419 E US HWY 175 · KEMP, TX 75143
p: 1-800-369-6671 · intl: 903-498-3363 · f: 903-498-3364 · sales@larsonelectronics.com

II. Safety Warnings

I. Warnings

DO NOT install damaged product.

This fixture can **NOT** be used in areas with limited ventilation or high ambient temperatures.

These instructions do not purport to cover all details or variations in equipment nor to provide every possible contingency to meet in connection with installation, operation or maintenance.

WARNING: Turn off electrical power at fuse or circuit breaker box before wiring fixture to the power supply.

WARNING: Turn off the power when performing any maintenance.

WARNING: Verify that supply voltage is correct by comparing it with the luminaire label information.

WARNING: Make all electrical and grounded connections in accordance with the National Electric Code and any applicable local code requirements.

WARNING: All wiring connections should be capped with UL approved wire connectors.

WARNING: All fixture to cool before handling. Do not touch enclosure or light source.

WARNING: Do **NOT** exceed maximum wattage marked on fixture label.

WARNING: Follow all lamp manufacturer's warnings, recommendations and restrictions for driver type, burning position, mounting locations/methods, replacement and recycling.

WARNING: Keep combustible and other materials that can burn away from fixture and lamp/lens.

WARNING: Electrostatic Discharge (ESD) can damage LED fixtures. Personal grounding equipment must be worn during all installation or servicing of the unit.

WARNING: Do **NOT** touch individual electrical components as the can cause ESD, shorten lamp life, or alter performance.

II. Options

II.I Color Temp
-2700
-4500
-5600

II.II Housing Color
-Black
-Brown