
Frosted Polycarbonate Lens Cover
for EPL-48-2L Series, Class I, Div. I Fixtures - Prevents Overspray

4 Pack Frosted (Opaque) Polycarbonate Overspray Shields for the EPL-48-2L series. Over time, spraying can lead to particles reaching the lens of the light fixture. With the polycarbonate shield, operator will not have to worry about such inconveniences. This over spray is designed to fit the EPL-48-2L series explosion proof fixtures, including the LED, LV, UV, and Bi-axial models. This includes (4) shields.

Follow the basic installation steps below and remember that the lens cover can be easily removed should you need to reposition it.

1. Clean the lens thoroughly with a lint free cloth and common glass cleaner in order to remove dust accumulation. Let it stand for several minutes to air dry.



2. Unfold lens cover over one end of the lens and continue down the light until completely covered. The lens film will wrap around itself on the lens.



3. When it comes time to replacing, simply grab one end of the lens film and pull away to remove.



A mild soap and water can be used to keep the film clean and clear. If you decide to run a different tint/clear film or if it becomes dirty it can be removed as easily as it was installed.

THESE INSTRUCTIONS MAY NOT COVER ALL DETAILS OR VARIATIONS OF THIS PRODUCT FOR YOUR EQUIPMENT OR INSTALLATION REQUIREMENTS. SHOULD FURTHER INFORMATION NOT COVERED BY THESE INSTRUCTIONS BE REQUIRED, PLEASE CONTACT LARSON ELECTRONICS BY EMAIL AT SALES@LARSONELECTRONICS.COM OR BY PHONE AT 1-800-369-6671 FOR FURTHER ASSISTANCE.

PLEASE VISIT LARSONELECTRONICS.COM FOR **WARRANTY** AND **RETURN** INFORMATION.