15 Million CP Rechargeable HID Handheld Spotlight
35W HID - 3200 Lumens - 2.5 hour Run Time
Instruction Manual

Familiarize yourself with all procedures outlined within this instruction sheet.

WARNING:

READ CAREFULLY BEFORE OPERATING FIXTURE. RETAIN THESE INSTRUCTIONS FOR FUTURE REFERENCE. CRITICAL SAFETY INSTRUCTIONS:

- NEVER PLACE SPOTLIGHT FACE DOWN WHEN LIGHT IS ON. DOING SO COULD BURN/IGNITE SURFACES SUCH AS SEATS, CARPETING, ETC. AND CAUSE MAJOR PROPERTY DAMAGE. ALWAYS TURN SPOTLIGHT OFF WHEN NOT IN USE.
- TO PREVENT SERIOUS DAMAGE TO EYESIGHT, NEVER LOOK INTO SPOTLIGHT WHEN LIGHT IS ON.
- **DO NOT** SHINE LIGHT INTO THE FACE OF SOMEONE ELSE.
- **DO NOT** TOUCH LENS OF SPOTLIGHT WHEN LIGHT IS ON OR IF IT WAS RECENTLY ON. THE LENS WILL BE HOT.
- **DO NOT** ALLOW CHILDREN TO HANDLE OR OPERATE THIS SPOTLIGHT.
- **DO NOT** USE THIS PRODUCT FOR OTHER THAN ITS INTENDED USE.
- **DO NOT** OPERATE IN CLOSE PROXIMITY OF COMBUSTIBLE OR FLAMMABLE MATERIALS.
- **DO NOT** ATTEMPT TO OPERATE THIS SPOTLIGHT IF CORD, PLUG, BATTERY, BULB OR ANY PART OF THE SPOTLIGHT IS DAMAGED OR CORRODED.

POWER

The compact lithium ion battery pack is recharged in 4 hours by an included 120-240V AC 50/60 Hz wall outlet plug in charging unit and provides 2.5 hours of operation. The charger is equipped with a 5-15 straight blade wall plug for USA models, and a two pin schuko plug adapters for international models. A booted push button switch provides easy one finger operation and the no-slip textured surface of the handle provides a sure grip even in wet conditions. A lanyard attachment at the top of the handle adds further protection against dropping should operators lose their grip.

*Actual fixture may differ from picture



MOUNTING

This HID light is hand held during operation and is ergonomically designed to produce a well balanced and easily managed hand held light source that can withstand demanding conditions and use. The entire unit weighs only 3 lbs 6 oz and is constructed with a high impact nylon handle and lamp housing and a thick polycarbonate lens for extreme durability.

ADJUST LIGHT

Users can lift the locking tab behind the lamp housing and rotate the lamp head to adjust the beam configuration. Rotating the housing adjusts the beam from a wide, soft flood pattern to a tight, spot beam reaching up to 2800 feet in length.



To change the lamp:

Continued rotation to the extreme disconnects the lamp head from the handle assembly, allowing operators to quickly and easily replace the bulb when necessary. The RL-85-HID-80W-CPR spotlight is designed for easy field maintenance with simple internal connectors accessed through the snap in base at the bottom of the handle and a lamp housing that is easily removed to access the bulb and wiring. No tools are required to change any part of the light including the bulb and battery pack. Contact Larson Electronics to order replacement parts for your RL-85-HID-80W-CPR.

THESE INSTRUCTIONS MAY NOT COVER ALL DETAILS OR VARIATIONS OF THIS PRODUCT FOR YOUR EQUIPMENT OR INSTALLATION REQUIREMENTS. SHOULD FURTHER INFORMATION NOT COVERED BY THESE INSTRUCTIONS BE REQUIRED, PLEASE CONTACT LARSON ELECTRONICS BY EMAIL AT SALES@LARSONELECTRONICS.COM OR BY PHONE AT 1-800-369-6671 FOR FURTHER ASSISTANCE.
PLEASE VISIT LARSONELECTRONICS.COM FOR **WARRANTY** AND **RETURN** INFORMATION.