160W Mobile LED Light Stand w/ Dual Wheels 360 Rotation - IP65 - 4' Stand - Extends to 7' Instruction Manual

Thank you for your purchase of the Larson Electronics WALPC-4.7-48-160W-LED-25 mobile light stand.

IMPORTANT

READ CAREFULLY BEFORE INSTALLING THIS FIXTURE. SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE. THE WALPC-4.7-48-160W-LED-25 MUST BE WIRED IN ACCORDANCE WITH NATIONAL ELECTRICAL CODE AND ALL APPLICABLE LOCAL CODES. PROPER GROUNDING IS REQUIRED FOR SAFETY.

WE STRONGLY ENCOURAGE ONLY A LICENSED ELECTRICIAN INSTALL, OPERATE AND MAINTAIN THIS PRODUCT. IF YOU ARE NOT QUALIFIED OR UNFAMILIAR WITH ANY ASPECT OF THIS INSTRUCTION SHEET, CONSULT AN ELECTRICIAN. THERE ARE NO SERVICEABLE PARTS INSIDE.

WARNING: MAKE SURE POWER IS TURNED **OFF** BEFORE STARTING THE INSTALLATION OR PERFORMING ANY MAINTENANCE.

RISK OF FIRE/ELECTRIC SHOCK – DISCONNECT POWER AT BREAKER BEFORE INSTALLING OR SERVICING.
RISK OF PERSONAL INJURY – FIXTURE MAY BECOME UNSTABLE OR DAMAGED IF NOT INSTALLED PROPERLY.
RISK OF BURN – ALLOW FIXTURE TO COOL BEFORE SERVICING.

The Larson Electronics WALPC-4.7-48-160W-LED-25 Mobile LED Light Stand w/ Wheels is designed for portable lighting in industrial facilities. This compact unit is mounted on an aluminum stand with wheels for quick deployment and transportation to various locations around the work site. The 160-watt LED lamp offers brilliant light output of 19,200 lumens with a 160-degree beam angle configuration.

Operation





Tilt the WALPC-4.7-48-160W-LED-25 up onto it's wheels and roll it into the desired position, near a power source outputting the correct voltage. Always position light on a flat surface, and use wheel chocks to prevent unwanted movement. Set vertical tilt of light fixture by loosening the T-handle screws on either end, then tighten back to hold in position.

Warning: ***Check product label for correct voltage!***

Run power cord to a compatible outlet outputting the correct voltage for the light and plug it in. Light is instant on and will illuminate as soon as power is supplied.

For flying leads:

We strongly encourage a licensed electrician install this product, in all locations, especially in outdoor areas where weatherproofing may be required.

Warning: ***Check product label for correct input voltage!***



Attach supply line wires to the appropriate light fixture wires as shown in the diagram ➔

Secure each pair of wires according to the diagram. Utilize a junction box or similar device and take precautionary steps for weatherproofing all connections if installed in a location where water may come in contact with the unit. Ensure the unit is properly grounded and that wiring is done according to all local and national electrical/building codes.

MAINTENANCE

There are no serviceable parts inside the fixture. However, it is good practice to routinely clean and check the fixture for proper function.

- Disconnect power running to the lamp and be sure the fixture is cool to the touch.
- Use a non-abrasive glass cleaning solution to clean the lens.

Note: *It is not necessary to open the fixture and clean or touch the LED's.*

THESE INSTRUCTIONS MAY NOT COVER ALL DETAILS OR VARIATIONS OF THIS PRODUCT FOR YOUR EQUIPMENT OR INSTALLATION REQUIREMENTS. SHOULD FURTHER INFORMATION NOT COVERED BY THESE INSTRUCTIONS BE REQUIRED, PLEASE CONTACT LARSON ELECTRONICS BY EMAIL AT SALES@LARSONELECTRONICS.COM OR BY PHONE AT 1-877-348-9680 FOR FURTHER ASSISTANCE.

PLEASE VISIT LARSONELECTRONICS.COM FOR **WARRANTY** AND **RETURN** INFORMATION.