

Middle Stage Mast Tiedown - Secures Fold Over Masts for Transit Instruction Guide

The LM-xx-3S-SP0343-R2 from Larson Electronics is a Base Stage Mast Tiedown that is used for securing fold over masts for transit.

The LM-xx-3S-SP0343-R2 bolts onto enclosures or other convenient surfaces to secure fold over masts to the trailer or genset. This adds an additional level of safety for secure and reliable transportation of fold over masts. This Base Stage Mast Tiedown requires the LM-xx-3S-SP0344 retaining pin and the LM-xx-SP0342 snap ring to operate.

The LM-xx-3S-SP0343-R2 is available in either a powder coated or galvanized finish.

WARNING

Only install to surfaces that can structurally support the load.

INSTALLATION

1. Place tiedown on flat surface aligning with the mast.
2. Ensure mast is properly aligned and fits the tiedown.
3. Mark holes to mount tiedown.
4. Drill through holes on your surface to secure mast tiedown.
5. Test to ensure alignment.
6. Insert mast and use retaining pin and snap ring to secure.

CAUTION

Ensure retaining pin is removed before inserting or removing mast from tiedown!

These instructions may not cover all details or variations of this product for your equipment or installation requirements. Should further information not covered by these instructions be required, please contact Larson Electronics by email at sales@larsonelectronics.com or by phone at 1-800-369-6671 for further assistance.

Please visit LarsonElectronics.com for **Warranty** and **Return** information.