Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

12/3 MC-HL Cable - Continuously Welded Armor Cable - C1D1 / C2D1 - 600V - Sold by Foot

C-MCHL-12.3

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).

12/3 MC-HL Cable - Continuously Welded Armor Cable - C1D1 / C2D1 - 600V - Sold by Foot

Conductors: Primary conductors are stranded, soft drawn annealed copper
Insulation: Polyvinyl Chloride (PVC), 15 mils plus 4 mils of Nylon, color coded for identification
Assembly: Pairs or Triads are assembled left hand lay, with non-wicking fillers as needed for a round finish with an overall aluminum / polyester shield with 7-strand tinned copper drain wire.
Inner Jacket: Polyvinyl Chloride (PVC) with rip cord for easy removal.
Armor: Continuously welded, impervious, corrugated aluminum armor. Exceeds the grounding requirements of NEC 250.122.
Outer Jacket: Black Polyvinyl Chloride (PVC)

Nominal OD Over Armor: 0.580"
Nominal OD Overall: 0.690"
Weight (per foot): 0.24 lbs

Standards:
Listed MC Cable
Listed Type MC-HL
Listed for cable tray use
UL83, UL1581, UL1569, UL2225
Meets NEC Articles 250-118, 501, 502, 503, 504, 505, and 725 for hazardous locations.
Sunlight Resistant
Oil Resistant
Approved for Direct Burial

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Links (Click on the below items to view):

- ISO 9001 Certification

- Business Certificate