# 25W Crane LED Warning Light
# 2250 Lumens - 347/480V AC 1PH - Pedestrian Warning Safety Light
# Instruction Manual

Thank you for your purchase of the LEDWL-CRN Warning Light. Do not attempt installation until you are familiar with all warnings, precautions, and procedures outlined within this instruction sheet.

## Safety Warnings

For personal safety, always follow the safety instructions in this manual to ensure safe and long- term use. Failing to do so can result in damage to the product or serious bodily injury.

### WARNINGS

To prevent serious damage to eyesight, never look into spotlight when light is on. **DO NOT** shine light into the face of someone else.

**DO NOT** touch lens of spotlight when light is on or if it was recently on.
**DO NOT** use this product for other than its intended use.
**DO NOT** operate in close proximity of Combustible or flammable materials.
**DO NOT** attempt to operate this light if cord, lens, bulb or any part of the light is damaged or corroded.

### MOUNTING AND ADJUSTMENTS:

The LEDWL-CRN is suspended within a form fitting trunnion (yolk-type) mount. This trunnion mount allows the LED light to be adjusted into any position once mounted. Simply loosen the Pivot Adjustment Bolt shown in **FIGURE 1**, angle, and tighten once desired position is achieved.

A single stainless steel tightening bolt protrudes from the mount, enabling the operator to install the light using a single through-hole. Mount the unit in a location free from obstructions and potential obstructions of the crane. Utilize an existing ½ inch hole or drill a new hole where applicable.

This LED crane light comes preconfigured in selected output color from factory indicated on product part number.



FIGURE 1

### WIRING AND PLUG:

This LED light comes with a Deutsch IPD / LADD DT04-2P connector for easy installation. Plug the Deutsch Connector into the back of the light, take the positive and negative leads at the other end of the cord and attach them to their respective polarities on your power source. Ensure voltage is within 347-480V AC 1PH.




For info on **Warranty** and **Returns** please contact us by phone or email sales@larsonelectronics.com