Magnetic Base for HL-8X, HL-8X-HID, RUL-8X and RUL-8X-HID Spotlights Instruction Manual

MOUNTING

3.5 inch diameter magnetic base with 100 pounds of magnetic grip. Base swivels 360 degrees and tilts 140 degrees via tension hinge. Magnetic base screws into tripod mount on handle base of many spotlights. 3/8-16 X 3/4 inch stud compatibility. This magnetic base can be screwed on in the field without the use of any tools. This magnetic base is heavy enough that it can hold the spotlight at any angle on a flat surface, even if the surface does not attract a magnetic charge. In other words, this magnetic base can hold a spotlight at any angle on just a regular table, etc.

The 3/8-16 stud is compatible with the Larson Electronics HL-8X and RL-8X series of spotlights.

The 5/16-18 X 3/4 stud is compatible with the Larson Electronics RL-xx-CPR and HL-xx-CPR series spotlights. This magnetic base can be screwed on in the field without the use of any tools.

To mount an abject simply use a 3/8-16 inch nut fixture, that is typically embedded in the base of the handle of most Larson Electronics products (Such as the HL-85 AND RL-85), enabling the operator to mount a magnetic base.



Should further information not covered by these instructions be required, please contact Larson Electronics at 1-800-369-6671 or sales@larsonelectronics.com for further assistance.

Please visit LarsonElectronics.com for **Warranty** and **Return** information.