18 Watt Handheld LED Spotlight for Industrial Lighting
Articulating Head - Polycarbonate Handle IP65
Instruction Manual

Thank you for your purchase of the HULBLT-18W-LED LED Fixture for Industrial Lighting. Please follow the steps below in order to operate and maintain this product.

WARNING:

READ CAREFULLY BEFORE OPERATING FIXTURE. RETAIN THESE INSTRUCTIONS FOR FUTURE REFERENCE. CRITICAL SAFETY INSTRUCTIONS:

- Never place spotlight face down when light is on. Doing so could burn/ignite surfaces such as seats, carpeting, etc. and cause major property damage. Always turn spotlight off when not in use.
- To prevent serious damage to eyesight, never look into spotlight when light is on.
- **DO NOT** shine light into the face of someone else.
- **DO NOT** touch lens of spotlight when light is on or if it was recently on.
- **DO NOT** allow children to handle or operate this spotlight.
- **DO NOT** use this product for other than its intended use.
- **DO NOT** operate in close proximity of combustible or flammable materials.
- **DO NOT** attempt to operate this spotlight if cord, plug, battery, lens or any part of the spotlight is damaged or corroded.

The HULBLT-18W-LED-R2-30 is shipped with selected Housing Color, Beam Config, and Cord Cap. Images shown may vary depending upon options selected.



POWER

1. Connect deutsch connector/cord to light.
2. Run cord and plug into compatible receptacle outputting voltage within range 100-277VAC, 50/60Hz.
   Note: There is no difference in light output between voltages.
3. This light is “instant-on” and will illuminate once plugged in.

If spotlight gets loose, tighten adjustment screws on trunnion mount.

If spotlight does not illuminate, check deutsch connector and/or power source.

DETACHABLE CORDS

- Cord is attached via a weatherproof 2-pin Deutsch connector.
- The cord is detachable by depressing the tab on the top of the connectors. This enables the operator to leave the cord connected to the power source and remove to store the light.
- Additional or replacement cords can be ordered from our website. Contact us for more information.



IP65 rated waterproof/vapor proof • Impact/Vibration Resistance • Operating Temperature Range: -40°C to +85°C • 18 Watts

THESE INSTRUCTIONS MAY NOT COVER ALL DETAILS OR VARIATIONS OF THIS PRODUCT FOR YOUR EQUIPMENT OR INSTALLATION REQUIREMENTS. SHOULD FURTHER INFORMATION NOT COVERED BY THESE INSTRUCTIONS BE REQUIRED, PLEASE CONTACT LARSON ELECTRONICS BY EMAIL AT SALES@LARSONELECTRONICS.COM OR BY PHONE AT 1-800-369-6671 FOR FURTHER ASSISTANCE.

PLEASE VISIT LARSONELECTRONICS.COM FOR **WARRANTY** AND **RETURN** INFORMATION.