8' Wash Down Light - 56 Watts - 7000 Lumens
Food Preparation - Surface Mount - 120/277V or 12/24V
Instruction Manual

Do not attempt installation until you are familiar with all warnings, precautions, and procedures outlined within this instruction sheet.

IMPORTANT

READ CAREFULLY BEFORE INSTALLING THIS FIXTURE. SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE. THE WDL-96-1L-LED MUST BE WIRED IN ACCORDANCE WITH NATIONAL ELECTRICAL CODE AND ALL APPLICABLE LOCAL CODES. PROPER GROUNDING IS REQUIRED FOR SAFETY.

WE STRONGLY ENCOURAGE ONLY A LICENSED ELECTRICIAN INSTALL, OPERATE AND MAINTAIN THIS PRODUCT. IF YOU ARE NOT QUALIFIED OR UNFAMILIAR WITH ANY ASPECT OF THIS INSTRUCTION SHEET, CONSULT AN ELECTRICIAN. THERE ARE NO SERVICEABLE PARTS INSIDE.

WARNING: MAKE SURE POWER IS TURNED **OFF** BEFORE STARTING THE INSTALLATION OR PERFORMING ANY MAINTENANCE.

RISK OF FIRE/ELECTRIC SHOCK – DISCONNECT POWER AT BREAKER BEFORE INSTALLING OR SERVICING.
RISK OF PERSONAL INJURY – FIXTURE MAY BECOME UNSTABLE OR DAMAGED IF NOT INSTALLED PROPERLY.
RISK OF BURN – ALLOW FIXTURE TO COOL BEFORE SERVICING.

INSTALLATION

This light is equipped with two heavy duty aluminum L brackets, each predrilled with a single hole, that allow for easy ceiling, wall, and surface mounting. Each bracket has a center screw that allows the operator to adjust the fixture position by simply loosening the screw, manually moving the lamp to the desired position, and retightening the screw. Alternative mounting options include chain hanging or safety cable hanging as well as wiring multiple units together end to end via conduit.

Snap the (larger) lamp side of the hanging hook to the lens of the light to mount

Mount the drop light in your desired location either vertically or horizontally. Use both hanging hooks. Run power to the fixture accordingly.

Caution:* *Only use voltage as shown on fixture nameplate!

Wiring for this unit is brought in through the ¾" or ½" hubs on either end. Multiple units can be wired together by bringing conduit to each fixture. The light on this fixture is "instant-on" and will illuminate once power is supplied.

CHECK PRODUCT LABEL FOR CORRECT VOLTAGE!

LAMP INSTALL (Designed for use with LED T8 and T10 style lamps)

1. Loosen the set screw from the base handle.
2. Pull the handle away from the plastic encasing tube.
3. As the handle is pulled away, the seated bulb will slide out from the plastic encasing tube.
4. The bulb is held in place with 2 end cap bulb "spiders".
5. Lay the handle and bulb assembly on a table.
6. Pull back the individual white plastic spiders on each end of the lamp. The bulb will free to remove.
7. Attach the individual white plastic spiders on each end of the new lamp and slide the entire assembly back into the plastic encasing tube.
8. Replace the handle and tighten set screw.

THESE INSTRUCTIONS MAY NOT COVER ALL DETAILS OR VARIATIONS OF THIS PRODUCT FOR YOUR EQUIPMENT OR INSTALLATION REQUIREMENTS. SHOULD FURTHER INFORMATION NOT COVERED BY THESE INSTRUCTIONS BE REQUIRED, PLEASE CONTACT LARSON ELECTRONICS BY EMAIL AT SALES@LARSONELECTRONICS.COM OR BY PHONE AT 1-800-369-6671 FOR FURTHER ASSISTANCE.

PLEASE VISIT LARSONELECTRONICS.COM FOR **WARRANTY** AND **RETURN** INFORMATION.