3" x 2" 316 Stainless Steel Type B Reducing Female Coupler x Male NPT Instruction Manual

Reducing Cam and Groove Couplings - Type B - Female Coupler x Male NPT - 316 Stainless Steel On hose assemblies, pressure rating is the lower of either the rating of the coupling or the hose at 70°F.

MOUNTING INFORMATION

Read all instructions before proceeding.

- To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
- Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.
- ***UNDER NO CIRCUMSTANCES SHOULD CAM AND GROOVE COUPLINGS BE USED FOR COMPRESSED AIR OR STEAM SERVICE!***
- Pressure rating recommendations are based on the use of mating fittings at ambient temperature 70°F with a standard seal installed.

USE AND CARE

Unauthorized modification may impair the function and/or safety of this device and could affect the life of the equipment. Always check for damaged or worn out parts before using the device. Store it in a secure place out of the reach of children when not in use. Inspect for good working condition prior to storage and before re-use.

REPLACEMENT PARTS

The XLE-AWH-HC-SS.316-2M-3F is designed to provide years of reliable performance. Should the need for replacement parts arise, please contact Larson Electronics.

THESE INSTRUCTIONS MAY NOT COVER ALL DETAILS OR VARIATIONS OF THIS PRODUCT FOR YOUR EQUIPMENT OR INSTALLATION REQUIREMENTS. SHOULD FURTHER INFORMATION NOT COVERED BY THESE INSTRUCTIONS BE REQUIRED, PLEASE CONTACT LARSON ELECTRONICS BY EMAIL AT SALES@LARSONELECTRONICS.COM OR BY PHONE AT 1-800-369-6671 FOR FURTHER ASSISTANCE.

PLEASE VISIT LARSONELECTRONICS.COM FOR **WARRANTY** AND **RETURN** INFORMATION.