



Larson Electronics LLC www.LarsonElectronics.com sales@larsonelectronics.com
9419 E US HWY 175, Kemp, TX 75143 - P: (800) 369-6671 - F: (903) 498-3364

9200S

OPERATION

RED: To +VDC

BLACK: To Chassis Ground (-)

BLUE: Flash patterns and Synchronization

- Momentarily apply +VDC to BLUE for Flash Pattern change
- Continuously apply +VDC to BLUE for Low Power
- Connect BLUE wires of all minibars together to synchronization; all units must be set at the same pattern

WARNING: Do not look directly into LEDs while in operation; may cause momentary blindness and/or eye damage.

FLASH PATTERNS

Momentarily apply +VDC to BLUE:

- Once for next pattern
- Quickly 3 times for reset to FP#1

FP #	Flash Patterns	FP #	Flash Patterns
1	Random	13	Quint (all)
2	Single (split)	14	Mega (all)
3	Double (split)	15	Ultra (all)
4	Quad (split)	16	Single-Quad (all)
5	Quint (split)	17	Single H/L (all)
6	Mega (split)	18	Steady (half)
7	Ultra (split)	19	Steady (all)
8	Single-Quad (split)	20	Single (2Hz)
9	Single H/L (split)	21	Double (2Hz)
10	Single (all)	22	Triple (2Hz)
11	Double (all)	23	Quad (2Hz)
12	Quad (all)		

