

C-16-TP7 - 7 Prong Trailer Plug with 16 foot with 2 pin Connector Instruction Manual

Thank you for your purchase of the Larson Electronics.

WARNING

READ CAREFULLY BEFORE INSTALLING FIXTURE. RETAIN THESE INSTRUCTIONS FOR FUTURE REFERENCE.
CRITICAL SAFETY INSTRUCTIONS:

- INSTALLATION SHOULD ONLY BE CONDUCTED BY A QUALIFIED ELECTRICIAN IN ACCORDANCE WITH NEC AND ANY RELEVANT LOCAL BUILDING CODES.
- RISK OF FIRE OR ELECTRIC SHOCK. FIXTURE INSTALLATION REQUIRES KNOWLEDGE OF LUMINAIRE ELECTRICAL SYSTEMS. IF NOT QUALIFIED, CONTACT A QUALIFIED ELECTRICIAN.
- BE CERTAIN ELECTRICAL POWER IS OFF BEFORE AND DURING INSTALLATION AND MAINTENANCE.
- MAKE SURE THE SUPPLY VOLTAGE IS THE SAME AS THE RATED LUMINAIRE FIXTURES VOLTAGE.
- TO PREVENT WIRING DAMAGE OR ABRASION, DO NOT EXPOSE WIRING TO EDGES OF SHEET METAL OR SHARP OBJECTS. SUITABLE FOR DAMP LOCATIONS.

DETACHABLE CORDS

16 foot cord with 7 prong trailer plug. The cord is terminated with a 2 pin SAE or Deutsch connector that can be attached to any Larson Electronics magnetic light, Go light remote control spotlight and several direct connect and rechargeable HID lights. This cord is offered with either round pins (for commercial / agriculture) or flat pins (RVs and trucks). Most vehicles require 7-pin round plug with flat connectors.

Male Connector: 7-Pin Trailer Connector w/ spring strain relief

Female Connector: Deutsch DT06-2S or 2-pin SAE connector

Max Amps: 13

FEATURES

- Manufactured with advanced synthetic rubber compounds
- Exceptional flexibility
- Excellent resistance to flame, deformation, ozone, oils, acids and chemicals
- Oil resistant insulation and jacket
- Abrasion resistant
- Flexible in cold temperatures



Should further information not covered by these instructions be required, please contact Larson Electronics at 1-800-369-6671 or sales@larsonelectronics.com for further assistance.

Please visit LarsonElectronics.com for **Warranty** and **Return** information.