



Larson Electronics LLC www.LarsonElectronics.com sales@larsonelectronics.com
9419 E US HWY 175, Kemp, TX 75143 - P: (800) 369-6671 - F: (903) 498-3364

Y Connector to power 2 HID or LED Units - Splitter Cable Instruction Manual

The wiring harnesses supplied by Larson Electronics' are assembled with with a male and two female connector on one end of the cable. A two conductor or three conductor cable is supplied with the light, depending on the series of LED light purchased.

1. To connect the wiring harness to the lights, push the male connector located on the end of the cable into the female connector protruding from the light.
2. Take the female connector end of the cable and push into the male connector. The cable consists of two.
 - a. The **white** wire is the positive (+) power wire.
 - b. The **black** wire is the negative (-) ground wire.
3. With the white (+) and black (-) wires have been securely connected to their mates, power will be provided to the LED light via the provided low voltage power source.

Additional or replacement cords can be ordered from our website. We offer replacement wiring harnesses for the LED lights in various lengths to meet the customer's requirements, including a six inch wire harness (LEDWH-6), 20 foot harness (LEDWH-20), 30 foot harness (LEDWH-30), and 50 foot harness (LEDWH-50). We also offer 16 foot coil cords with a cigarette plug (C-16-CC-CP), 21 foot cords with ring terminals (C-21-RT), 16 foot cords with battery clamps (C-16-BC), and 16 foot straight cords with cigarette plugs (C-16-CP).

