THREE PHASE PAD MOUNTED TRANSFORMER

MT-PML-R7-3P-GNF-45KVA-YE-LT-DF-A6-BB-CZ-2B4-M1


High Voltage		
Tap Position	Voltage (V)	Current (A)
1	4371	5.9
2	4264	6.1
3	4160	6.2
4	4056	6.4
5	3955	6.6
Low Voltage		
Voltage (V)		Current (A)
480		54.1

Rated Capacity	45	KVA
HV	4160GrdY/2400	V
LV	480Y/277	
Impedence	XXX	%
Use Condition	Outdoor	
Phase	3 Phase	
Vector Group	YnYn0	
Rated Frequency	60	Hz
Cooling Type	KNAN	

Product Code	283810		
Serial Number	XXXXX		
HV BIL	60	LV BIL	XX
Winding Con.	HV: CU	LV: CU	
Temp. Rise	65		°C
Oil Capacity	XXX		GAL
Total Weight	XXX		LBS
Body Weight	XXX		LBS
Step-Up Operation:	No		

Tank must be solidly grounded - NON-PCB Oil **Biodegradable Natural Vegtable Oil**

Wire Connection



Phasor Diagram



ANSI C57.12.34 - DOE 2016 Compliant - Manufactured xx/2022

LARSON MAGNETICS

Larson Magnetics LLC
Kemp, TX USA