THREE PHASE PAD MOUNTED TRANSFORMER

MT-PML-R2-3P-GMF-10MVA-YJ-LT-DF-A6-BB-AZ-2B4-M1

High Voltage		
Tap Position	Voltage (V)	Current (A)
1	26203	220.3
2	25564	225.9
3	24940	231.5
4	23417	237.4
5	23709	243.5
Low Voltage		
Voltage (V)		Current (A)
415		13912.5

Rated Capacity	10000	KVA
HV	24940GrdY/14400	V
LV	415Y/240	
Impedence	XXX	%
Use Condition	Outdoor	
Phase	3 Phase	
Vector Group	YYN0	
Rated Frequency	60	Hz
Cooling Type	KNAN	


Product Code	285128
Serial Number	XXXXX

HV BIL 125 LV BIL XX

Winding Con.	HV: A L	LV: AL	
Temp. Rise	65		°C
Oil Capacity	1,620		GAL
Total Weight	XXX		LBS
Body Weight	XXX		LBS
Step-Up Operation:	No		

Tank must be solidly grounded - NON-PCB Oil **Biodegradable Ester Oil**

Wire Connection



Phasor Diagram



Maximum operating pressures of liquid preservation system _____ kPa (lbf/in2) positive and _____ kPa (lbf/in2) negative.
Tank designed for ___ kPa (lbf/in2) vacuum filling.
Liquid level below top surface of the highest point of the highest manhole flange at 25 °C _____ mm (in). Liquid level changes _____ mm (in) per 10 °C change in liquid temperature.

ANSI C57.12.34 - DOE 2016 Compliant - Manufactured xx/2022

LARSON MAGNETICS

Larson Magnetics LLC
Kemp, TX USA