THREE PHASE PAD MOUNTED TRANSFORMER
MT-PML-R7-3P-GMF-75KVA-YT-LT-DF-A6-BB-CZ-2B4-M1

High Voltage		
Tap Position	Voltage (V)	Current (A)
1	26203	1.7
2	25564	1.7
3	24940	1.7
4	24317	1.8
5	23709	1.8
Low Voltage		
Voltage (V)		Current (A)
208		208.2


Rated Capacity	75	KVA
HV	24940GrdY/14400	V
LV	208Y/120	
Impedence	XXX	%
Use Condition	Outdoor	
Phase	3 Phase	
Vector Group	YnYn0	
Rated Frequency	60	Hz
Cooling Type	KNAN	

Product Code	285306		
Serial Number	XXXXX		
HV BIL	125	LV BIL	30
Winding Con.	HV: CU	LV: CU	
Temp. Rise	65		°C
Oil Capacity	75		GAL
Total Weight	2,160		LBS
Body Weight	730		LBS
Step-Up Operation:	No		

Tank must be solidly grounded - NON-PCB Oil

Biodegradable Natural Vegtable Oil

Wire Connection



Phasor Diagram



ANSI C57.12.34 - DOE 2016 Compliant - Manufactured xx/2022

LARSON MAGNETICS

Larson Magnetics LLC
Kemp, TX USA