

THREE PHASE PAD MOUNTED TRANSFORMER
MT-PML-R7-3P-GNF-2.5MVA-DE-LT-DF-A6-BB-CZ-2B4-M1



High Voltage		
Tap Position	Voltage (V)	Current (A)
1	4371	330.3
2	4264	338.5
3	4160	347.0
4	4056	355.9
5	3955	365.0
Low Voltage		
Voltage (V)		Current (A)
480		3007.1

Rated Capacity	2500	KVA
HV	4160GrdY/2400	V
LV	480V	
Impedence	XXX	%
Use Condition	Outdoor	
Phase	3 Phase	
Vector Group	YnD1	
Rated Frequency	60	Hz
Cooling Type	KNAN	

Product Code	292297	
Serial Number	XXXXXX	
HV BIL	60	LV BIL 30
Winding Con.	HV: AL	LV: AL
Temp. Rise	65	°C
Oil Capacity	310	GAL
Total Weight	11,534	LBS
Body Weight	4,918	LBS
Step-Up Operation:	No	

Tank must be solidly grounded - NON-PCB Oil

Biodegradable Natural Vegetable Oil



Maximum operating pressures of liquid preservation system _____ kPa (lbf/in2) positive and _____ kPa (lbf/in2) negative.
Tank designed for ____ kPa (lbf/in2) vacuum filling.
Liquid level below top surface of the highest point of the highest manhole flange at 25 °C _____ mm (in). Liquid level changes _____ mm (in) per 10 °C change in liquid temperature.

ANSI C57.12.34 - DOE 2016 Compliant - Manufactured xx/2022



Larson Magnetics LLC
Kemp, TX USA