IES ROAD REPORT
PHOTOMETRIC FILENAME : EPL-MJ-25W-LED-XX-CM.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] 193028
[TESTLAB] RADIANT IMAGING PROSOURCE
[TESTDATE] 2021-04-05 16:17:58
[ISSUEDATE] 2021-04-05 16:17:58
[MANUFAC] LARSON ELECTRONICS LLC
[LUMCAT] EPL-MJ-25W-LED-XX-CM-50K
[LUMINAIRE] CLASS 1 DIV 1 EXPLOSION PROOF LED MASON JAR FIXTURE
[MORE] CEILING MOUNT, 5000K
[LAMPPOSITION] 0,0
[OTHER] ZVISION 9107GT SYSTEM

CHARACTERISTICS



IES Classification	Type VS
Longitudinal Classification	Very Short
Lumens Per Lamp	3735.49 (1 lamp)
Total Lamp Lumens	3735.49
Luminaire Lumens	3735
Downward Total Efficiency	73 %
Total Luminaire Efficiency	100 %
Luminaire Efficacy Rating (LER)	150
Total Luminaire Watts	24.9
Ballast Factor	1.00
Upward Waste Light Ratio	0.27
Maximum Candela	552.68
Maximum Candela Angle	247.5H 46.5V
Maximum Candela (<90 Degrees Vertical)	552.68
Maximum Candela Angle (<90 Degrees Vertical)	247.5H 46.5V
Maximum Candela At 90 Degrees Vertical	394.86 (10.6% Lamp Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	431.86 (11.6% Lamp Lumens)
Cutoff Classification (deprecated)	Non-Cutoff

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : EPL-MJ-25W-LED-XX-CM.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	144.5	3.9	3.9
FM - Front-Medium (30-60)	560.6	15.0	15.0
FH - Front-High (60-80)	457.9	12.3	12.3
FVH - Front-Very High (80-90)	211.8	5.7	5.7
BL - Back-Low (0-30)	143.4	3.8	3.8
BM - Back-Medium (30-60)	543.4	14.5	14.6
BH - Back-High (60-80)	453.8	12.1	12.1
BVH - Back-Very High (80-90)	210.8	5.6	5.6
UL - Uplight-Low (90-100)	365.3	9.8	9.8
UH - Uplight-High (100-180)	643.2	17.2	17.2
Total	3734.7	99.9	100.0
BUG Rating	B1-U4-G2		

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : EPL-MJ-25W-LED-XX-CM.IES

CANDELA TABULATION

Vert. Angles	Horizontal Angles									
	0.0	22.5	45.0	67.5	90.0	112.5	135.0	157.5	180.0	202.5
0.0	398.71	398.71	398.71	398.71	398.71	398.71	398.71	398.71	398.71	398.71
0.5	400.77	400.89	395.95	399.27	395.65	398.33	392.73	397.74	397.91	398.04
1.0	392.04	402.51	387.93	399.09	387.70	397.13	394.29	391.87	394.14	399.92
1.5	388.46	391.93	381.38	389.18	384.22	394.30	399.32	389.65	400.43	390.51
2.0	386.73	386.09	377.53	384.49	382.13	394.64	396.98	394.54	405.28	388.12
2.5	389.72	382.72	376.59	380.87	382.15	396.08	394.44	404.98	404.53	399.70
3.0	396.31	381.56	376.62	375.56	382.07	395.06	393.58	406.88	404.25	401.07
3.5	401.38	383.31	372.51	369.00	379.38	394.66	396.40	404.42	406.33	394.25
4.0	401.38	385.67	369.75	367.31	377.99	394.95	397.98	402.03	407.77	388.43
4.5	401.21	386.60	371.46	370.40	378.54	393.02	398.16	401.57	407.06	388.42
5.0	399.47	388.26	372.79	372.88	377.99	389.51	398.34	394.96	403.83	393.46
5.5	398.72	386.55	369.88	374.68	377.32	386.00	398.46	389.66	398.22	396.81
6.0	397.02	388.70	366.62	374.80	376.80	385.01	397.84	388.59	392.95	392.23
6.5	392.95	388.99	365.47	373.64	380.55	383.39	398.73	389.15	390.55	388.59
7.0	393.76	385.79	368.21	371.50	384.71	380.38	398.47	390.29	389.46	386.54
7.5	394.89	384.00	373.26	369.79	383.17	378.11	395.96	396.33	393.52	387.02
8.0	392.74	384.07	375.24	371.92	379.68	375.64	391.79	396.96	392.27	386.05
8.5	393.52	384.41	370.45	380.02	374.02	375.71	390.38	394.10	388.32	390.99
9.0	391.32	385.57	364.15	387.06	371.08	373.66	392.33	388.19	383.36	391.84
9.5	381.40	383.93	359.44	390.58	369.84	368.94	392.68	383.36	377.19	387.21
10.0	369.67	379.71	357.74	391.74	368.92	362.54	390.92	382.47	370.98	383.61
10.5	365.12	375.18	357.40	380.02	366.38	357.07	386.29	385.83	368.97	383.90
11.0	365.65	376.84	360.77	364.98	365.61	355.38	379.14	386.01	376.79	389.52
11.5	358.95	369.99	365.76	352.50	364.07	357.69	376.85	378.88	377.31	389.19
12.0	355.42	363.29	363.58	349.04	359.13	361.03	373.79	376.14	382.00	384.50
12.5	354.55	366.87	359.44	350.66	354.82	361.83	371.38	372.71	383.52	381.87
13.0	351.34	369.32	355.20	350.41	353.53	358.37	372.47	368.32	380.64	382.24
13.5	345.82	364.33	351.56	345.47	351.79	352.05	373.18	370.58	377.01	381.09
14.0	342.93	354.40	354.80	340.39	345.13	349.10	365.90	371.56	375.87	373.42
14.5	337.51	350.89	354.28	338.13	337.41	350.10	361.47	370.67	374.79	367.05
15.0	332.47	352.63	352.65	337.55	331.70	350.67	361.30	369.49	372.84	361.74
15.5	331.52	355.67	352.91	334.56	331.16	350.21	361.63	366.06	369.81	359.38
16.0	329.08	357.95	353.91	333.67	331.64	354.68	355.94	360.04	366.40	358.96
16.5	323.90	354.39	347.33	333.20	333.28	363.62	349.56	355.84	361.00	356.40
17.0	316.28	345.49	338.96	328.77	330.64	372.23	343.45	352.66	356.27	351.47
17.5	310.43	334.24	333.86	318.74	325.17	371.40	341.05	347.76	354.78	347.39
18.0	308.38	331.09	332.31	311.73	320.54	364.57	337.23	341.34	353.03	340.55
18.5	308.08	330.46	326.50	309.93	318.74	356.51	332.55	333.50	350.42	332.05
19.0	310.81	332.15	324.80	310.20	319.41	352.97	328.48	328.81	346.84	324.18
19.5	319.12	341.18	327.24	311.04	321.71	353.26	322.68	323.60	341.49	319.16
20.0	320.21	345.03	319.35	309.74	324.18	356.17	316.93	317.81	337.85	315.49
20.5	306.16	329.96	308.72	306.62	322.31	354.10	311.23	312.49	334.62	309.76
21.0	296.16	318.81	311.30	303.44	321.12	344.11	306.89	306.57	331.79	307.27
21.5	301.26	319.92	309.79	306.21	317.26	330.87	304.51	301.99	329.32	310.24
22.0	312.42	324.47	305.89	309.62	314.74	323.52	304.81	299.16	325.22	318.31
22.5	314.77	325.54	304.21	309.37	315.04	318.24	308.38	299.01	321.79	323.43
23.0	305.15	316.22	307.91	302.13	315.91	314.18	309.88	301.66	317.95	318.22
23.5	297.23	310.52	309.19	301.21	315.38	312.72	305.42	305.35	318.87	312.08
24.0	300.31	314.34	310.10	302.39	316.73	310.98	299.11	309.23	317.86	313.25
24.5	306.66	321.32	312.90	302.55	319.44	310.15	295.61	306.08	316.02	317.96
25.0	311.70	328.21	313.19	301.72	319.92	312.64	298.00	296.77	315.41	322.02
25.5	313.51	326.23	318.29	296.59	319.22	315.40	303.44	292.26	317.82	322.42
26.0	314.79	321.17	322.44	295.06	315.19	319.54	305.47	292.39	322.56	317.11

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

26.5	324.53	321.67	324.26	299.75	309.76	325.95	306.20	296.54	323.05	310.00
27.0	343.76	328.14	328.27	306.32	308.29	325.58	306.35	300.16	324.19	310.40
27.5	373.65	337.60	331.87	313.22	312.56	327.27	306.03	299.87	323.67	317.83
28.0	408.82	346.96	338.73	321.67	320.65	325.77	307.79	300.39	321.54	329.90
28.5	437.96	359.07	349.14	330.38	329.18	326.05	314.89	302.08	320.59	343.59
29.0	444.71	366.23	362.26	341.51	337.25	328.90	323.98	305.69	323.19	356.34
29.5	437.81	373.70	377.81	354.41	344.39	334.83	332.55	311.51	331.37	363.43
30.0	410.89	388.24	393.34	371.25	356.71	337.76	342.75	322.42	340.61	374.02
30.5	389.50	402.69	405.95	394.26	373.86	341.17	352.63	335.27	350.16	393.74
31.0	390.82	416.88	414.61	411.79	394.01	343.82	365.30	346.11	357.32	413.36
31.5	403.27	430.19	422.07	419.45	412.92	347.39	378.41	358.36	364.34	433.09
32.0	420.05	436.16	431.87	409.50	419.76	353.79	393.41	371.61	375.97	442.51
32.5	451.90	440.77	441.92	392.99	414.60	363.88	407.24	387.51	387.32	442.24
33.0	469.34	442.67	451.37	368.05	402.59	380.55	407.58	401.15	399.42	431.11
33.5	452.51	440.57	458.39	359.36	388.83	393.26	395.01	408.50	410.25	415.15
34.0	423.64	439.90	474.99	365.70	377.64	403.23	379.88	405.52	422.96	398.45
34.5	405.57	440.45	489.44	379.83	376.30	412.50	367.79	390.11	434.14	392.81
35.0	406.35	445.44	487.02	404.70	386.13	417.93	366.36	368.48	438.04	403.72
35.5	413.54	457.46	478.16	425.87	404.88	423.39	373.73	359.43	440.67	431.73
36.0	426.80	469.75	487.52	439.80	429.16	431.00	389.36	358.11	450.18	458.38
36.5	441.33	472.39	498.15	460.67	445.85	434.77	413.06	368.08	459.86	472.04
37.0	455.09	469.87	501.06	472.56	453.43	438.17	434.70	391.44	467.45	485.57
37.5	469.98	474.84	502.90	463.64	466.05	445.40	456.44	424.27	475.82	498.53
38.0	485.37	485.71	503.11	440.51	471.57	453.44	470.71	444.35	490.58	504.05
38.5	492.44	492.89	509.05	417.92	464.60	459.81	468.88	462.91	496.99	495.52
39.0	486.79	494.67	513.23	401.76	452.41	460.99	449.18	476.74	484.46	480.59
39.5	474.87	500.83	516.79	394.61	441.05	455.45	422.84	470.63	468.24	465.13
40.0	466.94	513.91	512.79	400.18	432.83	452.37	402.90	448.59	464.89	457.31
40.5	464.69	516.65	503.29	413.65	431.33	449.85	396.85	424.63	465.30	457.19
41.0	470.70	506.84	495.54	428.01	439.93	447.78	398.50	406.88	463.97	468.95
41.5	479.14	501.03	495.56	442.03	449.92	452.55	405.94	402.65	469.49	482.86
42.0	485.35	502.23	496.20	453.10	455.39	460.57	416.83	406.91	477.97	491.01
42.5	486.93	505.88	495.26	464.47	456.25	470.06	431.00	415.41	482.91	493.88
43.0	487.40	507.89	494.83	475.35	459.81	482.60	445.73	423.32	486.85	501.80
43.5	490.17	507.69	497.17	482.37	470.70	484.75	464.32	432.61	495.62	513.64
44.0	496.62	508.26	499.20	484.99	485.45	480.58	479.41	449.16	503.28	522.37
44.5	506.01	508.81	500.02	482.45	493.39	474.27	485.39	466.46	503.40	522.40
45.0	513.48	507.51	502.06	478.65	494.16	471.44	483.45	478.40	498.60	514.52
45.5	518.46	505.50	506.54	475.83	492.18	471.05	481.49	479.62	492.06	506.15
46.0	522.51	504.78	509.68	474.86	490.09	472.74	482.05	477.59	488.70	505.78
46.5	525.03	506.18	511.24	473.09	489.77	473.85	479.74	479.37	486.96	509.27
47.0	526.70	506.13	510.62	469.63	489.25	473.58	471.73	486.98	486.65	511.93
47.5	524.63	503.39	509.06	464.86	486.98	475.25	455.90	489.78	489.47	508.41
48.0	518.26	501.77	507.70	461.93	482.29	479.74	443.30	481.52	496.08	503.76
48.5	511.31	502.42	502.06	463.12	478.68	484.62	437.81	467.46	501.10	503.47
49.0	507.98	504.77	494.81	466.30	478.04	487.45	440.75	457.39	506.18	506.85
49.5	505.93	505.55	489.06	470.08	476.47	486.81	447.54	456.91	508.58	510.24
50.0	504.46	505.61	485.03	473.96	473.86	485.09	455.52	459.76	508.16	510.41
50.5	503.27	505.62	482.80	478.14	470.46	482.85	461.01	459.46	503.88	510.61
51.0	504.59	502.79	482.06	485.00	469.00	481.10	466.01	459.68	499.06	508.05
51.5	507.83	499.25	481.80	493.15	470.55	478.28	470.80	462.13	493.42	506.69
52.0	511.89	495.32	482.40	498.63	474.46	476.12	475.49	467.93	485.86	506.49
52.5	512.96	493.27	483.60	502.80	479.88	472.15	479.56	474.20	481.91	508.22
53.0	511.46	492.53	486.00	503.29	486.18	468.82	480.07	477.30	479.63	510.89
53.5	508.91	492.13	487.75	499.65	492.35	467.25	480.16	478.32	477.22	513.72
54.0	507.01	491.04	488.78	495.15	495.72	468.26	480.88	479.78	475.60	515.62

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

54.5	505.88	488.84	489.36	491.62	495.13	471.26	481.54	482.13	475.99	517.19
55.0	504.96	486.65	488.34	487.81	492.72	472.97	482.22	484.46	477.02	517.83
55.5	502.34	484.78	486.00	482.92	490.35	475.17	480.01	486.95	478.33	519.03
56.0	498.01	483.14	484.11	477.30	486.69	476.83	474.03	489.09	479.84	517.68
56.5	494.44	481.25	481.64	471.95	479.95	477.97	465.15	489.68	482.45	513.37
57.0	491.45	479.00	477.81	469.20	472.46	478.86	457.04	486.66	485.26	506.10
57.5	489.74	476.17	474.22	467.59	464.25	478.96	451.48	480.73	487.09	498.92
58.0	488.40	473.52	471.50	465.74	459.43	477.86	448.97	473.67	486.92	492.72
58.5	487.48	470.85	469.82	463.01	456.68	476.00	446.80	465.45	484.97	487.21
59.0	486.53	469.00	468.94	460.54	454.85	474.11	444.50	455.91	481.91	483.09
59.5	485.29	467.64	468.21	459.85	453.86	471.24	443.25	448.56	477.19	479.31
60.0	485.01	466.90	468.10	460.88	453.78	468.34	442.23	444.84	472.62	476.93
60.5	485.73	465.50	468.74	462.97	455.03	463.83	440.71	443.90	468.19	475.61
61.0	486.41	464.48	469.56	465.75	455.54	458.39	440.06	443.76	464.66	475.08
61.5	486.18	463.54	470.33	468.20	455.43	454.27	440.81	443.72	461.37	475.23
62.0	485.09	462.86	470.69	469.75	455.99	450.67	442.67	443.92	458.29	476.07
62.5	483.51	462.30	471.07	470.53	456.48	449.30	445.33	445.69	456.09	477.37
63.0	481.24	462.14	471.40	470.38	455.74	449.07	447.28	448.19	454.76	478.42
63.5	478.48	462.14	471.10	468.90	454.10	450.39	448.59	450.61	454.34	478.82
64.0	475.90	462.23	470.82	465.77	451.86	452.88	449.56	452.34	454.89	479.10
64.5	473.10	462.09	469.93	461.99	449.31	456.17	449.09	453.27	456.20	478.37
65.0	470.55	462.07	468.94	457.56	446.68	459.05	446.14	454.48	457.46	476.87
65.5	467.59	461.83	467.32	453.73	444.91	461.47	441.98	454.14	459.00	474.32
66.0	464.40	461.15	465.32	450.53	443.81	463.98	437.53	451.78	460.37	471.40
66.5	461.75	459.75	462.77	447.51	441.92	465.08	432.59	446.74	461.54	468.05
67.0	458.63	458.27	460.14	445.26	440.34	464.49	429.27	441.40	461.76	463.86
67.5	455.47	456.69	458.26	443.45	439.36	462.41	427.25	435.96	461.15	459.90
68.0	452.79	455.38	456.59	442.60	437.88	459.10	425.68	432.09	459.70	455.80
68.5	450.48	453.87	455.26	442.31	435.05	455.21	423.64	430.16	458.41	451.80
69.0	449.09	451.66	454.07	442.04	430.99	451.84	421.49	429.05	457.69	448.43
69.5	447.92	449.58	452.63	441.33	427.58	448.61	419.98	428.06	456.86	444.49
70.0	446.69	447.28	451.53	440.21	424.38	446.44	418.87	426.74	455.41	441.54
70.5	445.03	445.23	451.02	438.73	421.26	444.35	417.87	425.59	453.20	439.47
71.0	442.65	443.92	450.42	437.74	419.30	442.97	416.63	423.99	451.33	438.18
71.5	440.05	442.77	449.19	436.24	418.61	442.54	415.75	421.46	449.94	437.36
72.0	436.99	441.84	447.28	435.01	418.60	442.43	415.67	419.08	448.49	437.03
72.5	433.85	440.47	445.76	432.80	418.42	443.18	416.38	417.25	447.73	437.17
73.0	430.83	439.07	444.76	430.20	417.09	444.54	416.51	415.95	447.09	437.39
73.5	427.57	437.59	443.35	427.62	415.33	445.58	415.25	414.37	446.44	437.50
74.0	424.90	436.52	440.94	424.54	414.00	445.99	412.30	412.43	445.72	436.29
74.5	422.02	435.36	439.13	421.11	412.81	445.60	409.25	410.70	444.98	433.82
75.0	419.75	433.82	438.27	417.88	411.29	444.76	405.76	408.08	444.00	430.47
75.5	417.76	432.68	437.29	415.83	409.87	443.12	402.59	405.06	442.54	426.76
76.0	415.59	431.71	436.69	414.35	409.08	440.30	399.36	401.80	441.24	423.31
76.5	413.59	430.95	436.83	412.80	406.52	436.74	395.36	398.63	440.30	419.61
77.0	411.13	429.83	436.51	411.51	402.60	432.96	390.94	396.79	439.42	415.56
77.5	408.56	427.81	435.56	409.27	400.22	430.54	386.44	395.29	437.36	411.77
78.0	406.03	426.37	434.51	406.27	399.55	428.96	383.58	393.55	435.01	408.20
78.5	403.21	425.49	433.21	403.55	399.47	428.03	381.78	391.38	433.60	406.62
79.0	400.83	424.87	432.35	400.79	399.48	427.30	380.88	388.66	433.00	406.38
79.5	398.46	423.83	431.12	398.54	399.05	426.18	380.77	386.45	432.20	406.10
80.0	396.14	422.32	429.16	396.17	398.12	425.76	379.52	384.56	431.68	405.11
80.5	394.21	420.65	426.48	393.40	397.24	425.52	378.49	383.29	430.59	404.30
81.0	392.01	418.67	424.21	391.21	396.79	424.79	378.49	381.51	428.68	404.58
81.5	389.58	416.55	421.54	388.69	396.21	424.44	378.80	378.64	426.72	404.20
82.0	386.97	413.63	418.31	386.44	395.23	423.74	378.47	376.28	424.55	402.71

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

82.5	384.44	410.19	414.66	383.84	391.81	422.58	376.36	374.74	422.29	400.46
83.0	381.79	407.16	411.01	380.63	388.17	420.17	372.77	373.65	418.64	396.44
83.5	378.41	404.46	408.11	377.44	384.77	415.65	368.30	372.33	415.27	391.52
84.0	375.18	401.90	405.52	373.88	381.51	411.13	362.85	369.90	411.38	386.62
84.5	371.78	399.40	403.43	370.60	379.31	406.03	357.75	367.34	406.92	381.60
85.0	368.11	397.43	401.97	367.27	377.17	402.35	353.21	364.15	403.53	377.54
85.5	365.10	396.07	400.55	364.13	375.73	399.75	349.04	360.79	400.10	373.94
86.0	362.26	394.76	399.54	361.54	374.50	398.09	346.09	357.05	397.39	371.59
86.5	360.23	393.71	398.52	359.62	373.60	396.43	343.62	353.12	395.38	369.75
87.0	358.04	392.87	397.08	357.74	372.88	395.27	342.26	350.27	394.04	368.38
87.5	356.34	391.89	395.68	356.23	372.37	395.00	341.61	347.73	393.10	368.06
88.0	354.71	390.83	393.70	354.49	371.50	394.90	341.20	346.02	392.44	367.79
88.5	352.52	389.40	391.55	352.65	370.13	394.79	341.31	344.78	392.00	367.54
89.0	350.21	387.60	389.16	350.49	368.41	394.39	341.61	344.09	391.26	367.35
89.5	346.82	385.81	386.16	347.55	366.34	393.31	341.07	343.97	390.35	367.02
90.0	343.08	383.41	383.22	344.12	363.37	391.51	338.90	343.60	389.19	365.61
90.5	339.14	380.78	380.02	339.67	360.51	388.65	334.81	342.68	387.15	362.55
91.0	334.79	377.54	376.58	335.43	357.35	384.26	330.29	341.17	384.32	358.89
91.5	330.94	374.01	373.38	331.38	354.12	379.96	325.15	338.56	380.59	354.90
92.0	327.31	370.79	370.00	327.12	351.39	375.26	320.92	335.38	376.02	350.63
92.5	323.42	367.38	367.04	323.59	348.41	371.45	316.98	331.45	371.76	346.90
93.0	320.06	364.29	364.10	320.17	345.79	368.34	313.90	327.71	367.88	343.41
93.5	316.02	361.61	361.79	317.01	343.18	365.48	311.07	324.32	364.09	340.80
94.0	312.50	358.67	359.72	314.11	340.61	362.99	308.05	321.05	361.09	338.47
94.5	308.99	356.27	357.22	310.71	338.34	360.26	305.46	318.44	357.73	336.04
95.0	305.17	353.99	354.87	307.76	335.64	357.64	302.88	315.92	354.90	334.23
95.5	301.62	352.09	352.29	304.21	333.43	355.23	300.69	313.77	352.40	332.19
96.0	297.73	349.44	349.66	301.09	331.21	352.60	298.69	311.49	350.05	330.09
96.5	294.09	346.70	347.29	297.77	329.06	350.15	296.66	309.20	347.79	327.99
97.0	291.05	343.82	344.88	294.76	326.99	347.61	294.94	306.95	345.47	325.59
97.5	287.61	340.60	342.28	292.04	324.97	345.45	293.09	304.14	343.53	323.50
98.0	284.16	337.24	339.28	288.79	323.04	343.40	291.33	301.70	341.59	321.27
98.5	280.19	333.81	336.78	286.14	320.94	341.33	289.55	299.12	339.20	319.03
99.0	276.78	330.68	333.97	283.07	318.69	339.61	287.36	296.41	336.97	316.73
99.5	273.49	327.43	331.06	279.68	316.38	337.81	285.04	293.88	334.38	314.28
100.0	269.41	324.02	328.45	276.54	313.88	336.17	282.18	290.85	332.16	312.17
100.5	265.57	321.47	325.48	272.97	311.51	334.06	279.40	288.24	329.54	309.47
101.0	261.46	318.50	322.90	269.69	308.73	331.41	276.45	285.72	326.24	306.84
101.5	257.90	315.60	320.17	266.29	305.70	328.77	273.15	282.89	323.41	304.21
102.0	254.80	313.01	316.66	262.32	302.99	325.21	270.23	280.43	320.19	301.12
102.5	251.49	310.55	313.07	258.59	300.00	321.93	267.38	277.62	317.24	298.16
103.0	248.53	308.30	309.47	254.51	297.15	318.69	265.13	275.09	314.61	294.61
103.5	245.15	305.27	305.63	251.14	294.44	315.38	262.99	272.39	311.54	291.30
104.0	242.30	302.51	301.87	247.83	291.41	312.65	260.73	269.22	308.47	287.96
104.5	239.14	299.62	298.21	244.39	288.86	309.63	258.46	266.28	305.23	284.39
105.0	235.61	296.46	295.42	241.04	285.86	307.06	255.77	263.12	302.17	281.69
105.5	232.17	293.78	292.30	237.42	282.95	304.21	253.17	260.07	299.39	278.97
106.0	228.00	290.77	289.25	234.31	280.16	301.18	250.53	257.15	296.60	276.19
106.5	224.88	287.89	286.46	231.25	277.00	298.44	247.50	253.91	293.77	273.40
107.0	221.64	285.39	283.08	227.98	274.28	295.33	244.89	251.00	290.48	270.37
107.5	217.99	282.54	280.08	225.19	270.89	292.54	242.09	248.02	287.39	267.49
108.0	215.15	280.02	276.87	222.14	267.72	289.58	238.78	245.30	284.39	264.14
108.5	212.12	276.81	273.98	219.46	264.82	286.11	235.69	242.52	280.84	260.77
109.0	209.38	273.58	270.91	216.75	261.43	282.91	232.04	239.11	277.47	257.35
109.5	206.50	270.96	267.52	213.73	258.25	278.70	228.60	235.98	273.96	253.15
110.0	203.40	268.00	264.28	211.11	254.88	275.11	225.11	232.10	270.84	249.46

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

110.5	201.12	265.16	260.64	208.06	251.71	272.04	221.21	228.65	267.65	245.71
111.0	198.69	262.18	257.47	205.38	248.31	268.60	217.97	225.23	264.14	242.54
111.5	196.22	259.47	254.10	202.56	244.51	265.63	214.34	221.58	261.03	239.35
112.0	193.81	256.75	250.26	199.40	241.07	262.65	211.42	218.29	257.57	235.57
112.5	191.18	253.28	246.81	196.79	237.40	259.24	208.13	214.66	254.69	232.04
113.0	188.49	250.26	243.20	193.80	234.16	256.10	205.38	211.34	251.73	228.30
113.5	185.87	246.64	239.73	191.13	230.97	252.70	202.71	208.29	248.34	224.65
114.0	183.34	242.94	236.47	188.30	227.49	249.58	199.76	204.82	245.33	220.97
114.5	180.84	239.38	232.45	185.49	224.46	246.21	197.03	201.79	241.67	216.92
115.0	177.99	235.03	228.80	182.74	220.88	243.08	194.37	198.68	238.28	213.42
115.5	175.46	230.96	224.26	180.04	217.38	239.70	191.43	196.07	234.88	209.55
116.0	172.66	226.72	220.41	177.61	213.84	236.05	188.73	193.46	231.18	206.06
116.5	169.82	222.39	216.25	175.36	210.01	232.78	185.65	190.62	227.85	202.47
117.0	167.29	217.97	211.85	172.65	206.24	229.09	182.72	187.78	223.98	198.28
117.5	164.67	213.44	207.39	170.25	201.80	225.39	179.75	184.41	220.37	194.40
118.0	161.93	209.40	203.02	167.24	198.20	221.82	176.59	181.33	216.71	190.26
118.5	158.90	204.45	198.10	164.63	194.54	217.58	173.64	178.29	212.73	186.56
119.0	156.39	200.44	193.70	162.03	190.68	213.77	170.36	174.87	209.21	183.09
119.5	153.55	196.16	188.80	159.14	187.04	209.54	167.38	171.78	205.19	179.47
120.0	150.80	190.67	184.56	156.45	182.85	205.89	164.50	168.35	201.14	176.34
120.5	148.10	186.01	180.40	154.14	179.16	202.19	161.45	165.39	196.54	172.63
121.0	145.27	181.00	175.79	151.85	175.42	197.91	158.67	162.50	191.30	169.06
121.5	142.53	176.56	171.69	149.71	171.22	193.87	155.62	159.27	186.78	165.26
122.0	139.72	172.19	167.00	147.52	167.61	189.13	152.69	156.63	181.94	160.74
122.5	136.74	167.42	162.76	145.52	163.64	184.71	149.72	153.73	177.84	156.53
123.0	133.77	163.07	158.37	143.17	159.78	179.95	146.24	150.87	173.92	151.67
123.5	130.98	158.15	153.09	140.43	155.30	174.96	143.03	148.04	169.67	147.28
124.0	128.05	152.11	147.79	137.85	150.37	170.14	139.32	145.01	165.68	143.23
124.5	125.24	146.47	141.21	134.75	146.30	165.53	135.93	142.09	160.24	138.64
125.0	121.78	141.11	134.07	132.13	142.37	160.49	132.41	138.34	154.19	134.45
125.5	118.61	134.76	126.73	129.51	137.91	155.86	128.30	134.78	148.02	130.01
126.0	115.32	128.78	119.16	126.73	132.99	149.40	124.89	131.55	141.49	125.78
126.5	110.24	121.35	112.76	124.30	125.01	142.65	121.51	128.14	135.75	120.12
127.0	105.39	115.66	105.90	121.72	117.83	135.24	118.82	125.15	129.09	111.54
127.5	100.59	108.36	98.93	118.90	110.78	128.28	115.97	122.25	122.31	104.55
128.0	96.25	101.29	91.73	115.07	104.93	121.68	110.70	119.42	115.10	98.44
128.5	91.27	94.34	84.36	110.33	99.60	113.43	104.26	114.29	106.76	93.50
129.0	85.05	86.86	78.49	105.33	92.76	106.02	96.42	106.27	99.79	86.71
129.5	80.00	80.61	72.66	98.94	86.69	99.51	90.38	99.16	91.97	79.36
130.0	75.01	73.17	65.48	93.85	81.25	92.52	85.79	93.11	84.12	74.22
130.5	69.35	66.59	59.71	89.22	75.74	86.16	80.19	88.74	75.75	69.02
131.0	62.66	60.94	55.21	83.68	70.10	78.55	73.73	83.47	69.28	63.32
131.5	57.88	55.60	50.71	79.05	63.35	72.37	67.24	76.99	64.43	57.57
132.0	54.69	50.56	45.08	72.78	58.02	67.11	63.13	71.64	57.81	53.86
132.5	46.51	44.37	39.62	67.09	54.84	61.24	59.67	66.38	51.53	48.76
133.0	41.53	38.39	35.79	62.93	47.31	55.89	55.50	61.97	45.78	42.31
133.5	37.67	36.68	31.85	57.69	41.97	49.95	46.62	56.31	38.75	37.13
134.0	33.05	32.85	27.75	51.36	37.93	44.89	41.69	49.47	37.41	33.55
134.5	26.83	28.90	24.06	44.63	35.08	41.32	38.91	43.88	32.58	29.37
135.0	23.92	25.01	20.31	37.40	31.12	36.97	34.68	38.16	27.63	25.33
135.5	21.87	22.11	17.50	37.53	26.11	32.35	28.87	35.67	23.07	21.91
136.0	17.95	19.30	14.62	31.83	22.77	28.02	23.97	30.38	20.02	18.91
136.5	16.45	16.14	12.07	28.24	19.45	24.51	19.32	24.93	17.48	15.21
137.0	13.54	13.35	10.46	25.59	16.19	20.48	17.72	20.67	14.75	12.00
137.5	10.74	10.77	7.92	21.94	13.62	17.56	15.41	17.70	11.84	9.54
138.0	8.58	8.03	5.52	19.58	10.71	14.78	11.60	15.58	9.63	7.36

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

138.5	5.94	6.12	4.25	16.83	8.35	11.38	10.27	12.99	7.69	5.50
139.0	4.79	4.45	2.98	13.53	5.82	9.50	7.27	10.85	6.22	4.10
139.5	2.39	3.03	2.48	11.45	4.22	6.97	5.79	8.66	4.71	2.59
140.0	1.99	2.74	2.22	8.63	2.43	5.01	4.37	6.93	4.07	2.10
140.5	1.83	2.55	2.07	6.57	2.08	3.91	2.41	4.90	3.64	1.85
141.0	1.68	2.31	1.85	3.13	1.98	3.44	2.19	3.49	3.37	1.72
141.5	1.50	2.18	1.72	2.83	1.88	3.19	2.03	3.14	3.02	1.53
142.0	1.39	2.00	1.57	2.63	1.79	2.96	1.81	2.80	2.74	1.37
142.5	1.30	1.86	1.40	2.44	1.65	2.76	1.72	2.50	2.61	1.30
143.0	1.18	1.77	1.33	2.21	1.53	2.63	1.56	2.26	2.38	1.21
143.5	1.06	1.65	1.19	2.03	1.33	2.45	1.50	2.09	2.09	1.15
144.0	1.05	1.57	1.12	1.84	1.17	2.29	1.34	1.97	1.92	1.08
144.5	0.90	1.46	0.94	1.72	1.13	2.20	1.25	1.83	1.80	1.01
145.0	0.89	1.33	0.86	1.58	1.04	2.04	1.17	1.75	1.71	0.99
145.5	0.81	1.24	0.72	1.55	0.93	1.77	1.07	1.65	1.51	0.92
146.0	0.81	1.20	0.70	1.47	0.86	1.63	1.00	1.57	1.46	0.88
146.5	0.65	1.14	0.73	1.39	0.87	1.56	0.89	1.56	1.42	0.80
147.0	0.58	1.02	0.57	1.29	0.78	1.42	0.85	1.39	1.35	0.76
147.5	0.47	1.02	0.58	1.16	0.75	1.30	0.83	1.32	1.29	0.69
148.0	0.42	0.95	0.59	1.09	0.65	1.23	0.76	1.31	1.16	0.66
148.5	0.42	0.90	0.46	0.99	0.63	1.19	0.74	1.25	1.17	0.58
149.0	0.40	0.87	0.45	0.93	0.54	1.12	0.63	1.13	1.10	0.58
149.5	0.37	0.78	0.41	0.84	0.53	1.04	0.59	1.12	1.08	0.52
150.0	0.32	0.72	0.39	0.85	0.48	0.97	0.51	0.98	0.98	0.46
150.5	0.34	0.73	0.40	0.78	0.49	0.96	0.46	0.92	0.90	0.43
151.0	0.28	0.69	0.35	0.75	0.42	0.86	0.45	0.83	0.88	0.40
151.5	0.27	0.66	0.33	0.69	0.42	0.84	0.40	0.77	0.84	0.38
152.0	0.27	0.58	0.29	0.66	0.33	0.79	0.36	0.70	0.75	0.30
152.5	0.27	0.56	0.28	0.64	0.30	0.75	0.35	0.71	0.70	0.29
153.0	0.23	0.50	0.25	0.56	0.29	0.72	0.30	0.67	0.68	0.28
153.5	0.26	0.51	0.28	0.59	0.26	0.66	0.27	0.59	0.66	0.31
154.0	0.24	0.47	0.26	0.54	0.29	0.57	0.31	0.58	0.58	0.23
154.5	0.24	0.50	0.21	0.53	0.25	0.61	0.27	0.57	0.56	0.26
155.0	0.19	0.42	0.24	0.46	0.24	0.56	0.26	0.50	0.48	0.23
155.5	0.21	0.47	0.22	0.52	0.24	0.52	0.16	0.54	0.47	0.23
156.0	0.23	0.40	0.16	0.42	0.19	0.46	0.26	0.49	0.46	0.21
156.5	0.24	0.40	0.19	0.45	0.20	0.44	0.17	0.51	0.45	0.20
157.0	0.24	0.39	0.17	0.47	0.22	0.46	0.20	0.45	0.42	0.21
157.5	0.21	0.38	0.20	0.45	0.19	0.47	0.24	0.45	0.42	0.21
158.0	0.19	0.37	0.20	0.42	0.19	0.45	0.21	0.42	0.41	0.21
158.5	0.20	0.32	0.16	0.43	0.22	0.42	0.14	0.39	0.40	0.19
159.0	0.22	0.35	0.19	0.37	0.22	0.43	0.16	0.38	0.37	0.21
159.5	0.22	0.36	0.19	0.40	0.24	0.46	0.22	0.41	0.39	0.19
160.0	0.22	0.29	0.20	0.40	0.13	0.39	0.21	0.37	0.36	0.17
160.5	0.21	0.36	0.17	0.34	0.21	0.39	0.20	0.38	0.37	0.21
161.0	0.26	0.36	0.17	0.39	0.21	0.39	0.19	0.37	0.37	0.19
161.5	0.22	0.35	0.17	0.36	0.16	0.36	0.19	0.40	0.36	0.15
162.0	0.21	0.34	0.24	0.39	0.19	0.34	0.19	0.35	0.36	0.20
162.5	0.17	0.36	0.12	0.32	0.19	0.37	0.19	0.34	0.37	0.17
163.0	0.19	0.30	0.19	0.34	0.17	0.35	0.20	0.36	0.36	0.17
163.5	0.20	0.31	0.17	0.34	0.13	0.34	0.16	0.34	0.29	0.13
164.0	0.20	0.35	0.19	0.31	0.20	0.28	0.20	0.31	0.33	0.14
164.5	0.19	0.33	0.13	0.32	0.19	0.32	0.16	0.33	0.31	0.17
165.0	0.20	0.34	0.22	0.34	0.19	0.30	0.17	0.32	0.36	0.17
165.5	0.23	0.30	0.16	0.35	0.17	0.35	0.14	0.32	0.35	0.15
166.0	0.19	0.29	0.19	0.30	0.15	0.33	0.16	0.33	0.30	0.15

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

166.5	0.23	0.30	0.14	0.28	0.12	0.35	0.15	0.32	0.33	0.21
167.0	0.14	0.29	0.15	0.28	0.15	0.31	0.21	0.33	0.31	0.15
167.5	0.23	0.28	0.17	0.33	0.20	0.31	0.17	0.32	0.30	0.14
168.0	0.15	0.25	0.10	0.31	0.16	0.29	0.14	0.33	0.34	0.16
168.5	0.16	0.26	0.16	0.29	0.10	0.29	0.14	0.29	0.29	0.13
169.0	0.17	0.26	0.19	0.29	0.19	0.28	0.14	0.29	0.32	0.15
169.5	0.20	0.26	0.17	0.27	0.14	0.30	0.17	0.24	0.28	0.14
170.0	0.19	0.25	0.13	0.25	0.16	0.29	0.19	0.24	0.24	0.17
170.5	0.15	0.26	0.14	0.23	0.12	0.28	0.15	0.25	0.21	0.16
171.0	0.16	0.26	0.15	0.23	0.09	0.26	0.12	0.20	0.26	0.12
171.5	0.16	0.20	0.15	0.27	0.16	0.25	0.20	0.24	0.20	0.19
172.0	0.17	0.22	0.14	0.25	0.11	0.27	0.12	0.25	0.23	0.14
172.5	0.19	0.22	0.14	0.26	0.15	0.25	0.16	0.22	0.27	0.12
173.0	0.21	0.22	0.13	0.14	0.14	0.23	0.11	0.16	0.19	0.12
173.5	0.16	0.21	0.15	0.22	0.16	0.24	0.17	0.21	0.28	0.15
174.0	0.15	0.20	0.10	0.22	0.10	0.21	0.11	0.20	0.19	0.13
174.5	0.14	0.17	0.12	0.20	0.15	0.21	0.10	0.22	0.21	0.19
175.0	0.19	0.16	0.13	0.23	0.10	0.21	0.13	0.19	0.19	0.14
175.5	0.13	0.22	0.12	0.20	0.13	0.20	0.15	0.24	0.19	0.12
176.0	0.16	0.17	0.13	0.19	0.14	0.22	0.12	0.21	0.15	0.13
176.5	0.14	0.20	0.10	0.19	0.14	0.16	0.13	0.22	0.19	0.09
177.0	0.12	0.17	0.12	0.15	0.13	0.21	0.11	0.16	0.15	0.09
177.5	0.12	0.15	0.09	0.21	0.11	0.17	0.12	0.17	0.16	0.10
178.0	0.15	0.16	0.10	0.19	0.09	0.17	0.13	0.21	0.17	0.13
178.5	0.17	0.15	0.11	0.15	0.14	0.14	0.09	0.21	0.14	0.10
179.0	0.19	0.19	0.14	0.16	0.12	0.17	0.12	0.15	0.19	0.11
179.5	0.15	0.15	0.10	0.15	0.13	0.15	0.13	0.19	0.14	0.10
180.0	0.16	0.12	0.13	0.15	0.10	0.16	0.14	0.19	0.15	0.09

Vert. Angles	**Horizontal Angles**						
	225.0	**247.5**	**270.0**	**292.5**	**315.0**	**337.5**	**360.0**
0.0	398.71	398.71	398.71	398.71	398.71	398.71	398.71
0.5	394.96	398.59	396.19	396.10	400.13	397.39	400.77
1.0	394.77	402.72	393.54	397.70	402.63	394.44	392.04
1.5	401.30	395.76	400.77	404.46	402.99	396.65	388.46
2.0	395.33	387.70	405.49	411.54	404.42	396.27	386.73
2.5	386.03	393.40	406.02	416.16	410.25	399.01	389.72
3.0	390.84	403.02	400.75	419.50	417.65	401.55	396.31
3.5	396.43	405.84	399.78	426.62	424.25	400.27	401.38
4.0	390.85	398.49	402.17	430.79	425.96	402.79	401.38
4.5	383.18	395.85	402.72	427.94	426.38	402.23	401.21
5.0	384.13	397.01	410.33	420.92	420.66	398.15	399.47
5.5	392.45	401.38	413.98	413.23	409.28	395.70	398.72
6.0	397.96	404.20	410.33	403.98	399.11	390.62	397.02
6.5	392.18	396.13	405.78	397.92	398.22	387.28	392.95
7.0	387.04	388.15	397.05	392.85	396.89	383.92	393.76
7.5	385.14	385.07	394.61	387.54	392.79	378.68	394.89
8.0	382.80	383.99	398.87	387.08	389.92	375.21	392.74
8.5	388.04	383.99	403.83	386.68	391.71	371.73	393.52
9.0	395.35	384.97	407.59	384.30	394.50	370.05	391.32
9.5	392.10	383.50	404.87	382.69	391.92	363.28	381.40
10.0	382.34	375.87	396.03	379.16	382.62	355.38	369.67
10.5	374.79	367.02	382.10	378.79	373.14	352.00	365.12
11.0	370.63	366.99	371.16	381.19	366.31	347.73	365.65
11.5	372.96	369.00	367.19	381.15	361.31	340.89	358.95

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

12.0	379.32	369.52	368.75	377.48	358.41	336.89	355.42
12.5	384.89	369.05	371.19	369.33	354.82	343.59	354.55
13.0	384.28	370.45	373.38	360.27	352.50	355.13	351.34
13.5	378.29	373.88	373.69	355.72	354.60	358.52	345.82
14.0	366.77	376.21	372.86	352.26	356.97	350.63	342.93
14.5	358.31	375.14	369.75	347.93	355.93	340.06	337.51
15.0	355.96	371.33	365.93	344.52	352.48	336.14	332.47
15.5	354.74	366.74	359.08	339.83	348.98	337.39	331.52
16.0	352.20	361.60	354.66	334.83	348.27	339.64	329.08
16.5	350.53	358.85	350.25	329.33	349.80	337.88	323.90
17.0	351.80	358.78	345.60	327.22	347.98	331.58	316.28
17.5	354.73	356.12	340.55	322.81	343.88	326.39	310.43
18.0	352.15	353.14	335.80	317.57	338.68	321.96	308.38
18.5	341.10	350.60	331.07	312.38	334.78	328.17	308.08
19.0	326.54	346.56	327.80	309.76	332.56	340.18	310.81
19.5	317.28	338.96	324.96	310.44	330.31	337.15	319.12
20.0	311.41	327.86	322.50	315.28	328.14	323.44	320.21
20.5	308.13	315.57	319.41	313.92	313.67	317.51	306.16
21.0	308.00	309.74	316.42	301.01	311.87	311.81	296.16
21.5	312.90	312.51	316.26	296.95	312.79	309.59	301.26
22.0	319.31	315.44	312.95	301.69	311.04	309.57	312.42
22.5	319.88	317.52	310.90	309.50	314.30	312.04	314.77
23.0	311.36	321.12	307.37	304.97	319.07	316.93	305.15
23.5	303.27	330.04	310.26	296.19	314.92	320.06	297.23
24.0	305.91	332.78	310.39	296.27	309.62	320.83	300.31
24.5	310.79	331.10	309.22	304.32	313.88	321.99	306.66
25.0	309.11	330.27	306.98	316.77	321.80	321.15	311.70
25.5	301.50	331.83	304.86	331.90	326.59	322.87	313.51
26.0	291.41	337.10	309.68	340.31	325.81	327.76	314.79
26.5	289.83	341.30	316.22	353.65	326.39	332.93	324.53
27.0	296.44	339.62	322.60	376.48	329.76	338.76	343.76
27.5	307.61	341.28	333.36	410.51	340.31	350.63	373.65
28.0	317.39	346.81	351.12	446.41	358.73	364.27	408.82
28.5	327.81	355.62	365.71	455.75	376.55	381.91	437.96
29.0	339.83	367.42	382.79	443.30	390.06	401.13	444.71
29.5	354.51	381.57	407.62	418.06	404.33	423.76	437.81
30.0	374.85	395.27	427.87	394.66	412.59	431.70	410.89
30.5	391.26	412.28	438.39	374.53	421.08	441.64	389.50
31.0	407.38	425.84	432.20	360.14	439.34	441.31	390.82
31.5	423.16	430.95	420.29	375.17	461.63	441.97	403.27
32.0	432.27	440.98	409.99	401.91	475.50	442.51	420.05
32.5	423.64	447.86	402.36	420.24	475.61	444.91	451.90
33.0	400.25	456.82	402.18	480.84	473.28	453.54	469.34
33.5	375.69	463.48	415.65	493.39	466.39	473.20	452.51
34.0	365.97	477.23	435.42	472.10	458.72	488.92	423.64
34.5	374.72	489.46	453.44	449.18	454.25	500.70	405.57
35.0	398.72	501.80	463.00	439.89	464.46	511.19	406.35
35.5	433.47	515.12	472.45	440.88	481.18	515.66	413.54
36.0	455.58	520.13	485.94	446.66	501.00	515.55	426.80
36.5	481.31	524.17	489.31	458.24	509.56	507.69	441.33
37.0	501.47	521.34	482.87	465.88	516.74	506.27	455.09
37.5	502.49	518.71	472.45	467.95	514.89	519.92	469.98
38.0	484.69	525.49	468.84	470.57	511.28	540.88	485.37
38.5	460.56	528.43	473.50	480.62	510.47	551.80	492.44
39.0	437.39	525.38	487.01	490.34	511.14	545.47	486.79
39.5	422.44	528.87	496.94	494.26	511.75	537.83	474.87

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : EPL-MJ-25W-LED-XX-CM.IES

CANDELA TABULATION - (Cont.)

40.0	418.23	535.75	497.80	490.55	515.60	535.31	466.94
40.5	428.63	533.13	497.00	482.58	518.70	528.80	464.69
41.0	445.71	528.00	510.10	482.69	519.78	522.96	470.70
41.5	465.09	526.47	525.81	487.17	524.39	516.01	479.14
42.0	478.41	523.63	527.60	497.22	529.95	509.40	485.35
42.5	489.63	521.67	521.86	512.38	535.97	509.42	486.93
43.0	498.36	518.39	519.69	527.01	533.13	512.69	487.40
43.5	506.74	519.59	523.98	533.35	527.01	516.36	490.17
44.0	513.87	525.59	528.31	536.18	524.39	519.58	496.62
44.5	514.49	532.47	530.45	537.06	525.26	523.66	506.01
45.0	510.51	539.57	535.64	539.35	527.01	527.11	513.48
45.5	508.51	548.09	538.04	539.02	532.58	528.89	518.46
46.0	510.85	552.02	542.52	534.76	540.55	528.91	522.51
46.5	516.36	552.68	543.72	528.22	544.59	525.96	525.03
47.0	519.34	551.47	539.79	525.05	544.81	521.07	526.70
47.5	516.00	548.52	534.44	522.87	544.92	517.61	524.63
48.0	508.56	540.77	530.18	520.13	543.83	516.49	518.26
48.5	501.27	536.40	526.80	519.26	537.27	514.61	511.31
49.0	499.41	526.05	524.83	521.55	529.53	511.20	507.98
49.5	502.66	520.86	523.53	525.82	524.39	508.51	505.93
50.0	505.87	518.25	521.45	531.50	519.26	504.47	504.46
50.5	507.32	515.62	520.03	533.89	514.24	501.56	503.27
51.0	509.86	512.54	519.04	532.26	511.52	499.20	504.59
51.5	514.83	508.18	518.50	529.75	510.20	498.69	507.83
52.0	521.59	505.93	517.41	529.53	509.22	498.57	511.89
52.5	527.77	507.02	517.95	532.26	509.77	497.15	512.96
53.0	528.40	509.23	519.59	534.76	511.52	495.81	511.46
53.5	525.68	511.36	519.70	535.54	512.28	495.59	508.91
54.0	523.65	512.22	519.49	527.33	512.94	495.93	507.01
54.5	521.73	513.50	520.58	521.23	513.04	495.92	505.88
55.0	519.73	515.30	521.23	513.35	513.91	494.85	504.96
55.5	517.59	515.42	520.25	506.38	514.36	494.59	502.34
56.0	515.09	514.82	516.97	499.65	514.24	494.63	498.01
56.5	512.95	512.08	512.49	495.63	513.58	494.04	494.44
57.0	509.32	509.21	505.62	492.82	511.40	492.63	491.45
57.5	503.35	506.17	499.07	490.08	507.03	490.97	489.74
58.0	496.96	501.37	492.85	488.82	501.69	489.13	488.40
58.5	490.99	497.30	488.04	489.40	496.01	486.34	487.48
59.0	486.69	494.76	486.18	490.91	491.31	482.65	486.53
59.5	483.30	492.67	485.52	491.26	487.71	478.64	485.29
60.0	480.36	489.30	484.98	490.55	484.55	474.04	485.01
60.5	479.60	485.37	484.88	489.73	482.36	470.22	485.73
61.0	479.84	481.58	484.11	488.99	480.84	466.57	486.41
61.5	480.17	478.02	483.67	488.33	479.75	463.17	486.18
62.0	481.02	476.62	482.91	488.12	478.97	461.83	485.09
62.5	482.24	475.45	482.04	487.36	478.97	461.72	483.51
63.0	482.10	475.81	481.27	486.16	479.85	463.24	481.24
63.5	480.54	477.11	481.60	484.22	480.29	465.39	478.48
64.0	479.18	480.34	481.71	480.48	480.84	468.02	475.90
64.5	477.43	483.63	480.72	476.53	481.60	470.68	473.10
65.0	474.48	486.89	479.09	472.52	481.93	472.92	470.55
65.5	471.60	489.23	476.14	467.72	481.71	473.68	467.59
66.0	468.43	490.47	473.20	463.84	480.84	473.35	464.40
66.5	465.01	490.20	469.92	460.40	478.65	471.64	461.75
67.0	461.24	488.82	465.22	458.23	475.26	468.54	458.63
67.5	457.18	486.74	460.96	456.42	471.12	463.94	455.47

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

68.0	454.22	483.06	457.36	455.25	466.97	458.91	452.79
68.5	451.49	479.10	454.31	454.68	462.28	453.65	450.48
69.0	450.14	474.28	451.36	453.84	458.02	447.66	449.09
69.5	449.23	469.45	448.30	452.44	453.65	442.48	447.92
70.0	447.66	464.46	445.90	449.59	448.85	438.46	446.69
70.5	445.37	460.58	444.69	446.27	445.78	437.01	445.03
71.0	442.26	457.57	444.15	442.81	444.37	437.66	442.65
71.5	438.67	455.92	444.59	438.44	445.47	439.77	440.05
72.0	435.68	456.54	445.02	434.48	447.53	441.37	436.99
72.5	432.91	459.12	445.78	430.75	449.83	443.30	433.85
73.0	430.81	460.88	446.01	427.65	451.36	445.42	430.83
73.5	428.91	461.36	446.66	424.85	453.65	446.86	427.57
74.0	425.95	462.75	446.44	422.20	455.50	447.32	424.90
74.5	422.89	464.15	443.82	420.11	455.94	446.17	422.02
75.0	420.17	464.60	441.20	418.20	454.96	444.05	419.75
75.5	418.35	463.82	439.24	417.04	453.54	441.14	417.76
76.0	416.73	462.35	435.82	415.96	451.57	437.51	415.59
76.5	414.96	459.42	433.43	414.29	448.62	431.76	413.59
77.0	412.64	455.48	430.22	412.31	444.15	427.00	411.13
77.5	410.72	450.49	428.25	409.54	438.03	423.50	408.56
78.0	409.71	445.61	426.24	405.55	432.43	421.43	406.03
78.5	408.23	441.36	424.53	401.99	430.14	420.06	403.21
79.0	405.52	438.06	423.84	398.63	427.92	418.70	400.83
79.5	402.07	435.03	423.47	396.15	425.76	417.75	398.46
80.0	397.70	431.86	421.33	394.09	424.31	417.40	396.14
80.5	393.90	429.32	419.53	391.69	423.97	417.30	394.21
81.0	390.74	428.79	420.29	389.52	424.38	416.82	392.01
81.5	387.84	429.43	420.09	386.87	424.14	415.68	389.58
82.0	385.77	429.45	417.28	384.35	422.67	413.81	386.97
82.5	383.74	428.45	415.39	382.03	421.72	410.70	384.44
83.0	381.84	426.72	413.50	379.18	420.45	407.41	381.79
83.5	379.84	423.50	410.34	376.05	416.98	403.33	378.41
84.0	377.40	418.91	405.73	372.21	412.36	398.98	375.18
84.5	374.84	414.70	400.72	368.95	407.25	395.97	371.78
85.0	371.32	410.93	397.15	365.98	402.58	393.14	368.11
85.5	367.69	407.95	394.70	363.53	398.91	390.63	365.10
86.0	364.01	405.16	392.85	360.92	395.21	388.40	362.26
86.5	359.80	402.49	390.93	358.38	392.84	387.36	360.23
87.0	356.34	400.82	388.82	356.08	391.14	386.93	358.04
87.5	353.16	399.72	387.61	354.08	390.15	386.05	356.34
88.0	350.74	398.84	386.81	352.74	390.01	385.69	354.71
88.5	348.72	398.42	386.29	351.65	390.18	385.48	352.52
89.0	347.21	398.49	386.85	349.62	390.54	384.58	350.21
89.5	346.27	397.70	387.70	346.66	390.32	382.37	346.82
90.0	345.20	394.86	386.78	342.49	388.71	378.87	343.08
90.5	343.31	390.78	383.95	337.38	385.70	375.23	339.14
91.0	340.04	386.11	378.92	332.78	381.04	371.49	334.79
91.5	334.89	381.19	374.04	328.05	375.92	367.39	330.94
92.0	329.83	377.02	368.33	324.30	370.77	363.74	327.31
92.5	324.47	373.95	364.01	320.56	365.51	359.98	323.42
93.0	320.13	370.85	360.66	316.76	361.14	357.01	320.06
93.5	316.45	368.00	357.46	313.13	356.68	354.02	316.02
94.0	312.66	364.75	354.91	308.84	353.31	351.22	312.50
94.5	309.31	361.63	352.50	304.72	350.35	348.49	308.99
95.0	305.34	358.45	349.69	300.17	347.54	345.35	305.17
95.5	301.77	355.72	347.27	296.41	345.05	342.41	301.62

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

96.0	298.23	353.02	344.59	292.61	343.00	338.98	297.73
96.5	294.48	350.11	342.31	288.47	340.92	335.89	294.09
97.0	291.39	347.89	340.10	285.08	339.17	333.10	291.05
97.5	288.37	345.90	337.74	281.55	337.37	330.38	287.61
98.0	285.90	343.22	335.44	278.62	335.57	328.29	284.16
98.5	283.48	340.70	332.76	275.91	333.59	325.61	280.19
99.0	280.86	338.09	330.02	272.80	331.07	323.05	276.78
99.5	278.54	335.75	327.12	269.72	328.30	320.49	273.49
100.0	275.71	332.92	323.89	266.17	325.04	317.77	269.41
100.5	272.91	329.68	321.12	262.57	321.88	314.94	265.57
101.0	269.83	326.59	318.10	258.84	318.48	311.59	261.46
101.5	266.05	322.79	315.17	254.46	314.87	308.54	257.90
102.0	262.31	319.41	312.09	250.53	311.71	305.72	254.80
102.5	258.12	316.25	308.97	246.29	307.56	302.79	251.49
103.0	254.57	312.91	305.82	242.61	304.37	299.88	248.53
103.5	251.25	309.85	301.84	239.19	301.61	296.37	245.15
104.0	247.65	306.75	298.90	235.41	298.92	293.05	242.30
104.5	244.80	304.17	295.66	232.16	296.43	289.79	239.14
105.0	241.96	301.26	293.16	228.89	293.62	286.27	235.61
105.5	239.51	298.04	290.60	226.12	290.85	283.03	232.17
106.0	236.80	295.14	287.60	223.49	287.95	279.86	228.00
106.5	234.53	291.71	284.70	220.69	284.79	277.06	224.88
107.0	232.19	288.42	281.59	218.14	281.73	273.83	221.64
107.5	229.39	284.65	278.27	214.89	278.25	270.53	217.99
108.0	226.71	280.45	274.81	211.56	274.73	267.95	215.15
108.5	223.74	276.94	271.01	208.20	271.38	265.32	212.12
109.0	220.16	273.22	267.49	204.67	267.74	262.10	209.38
109.5	216.65	269.60	263.87	201.61	264.41	258.69	206.50
110.0	212.82	265.87	259.92	198.33	260.65	254.92	203.40
110.5	209.72	262.78	256.38	195.41	257.40	251.40	201.12
111.0	206.52	259.55	252.39	192.54	254.15	247.13	198.69
111.5	203.79	255.84	248.85	189.64	250.44	243.13	196.22
112.0	201.22	252.46	245.51	187.28	246.85	239.12	193.81
112.5	198.55	248.68	241.93	184.69	242.86	234.57	191.18
113.0	196.24	245.33	238.51	182.54	239.21	230.48	188.49
113.5	192.64	241.72	234.69	180.47	235.41	225.98	185.87
114.0	189.20	237.72	231.40	178.16	231.57	222.28	183.34
114.5	186.06	233.89	228.24	175.88	227.79	218.08	180.84
115.0	182.97	229.42	224.48	173.18	223.30	213.39	177.99
115.5	180.36	225.39	220.97	170.71	219.00	209.36	175.46
116.0	177.57	221.09	216.75	168.24	214.57	204.90	172.66
116.5	175.37	216.38	212.44	165.32	209.80	200.70	169.82
117.0	173.06	212.10	208.06	162.67	205.76	196.70	167.29
117.5	170.23	207.34	203.32	159.75	201.39	192.08	164.67
118.0	167.66	202.97	199.18	157.23	197.33	188.06	161.93
118.5	164.82	198.48	194.89	154.77	193.32	183.72	158.90
119.0	161.48	193.63	191.18	152.09	189.21	179.80	156.39
119.5	158.29	189.36	187.29	149.64	185.45	175.56	153.55
120.0	154.93	184.58	183.09	147.07	180.93	170.89	150.80
120.5	152.27	180.17	179.31	144.83	176.62	166.56	148.10
121.0	149.41	175.10	174.91	142.74	172.27	161.63	145.27
121.5	146.67	167.91	170.99	140.31	167.35	156.79	142.53
122.0	144.25	162.22	167.00	138.00	162.58	151.84	139.72
122.5	139.15	156.44	162.23	135.02	157.01	146.37	136.74
123.0	132.94	149.72	157.56	131.95	151.54	141.60	133.77
123.5	127.21	143.38	151.93	128.76	145.80	136.66	130.98

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

124.0	120.19	135.96	146.94	125.05	140.72	131.19	128.05
124.5	110.98	128.15	141.96	121.84	135.71	125.15	125.24
125.0	102.99	120.05	136.48	118.36	129.31	118.49	121.78
125.5	93.57	112.20	131.47	115.43	123.23	112.47	118.61
126.0	83.28	102.44	125.05	112.68	117.43	104.91	115.32
126.5	75.39	91.11	119.74	107.52	112.28	97.74	110.24
127.0	65.80	82.24	114.92	102.54	106.43	90.76	105.39
127.5	58.90	71.40	108.78	98.23	98.87	83.77	100.59
128.0	55.27	60.13	102.21	94.93	92.11	77.83	96.25
128.5	46.32	54.86	94.40	90.72	85.37	70.15	91.27
129.0	42.72	40.80	87.74	84.97	79.84	63.94	85.05
129.5	35.59	33.30	81.61	80.18	73.81	58.37	80.00
130.0	34.64	24.90	75.00	75.51	66.00	54.78	75.01
130.5	30.26	19.08	68.50	69.82	59.84	48.01	69.35
131.0	26.42	15.24	61.91	63.90	54.48	41.26	62.66
131.5	23.54	13.34	57.15	57.51	49.73	37.06	57.88
132.0	21.00	11.82	52.10	54.37	43.98	32.59	54.69
132.5	20.78	10.28	44.83	46.20	36.66	28.86	46.51
133.0	20.70	8.45	37.99	41.34	34.62	24.90	41.53
133.5	19.81	7.30	35.48	37.18	31.20	21.45	37.67
134.0	19.57	6.43	32.22	32.07	27.82	18.91	33.05
134.5	21.14	5.32	27.93	28.19	24.29	16.09	26.83
135.0	21.75	4.40	24.20	25.95	21.01	13.33	23.92
135.5	20.66	3.98	22.08	21.56	18.37	10.46	21.87
136.0	21.42	3.44	19.00	18.84	15.70	8.31	17.95
136.5	21.09	2.41	15.72	17.37	13.17	6.24	16.45
137.0	19.64	2.07	13.22	12.71	10.86	4.39	13.54
137.5	18.41	1.68	10.48	10.41	8.42	3.86	10.74
138.0	15.40	1.45	7.61	7.69	5.93	2.70	8.58
138.5	12.41	1.42	5.50	5.67	4.63	2.36	5.94
139.0	10.51	1.39	4.03	4.47	3.17	2.21	4.79
139.5	7.53	1.37	3.27	2.22	2.88	2.03	2.39
140.0	5.52	1.32	2.93	1.97	2.65	1.92	1.99
140.5	2.51	1.23	2.74	1.85	2.57	1.71	1.83
141.0	2.40	1.17	2.55	1.62	2.39	1.62	1.68
141.5	2.27	1.15	2.34	1.55	2.15	1.52	1.50
142.0	2.13	1.08	2.25	1.43	2.04	1.38	1.39
142.5	1.97	1.01	2.10	1.27	1.92	1.12	1.30
143.0	1.87	0.89	2.00	1.19	1.79	1.10	1.18
143.5	1.77	0.81	1.91	1.07	1.66	0.99	1.06
144.0	1.58	0.79	1.77	1.00	1.60	0.95	1.05
144.5	1.48	0.69	1.66	0.88	1.54	0.84	0.90
145.0	1.41	0.59	1.59	0.88	1.43	0.81	0.89
145.5	1.31	0.60	1.46	0.80	1.34	0.69	0.81
146.0	1.30	0.65	1.36	0.69	1.25	0.65	0.81
146.5	1.15	0.64	1.32	0.69	1.19	0.58	0.65
147.0	1.09	0.65	1.27	0.64	1.10	0.52	0.58
147.5	1.08	0.53	1.21	0.53	1.05	0.47	0.47
148.0	1.00	0.50	1.14	0.56	0.99	0.44	0.42
148.5	0.93	0.46	1.05	0.43	0.89	0.42	0.42
149.0	0.88	0.42	1.06	0.41	0.89	0.39	0.40
149.5	0.81	0.39	1.03	0.39	0.82	0.36	0.37
150.0	0.78	0.38	0.94	0.34	0.75	0.34	0.32
150.5	0.77	0.31	0.93	0.26	0.72	0.29	0.34
151.0	0.65	0.30	0.81	0.32	0.67	0.30	0.28
151.5	0.67	0.32	0.79	0.31	0.58	0.26	0.27

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

152.0	0.60	0.32	0.73	0.26	0.56	0.24	0.27
152.5	0.62	0.29	0.66	0.25	0.54	0.17	0.27
153.0	0.54	0.27	0.60	0.24	0.53	0.23	0.23
153.5	0.52	0.24	0.54	0.24	0.48	0.21	0.26
154.0	0.53	0.25	0.51	0.21	0.47	0.20	0.24
154.5	0.51	0.22	0.57	0.24	0.46	0.17	0.24
155.0	0.49	0.17	0.53	0.22	0.42	0.17	0.19
155.5	0.49	0.20	0.47	0.17	0.40	0.21	0.21
156.0	0.46	0.17	0.47	0.17	0.44	0.15	0.23
156.5	0.42	0.25	0.41	0.19	0.40	0.17	0.24
157.0	0.45	0.20	0.46	0.16	0.36	0.16	0.24
157.5	0.44	0.21	0.45	0.16	0.36	0.17	0.21
158.0	0.42	0.20	0.44	0.25	0.33	0.13	0.19
158.5	0.44	0.21	0.37	0.16	0.36	0.13	0.20
159.0	0.38	0.21	0.40	0.21	0.34	0.16	0.22
159.5	0.36	0.19	0.39	0.17	0.36	0.19	0.22
160.0	0.30	0.23	0.41	0.19	0.37	0.15	0.22
160.5	0.36	0.21	0.35	0.15	0.33	0.15	0.21
161.0	0.36	0.14	0.41	0.19	0.31	0.11	0.26
161.5	0.32	0.19	0.35	0.20	0.33	0.16	0.22
162.0	0.31	0.20	0.39	0.19	0.31	0.15	0.21
162.5	0.34	0.20	0.37	0.19	0.31	0.15	0.17
163.0	0.34	0.22	0.32	0.20	0.31	0.14	0.19
163.5	0.33	0.13	0.37	0.20	0.30	0.17	0.20
164.0	0.36	0.17	0.33	0.19	0.31	0.20	0.20
164.5	0.28	0.14	0.32	0.15	0.31	0.20	0.19
165.0	0.27	0.16	0.30	0.16	0.34	0.15	0.20
165.5	0.29	0.21	0.33	0.14	0.27	0.15	0.23
166.0	0.28	0.14	0.36	0.14	0.31	0.17	0.19
166.5	0.28	0.14	0.28	0.13	0.27	0.12	0.23
167.0	0.31	0.21	0.32	0.16	0.31	0.13	0.14
167.5	0.27	0.15	0.30	0.17	0.23	0.15	0.23
168.0	0.27	0.15	0.27	0.14	0.28	0.11	0.15
168.5	0.29	0.16	0.27	0.15	0.28	0.17	0.16
169.0	0.30	0.17	0.26	0.14	0.28	0.12	0.17
169.5	0.25	0.15	0.27	0.15	0.24	0.14	0.20
170.0	0.24	0.16	0.23	0.14	0.25	0.16	0.19
170.5	0.24	0.16	0.23	0.16	0.23	0.13	0.15
171.0	0.28	0.16	0.25	0.13	0.22	0.09	0.16
171.5	0.22	0.10	0.24	0.13	0.20	0.10	0.16
172.0	0.22	0.14	0.22	0.13	0.26	0.13	0.17
172.5	0.24	0.16	0.21	0.20	0.23	0.11	0.19
173.0	0.20	0.11	0.23	0.13	0.20	0.17	0.21
173.5	0.23	0.15	0.20	0.13	0.23	0.13	0.16
174.0	0.21	0.14	0.26	0.11	0.22	0.10	0.15
174.5	0.24	0.14	0.21	0.16	0.20	0.16	0.14
175.0	0.17	0.14	0.16	0.12	0.23	0.12	0.19
175.5	0.16	0.13	0.24	0.13	0.14	0.11	0.13
176.0	0.16	0.13	0.20	0.13	0.16	0.10	0.16
176.5	0.20	0.15	0.17	0.12	0.16	0.13	0.14
177.0	0.19	0.11	0.15	0.12	0.17	0.14	0.12
177.5	0.19	0.10	0.16	0.09	0.21	0.11	0.12
178.0	0.15	0.09	0.23	0.15	0.13	0.10	0.15
178.5	0.22	0.09	0.13	0.10	0.15	0.11	0.17
179.0	0.21	0.09	0.16	0.13	0.15	0.12	0.19
179.5	0.14	0.08	0.15	0.15	0.15	0.13	0.15


Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

180.0	0.21	0.10	0.15	0.13	0.15	0.12	0.16

IES ROAD REPORT
PHOTOMETRIC FILENAME : EPL-MJ-25W-LED-XX-CM.IES

COEFFICIENTS OF UTILIZATION




FLUX DISTRIBUTION

	Lumens	Percent Of Lamp
Downward Street Side	1374.8	36.8
Downward House Side	1351.3	36.2
Downward Total	2726.1	73.0
Upward Street Side	497.6	13.3
Upward House Side	510.9	13.7
Upward Total	1008.5	27.0
Total Flux	3734.6	100.0

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : EPL-MJ-25W-LED-XX-CM.IES

POLAR GRAPH




Maximum Candela = 552.68 Located At Horizontal Angle = 247.5, Vertical Angle = 46.5
1 - Vertical Plane Through Horizontal Angles (247.5 - 67.5) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (46.5) (Through Max. Cd.)

Photometric Toolbox Professional Edition - Copyright 2002-2015 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.


IES ROAD REPORT
PHOTOMETRIC FILENAME : EPL-MJ-25W-LED-XX-CM.IES

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE



Distance In Units Of Mounting Height

Values Based On 10 Foot Mounting Height


Luminaire Lumens
Uplight
643
482
322
161
100
100
90
90
80
80
60
60
30
30
0
Back
Front