Stainless Steel Ultraviolet Fluorescent Fixture - Hazardous Location Lighting - Glass Lens - Marine NEW-

Part # HALSS-48-2L-BL-UV

Made in the USA
The Larson Electronics HALSS-48-2L-BL-UV Hazardous Area Fluorescent Ultraviolet Light Fixture is approved Class 1 Division 2 Groups A, B, C and D, UL 1598/A listed and is specifically designed to withstand high vibration locations and the rigors of wet and corrosive marine environments.

The HALSS-48-2L-BL-UV hazardous area ultraviolet fluorescent light fixture is designed for use in wet areas and saltwater-marine environments where corrosion resistance is critical to equipment longevity and safety. This Class 1 Division 2 rated fixture is constructed of non-corrosive materials including a stainless steel housing, a poured in gasket for reliable sealing and a glass diffuser. Corrosion resistant stainless steel latches secure the lamp cover to the housing and provide a firm lock against the poured in seal to prevent drips and water intrusion.

This fixture is 844 rated and Class 1 Division II, Groups A, B, C, D approved. The HALSS-48-2L-BL-UV also carries 1598A and 595 outdoor marine ratings and meets US Coast Guard specifications.

This fixture is designed for heavy duty use in applications where intense vibration and corrosive environments may be encountered. Stainless steel construction, high impact acrylic lamp covers, and a Class 1 Division 2 ETL rating make this light ideal for hazardous locations that require illumination with above average dependability.

NOTE ON LAMPS: This fixture comes equipped with ultraviolet lamps that produce radiation in the UV-A, UV-B, or UV-C wavelength ranges.

Ultraviolet Wavelength Options:
Ultraviolet A Wavelength produces a longer wave between the 400nm - 315nm spectrum.
Ultraviolet B Wavelength produces a shorter wave than the UVA wavelength. These medium sized waves range from 315nm - 280nm.
Ultraviolet C wavelength is reduced exceptionally. Some refer to this wave as the 'germicidal' wave. The Ultraviolet C Wavelength ranges from 280nm - 100nm.

Standard Flange Brackets: Stainless steel bracket mounts attached at each end of the fixture enables it to be simply secured to any surface. The mounts provide flexibility in setting the angle of the fixture. Three through holes provide sufficient mounting for any environment.

LARSON ELECTRONICS LLC • 9419 E US HWY 175 • KEMP, TX 75143
p: 1-800-369-6671 • intl: 903-498-3363 • f: 903-498-3364 • sales@larsonelectronics.com

Suggested Applications: The HALSS-48-2L is designed for marine wet and damp locations, where corrosion resistant fluorescent lights are required. This lamp is also ideal for locations where heavy vibratory conditions are present. This includes petrochemical facilities, lubrication pits, oil drilling rigs, crew quarters, solvent/cleaning areas, water treatment areas, processing plants and marine loading docks.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Flange type stainless steel mounts attached at each end of the fixture enables it to be simply secured to any surface.
3. Fixture housing constructed of 14 gauge stainless steel..
4. Relamping done via stainless steel snap locking latches which allow the operator to remove the door and access the lamps.
5. Lamp cover-diffuser constructed of glass.
6. 3/4 inch, threaded access hole for wiring conduit.

Lamp Options

Lamp options for UV fixtures are determined by UV range.
Operators can specify when ordering- UVA (-A suffix), and UVB,(-B suffix) UVC (-C suffix).
T8 bulbs designed for UV applications are used.
The bulb and ballast in our UV fluorescent fixtures are unique to UV applications.
UVA(-A) 400nm - 315nm
UVB (-B) 315nm - 280nm
UVC (-C) 280nm - 100nm

Specifications / Additional Information

HALSS-48-2L-BL-UV Hazardous Location Lighting

ETL Listing: United States

Dimensions: W-9 1/2" L-54 " H-6 3/4"

Weight: 35 Lbs

Total Watts: 80W*

Voltage: Universal 120-277V AC 50/60 H
Total Intensity: 16.2 W
Lamp Life Expectancy: 5,000 Hours
Radiant Efficiency: 202.5 mW/w
Light Color: Ultraviolet - UVA, UVB, or UVC
Wavelengths: 400-315Nm (UVA), 315-280Nm (UVB), or 280-100Nm (UVC)

ETL Ratings

Class 1 Division 2, Groups A, B, C, D
UL 595 outdoor marine
UL 1598A Marine Type (Salt water)
Meets US Coast Guard specifications.

LARSON ELECTRONICS LLC • 9419 E US HWY 175 • KEMP, TX 75143
p: 1-800-369-6671 • intl: 903-498-3363 • f: 903-498-3364 • sales@larsonelectronics.com

Beam Angle: 150°
Ambient Operating Temp Range:-30° C to +70°C
Operating Temp Rating: T4C Rated
Minimum Operating Temp: -30°C
Maximum Case Temp: +90°C
Housing Material: 304 Stainless Steel

Lens Material: Hardened Glass

Mounting: Surface Standard - Pendant Optional
Wiring Hub: 3/4" NPT

Warranty: 5 Years**

*Wattage totals are lamps only and may vary with different lamps.
**5 year warranty replacement on this light (or LED bulbs for light fixtures with removable LED bulbs). After 30 days, the customer ships the failed light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, Larson Electronics will ship a new replacement. Please click here to see our 5 Year Warranty pamphlet.

Special Orders- Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-498-3363
E-mail: sales@larsonelectronics.com

Scroll Down to Purchase-

Part #: HALSS-48-2L-BL-UV (106068)
In Stock: Yes