



Low Profile - Explosion Proof Light - 4 Foot, 4 Lamp - Class 1 Division 2 - Paint Spray Booth Rated

Part # HALD-48-4L-T8

Made in the USA

The Larson Electronics HALD-48-4L-T8 Hazardous Area Fluorescent Light Fixture is designed to provide a thin fixture profile that allows the maximum use of available space. This fluorescent fixture is U.S./Canada approved Class 1 Division 2, Groups A, B, C and D - Class 2 Division 2, Groups F and G and designed for paint spray booths and locations where flammable chemical/petrochemical vapors are present. THIS FIXTURE IS NOT APPROPRIATE FOR SURFACE MOUNT APPLICATIONS.

*****PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO THIS HAZARDOUS LOCATION LIGHT FIXTURE*****

The HALD-48-4L-T8 Explosion Proof fixture is a 4 foot long, 4 lamp, Class 1 Division 2 hazardous area fluorescent light and ideal for use in paint spray booths and hazardous locations where space for lighting fixtures is limited. This fixture is T3C temperature rated, comes standard with F32-T8/841 bulbs and features an integrated magnetic paint spray system cutoff switch that is activated when this fixture's lamp door is opened. The lamps are protected by a steel framed, hinged, 3/16" thick glass door that provides direct front access to the four lamps. The lamp housing is only 2 and 1/4 inches thick, designed for recessed mounting, constructed of 20 Gauge steel and coated with a baked on white enamel finish.

This fixture is multi-voltage capable and is approved for use paint spray booths. The HALD-48-4L provides operators in hazardous locations with a reliable and durable, low profile lighting solution that provides added safety through the inclusion of an integral paint spray cutoff switch that shuts down paint spray systems when the fixture is opened.

NOTE: The integral magnetic cutoff switch included with this fixture is activated when the lamp door is opened. This switch is not intended to directly control light operation and requires the addition of a separate solid state relay which is then used to control actual system operation. The Cutoff Switch acts only as an activator for an external relay and is rated for 10 watts at a maximum of 300 VAC. Overloading the switch through improper connection will result in switch failure. It is recommended that a certified electrician make any installations and reviews of relay connections intended to take advantage of this light's cutoff switch. The HALD-48-4L has an electronic multi-voltage ballast and works with 120 Volt 60 HZ, 220 Volt 50 HZ, 240 Volt 60 HZ and 277 Volts 60 HZ.



Mounting: This fixture is designed for recessed mounting and requires a mounting hole to be made in booth panels capable of accommodating the fixture housing in order to provide the maximum amount of space in paint spray booth enclosures. Once mounted, this fixture's glass door frame will extend 3/8" into the spray booth.

Applications: Paint spray booths and enclosed spaces where flammable chemical/petrochemical vapors are present.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost.
3. Fixture constructed of 20 gauge steel with a baked on white enamel finish.
4. Relamping done via fixed hinge, drop open door.
5. Reflectors coated with high gloss reflective enamel finish.
6. 1/2 NPT conduit hub for wiring.
7. Integrally mounted magnetic cutoff switch for connection to relay system allows automatic shutoff of paint system when fixture door is opened.
8. Low profile fixture housing is only 2 1/4" thick, providing the maximum amount of room in space limited spray booth enclosures.

Lamp Options

F32-T8/841 – 2950 lumens per bulb, 24,000 hours life, 4100 Kelvin color

Specifications / Additional Information

HALD-48-4L-T8 Paint Booth Fixture

UL Listing: United States - Canada

Dimensions: W-14 1/2" L-50" D-2 1/4"

Magnetic Switch: 10 watts@300 VAC Max

Total Watts: 128 watts

Voltage: Multi- 120-277 Volts 50/60 Hz

Total Lumens: STD-T8 Bulbs 11,800

Lamp Life Expectancy: STD-T8 Bulbs 24,000 Hours

Efficiency: STD-T8- Bulbs 92 Lumens per Watt

Operating Temp Range: T3C Rated

Beam Angle: N/A

Color Temp: 4100- F32-T8/841 Bulbs

Mounting: Recessed Panel Mounting

Wiring Hub: 1/2 inch threaded NPT

E.T.L Ratings

Class 1 Division 2, Groups A, B, C, D

Class 2 Division 2 Groups F,G

T3C (160 degree C)

ETL listed U.S. and Canada

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

Email: sales@larsonelectronics.com



*3 year warranty replacement on this LED light (or LED bulbs for light fixtures with removable LED bulbs). After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, Larson Electronics will ship a new replacement. [Please click here to see our 3 Year Warranty pamphlet.](#)

Scroll Down to Purchase- Please note: 2 day lead time on this light.

[Click here to view the Explosion Proof Light Temperature Rating Table](#)

Part #: HALD-48-4L-T8 (48562)
In Stock: Yes