



Stainless Steel Fluorescent Light Fixture - Glass Lens - Corrosion Resistant – Marine

Part # HALSS-48-2L-BL

Made in the USA

The Larson Electronics HALSS-48-2L-BL Hazardous Area Fluorescent Light Fixture is ETL approved Class 1 Division 2 Groups A, B, C and D - 1598A listed and is specifically designed to withstand high vibration locations and the rigors of wet and corrosive marine environments.

[Click here to see the LED version of this light.](#)

The HALSS-48-2L-BL hazardous area fluorescent light fixture is designed for use in wet areas and saltwater-marine environments where corrosion resistance is critical to equipment longevity and safety. This Class 1 Division 2 rated fixture is constructed of non-corrosive materials including a stainless steel housing, a poured in gasket for reliable sealing and a glass diffuser. Corrosion resistant stainless steel latches secure the lamp cover to the housing and provide a firm lock against the poured in seal to prevent drips and water intrusion.

This fixture is 844 rated and Class 1 Division II, Groups A, B, C, D approved. The HALSS-48-2L-BL also carries 1598A and 595 outdoor marine ratings and meets US Coast Guard specifications.

This fixture is designed for heavy duty use in applications where intense vibration and corrosive environments may be encountered. Stainless steel construction, high impact acrylic lamp covers, and a Class 1 Division 2 ETL rating make this light ideal for hazardous locations that require illumination with above average dependability.

Note on Lamps: This fixture comes equipped with F54-T5/850/HO – 54 Watt lamps producing 5,000 lumens per bulb, a 5000 Kelvin color and a 20,000 hour rated service life. We offer F48-T12/HO – 4050 lumens per bulb, 12,000 hours life, 4100 Kelvin color and F32-T8/841 – 2950 lumens per bulb, 24,000 hours life, 4100 Kelvin color tubes as lamp options for this fixture. The HALSS-48-2L has an electronic multi-voltage ballast and works with 120 Volt 60 HZ, 220 Volt 50 HZ, 240 Volt 60 HZ and 277 Volts 60 HZ. 24 Volt models available on request for an additional \$100 per unit charge.



Standard Flange Brackets: Stainless steel bracket mounts attached at each end of the fixture enables it to be simply secured to any surface. The mounts provide flexibility in setting the angle of the fixture. Three through holes provide sufficient mounting for any environment.

Suggested Applications: The HALSS-48-2L is designed for marine wet and damp locations, where corrosion resistant fluorescent lights are required. This lamp is also ideal for locations where heavy vibratory conditions are present. This includes petrochemical facilities, lubrication pits, oil drilling rigs, crew quarters, solvent/cleaning areas, water treatment areas, processing plants and marine loading docks.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Flange type stainless steel mounts attached at each end of the fixture enables it to be simply secured to any surface.
3. Fixture housing constructed of 14 gauge stainless steel..
4. Relamping done via stainless steel snap locking latches which allow the operator to remove the door and access the lamps.
5. Lamp cover-diffuser constructed of glass.
6. 1/2 inch, threaded access hole for wiring conduit.

Lamp Options

F54-T5/850/HO – 54 Watt, 5000 lumens per bulb, 20,000 hours life, 5000 Kelvin color

F48-T12/HO – 4050 lumens per bulb, 12,000 hours life, 4100 Kelvin color

F32-T8/841 – 2950 lumens per bulb, 24,000 hours life, 4100 Kelvin color

F48-T8/HO - 48 watt, 4000 lumens per bulb, 18,000 hours life, 4100 Kelvin color
(Suffix -T8HO)

Specifications / Additional Information

HALSS-48-2L-BL Hazardous Location Lighting

ETL Listing: United States

Dimensions: W-9 1/2" L-54 " H-6 3/4"

Weight: 35 Lbs

Total Watts: 108 watts*

Voltage: 120V-60hz 220V-50hz 240V-60hz 277V-60hz (24V on Request)

Total Lumens: STD-T5-HO Bulbs 10,000

Lamp Life Expectancy: STD-T5-HO

Bulbs 20,000 Hours

ETL Ratings

Class 1 Division 2, Groups A, B, C, D

595 outdoor marine

1598A Marine Type (Salt water)



Efficiency: STD-T5-HO Bulbs 92 Lumens per Watt

Operating Temp Range: T4C Rated -30 C to 70 C

Minimum Operating Temp: -30 C

Maximum Case Temp: 90 C

Beam Angle: N/A

Color Temp: 5000K- T5-HO Bulbs

Mounting: Flange type stainless steel

Wiring Hub: 1/2 inch threaded

Meets US Coast Guard specifications.

*Wattage totals are lamps only and may vary with different lamps.

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-498-3363

E-mail: sales@larsonelectronics.com

Scroll Down to Purchase-

Part #: HALSS-48-2L-BL (68723)

In Stock: Yes