

GAU-LTL-500W-LED

480 Watt High Intensity LED Light - 64,800 Lumens - 100-277V AC - High Mast / Stadium Lighting

Product ID: 104751

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: GAU-LTL-500W-LED

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

GAU-LTL-500W-LED High Mast LED Light

Lamp Type: CREE® LED

Dimensions: 22.92"-L x 14.51"-W x 5.153"-D

Weight: 32.35 Lbs

Total Watts: 480

Total Lumens: 64,800

Luminous Efficiency: 135 lm/w

Beam Configurations: 10° Spot, 24° Wide Spot, 38° Narrow Flood, 60° Flood, or 90° Wide Flood

LED Color Temperature: Cool White - 5500-6500K

LED Life Expectancy: 80,000 hours

Optics Efficiency: 98% - PMMA High Transmittance Optics

Led Drive %: 90%

Voltage: 100-277V AC or 127-431V DC

Amp Draw: 5A @ 120V, 2.5A @ 240V, 2.67A @ 277V

Wiring: 2.5" Pigtail w/ Flying Leads

Mounting: Flat Surface Trunnion Mount U-Bracket

Materials: Die Cast Aluminum Housing, PMMA (Acrylic) Optics

Housing Color: Powder Coated Black

Ambient Temperature Range: -40°C to +80°C

Waterproof Rating: IP67

Quick Summary

1000 Watt Metal Halide Replacement

Ambient Op Temp -40C to +80C

Ideal for Light Towers & LED Retrofits

98% Transmission High Purity PMMA Optics

Multiple LED Banks for Heat Dispersion

135 Lumens Per Watt Efficiency

70% Lumen Retention after 80,000 Hours

UL1012 Compliant

UL60950-1 Compliant

CE Certified

RoHS Compliant

IP67 Rated Waterproof

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671


Intl: 1-903-270-1187

Fax: 1-903-765-7664

E-mail: sales@larsonelectronics.com

The GAU-LTL-500W-LED High Mast (Stadium) LED Flood Light offers intense light output and is ideal for flood lighting, high mast lighting, light towers, as well as industrial and outdoor lighting applications. Producing 64,800 lumens, a 4.25 amp draw at 120V, 80,000 hour service life, 100-277 volt compatibility, and IP67 waterproof rating, this LED flood light provides operators with a rugged and powerful LED alternative to 1000 watt metal halide lamps that uses little power and can withstand rugged use and abusive conditions.


The GAU-LTL-500W-LED LED light from Larson Electronics produces 64,800 lumens of high intensity light while drawing only 480 watts at 5 amps from a 120 volt electrical system. Forty-Eight CREE® high output LEDs producing 1,350 lumens each are arranged in rows and paired with PMMA high purity optics to produce a well focused 24° wide spot beam that is ideal for providing far reaching concentrated illumination while still covering a substantial amount of area. We also offer optional optics with 10° spot, 38° narrow flood, 60° flood, and 90° wide flood beam spreads. The spot beams are tightly focused and are designed for high elevation mounting to achieve distance, making spot versions ideal for high mast and spots lighting. The flood beams are designed to provide more light over a larger area nearer the fixture, making flood versions ideal for use as dedicated work and area lights.



[Click Photo to Enlarge](#)




[Click Photo to Enlarge](#)



[Click Photo to Enlarge](#)

GAU-LTL-500W-LED lights are ideal replacements for fragile and hot running 1000 watt metal halide lamps. They offer low power requirements, high durability and a versatile mounting system that makes these LED light emitters a superior lighting solution for demanding applications where power and reliability is critical. The heavy duty design and high power of these LED lights also makes them suitable for a wide array of applications including but not limited to: high mast lighting, light towers, light plant LED retrofits, military, mining, industrial manufacturing, machine visioning, security and law enforcement, commercial structure illumination, sport complexes, billboards, race tracks, and parking lots to name a few.



[Click Photo to Enlarge](#)

The above image shows the comparison of the traditional (4) 1500 watt metal halides light fixtures mounted to a 30' light tower (left) to (4) GAU-LTL-500W-LED 480 watt LED light fixtures mounted to a 30' light tower. The area being illuminated by each tower is 300' in length and 250' in width. Unlike the metal halide light fixtures, there are no hot spots with these LED fixtures.

This high output LED light fixture provides an even beam spread over the targeted work area without overcast, glare, light spillage, and wasted illumination. Color rendering is also increased with LED light plants, providing a more realistic night vision that more closely resembles natural daylight illumination.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units feature individual heat sinks per bank of six LEDs to control heat buildup rather than utilizing a single housing to dissipate heat. This allows for more thorough cooling of the LEDs for extended operating periods. This allows the LEDs to be driven at up to 90% capacity without overheating or visible loss of light output. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 80,000 hours.

Durability: As well as unparalleled heat control, the GAU-LTL-500W-LED series of LED lights from Larson Electronics also offer IP67 rated construction that is designed to withstand extremes of environmental and operating conditions. These units can withstand rapid temperature changes of -40° Celsius to +80° Celsius, are waterproof, and resist ingress of dust, dirt and humidity. The housings are formed from die cast aluminum and the optics are high transmission PMMA with 98% light transmittance. The CREE® LEDs help these units achieve resistance to vibrations and are rated at 70% lumen maintenance after 80,000 hours of use. We recommend these LED lights for use in applications where a lot of vibration, dust, dirt, dampness and abusive working conditions are encountered.



In-use Image of GAU-LTL-500W-LED Mounted

Mounting: Each unit is equipped with a back mount trunnion style mounting bracket that allows the light to be attached to flat surfaces and adjusted through 160° of vertical movement. To adjust the unit after mounting, the user simply loosens the set screws located on either side of the unit, moves it into the desired position, then re-tightens the screws. The base of the mounting trunnion is equipped with several machined slots which allow users to utilize existing mounting holes and slide the unit for precise mount positioning.



Frequently Asked Questions (FAQ)

There are no Faqs



Image: GAU-LTL-500W-LED



Image: GAU-LTL-500W-LED



Image: GAU-LTL-500W-LED




Image: GAU-LTL-500W-LED

GAU-LTL-500W-LED

Product ID: 104751

Warranty: 60 Months.

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

GAU-LTL-500W-LED-Beam Angle-Color Temp

Example: GAU-LTL-500W-LED-10SP-50K

Beam Angle	
10° SPOT	-10SP
24° WIDE SPOT	-24WS
38° NARROW FLOOD	-38NF
60° FLOOD	-60F
90° WIDE FLOOD	-90WF

Color Temp	
5000K	-50K
4000K	-40K
3000K	-30K

Links (Click on the below items to view):

- **Beam Information (Coverage, Datafile)**(<https://www.larsonelectronics.com/images/product/BeamInfo/104751.PDF>)
- **Dimensional Drawing 2D**(<https://www.larsonelectronics.com/images/product/DimensionalDrawing/104751.PDF>)
- **IES (Photometric File)**(<https://www.larsonelectronics.com/images/product/ies/104751.ZIP>)
- **Lighting Study (Layout) Example 1**(<https://www.larsonelectronics.com/images/product/Layout1/104751.PDF>)
- **Lighting Study (Layout) Example 2**(<https://www.larsonelectronics.com/images/product/Layout2/104751.PDF>)
- **Lighting Study (Layout) Example 3**(<https://www.larsonelectronics.com/images/product/Layout3/104751.PDF>)
- **Operations Manual**(<https://www.larsonelectronics.com/images/product/Manual/104751.PDF>)
- **Photometric Flood Report**(<https://www.larsonelectronics.com/images/product/FloodReport/104751.PDF>)
- **Photometric Indoor Report**(<https://www.larsonelectronics.com/images/product/IndoorReport/104751.PDF>)
- **Photometric Polar Graph**(<https://www.larsonelectronics.com/images/product/PolarGraph/104751.PDF>)
- **SpecSheetSpanish**(<https://www.larsonelectronics.com/images/product/SpecSheetSpanish/104751.PDF>)
- **Spectrum Curve (Wavelength Graph)**(<https://www.larsonelectronics.com/images/product/SpectrumChart/104751.PDF>)
- **STEP File (3D CAD Model)**(<https://www.larsonelectronics.com/images/product/Step/104751.ZIP>)
- **HigResPic1**(<https://www.larsonelectronics.com/images/product/HigResPic1/104751.JPG>)
- **HigResPic2**(<https://www.larsonelectronics.com/images/product/HigResPic2/104751.JPG>)
- **HigResPic3**(<https://www.larsonelectronics.com/images/product/HigResPic3/104751.JPG>)
- **HigResPic4**(<https://www.larsonelectronics.com/images/product/HigResPic4/104751.JPG>)
- **HigResPic5**(<https://www.larsonelectronics.com/images/product/HigResPic5/104751.JPG>)
- **HigResPic6**(<https://www.larsonelectronics.com/images/product/HigResPic6/104751.JPG>)
- **HigResPic7**(<https://www.larsonelectronics.com/images/product/HigResPic7/104751.JPG>)
- **HigResPic8**(<https://www.larsonelectronics.com/images/product/HigResPic8/104751.JPG>)
- **HigResPic9**(<https://www.larsonelectronics.com/images/product/HigResPic9/104751.JPG>)
- **HigResPic10**(<https://www.larsonelectronics.com/images/product/HigResPic10/104751.JPG>)
- **Video1**(<https://www.youtube.com/watch?v=x0AJy8QC7OE>)
- **Video2**(<https://www.youtube.com/watch?v=fJNW13lab4>)
- **ISO 9001 Certification**(<http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF>)
- **Business Certificate**(<https://www.larsonelectronics.com/images/pdfdocs/w9.PDF>)
- **Shipping Time Map**(<https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf>)