Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MMLP-21W-12P

21 Watt Temporary Manhole Mount Explosion Proof LED Fixture - Tank Nozzle Mount Lighting - 12" Drop

Product ID: 104776

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MMLP-21W-12P Manhole Mount Light
Lamp Type: LED
Dimensions: 7.25 " Diameter, 5" Thickness- 21" Man-Way Support Bracket
Total Watts: 21W
Lumens: 1,750
Voltage: Multi- 100-240 VAC, 50/60Hz
Lighting Configuration: Suitable for Paint Spray Booths
Mounting: 21" Manway Entry Support Plate w/ 12" Pipe
Weight: 31lbs
Color Temp: 6000K, 70-CRI.
Wiring: 50 Foot SOOW Cord with an ECP 1523 Explosion Proof Plug

Ratings
T3C Temperature Rating
Class 1 Class 1, Groups C and D 1&2 Groups C and D
Class II, Groups E and F (T3 Temp Rating)
Class III, Groups E, F and G
IP67 (water proof)
LEDs Driven at 90%

Special Orders - Special Requirements
Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics MMLP-21W-12P Temporary Manhole Mount Light Fixture provides operators with a powerful and highly convenient alternative to traditional string or tank lights. LED technology, an innovative 21" man-way support bracket, and compact design, makes this lamp an excellent lighting solution for operators working within storage tanks, railcars, and other locations where entry is through a 21" man-hole opening.

This Class 1 Division 1 & 2, Class 2 Division 1 & 2 explosion proof light fixture provides 1,750 lumens of high quality light while drawing only 21 watts. The copper free aluminum alloy body is powder coated for added durability and an attractive aesthetic appearance. A special heat dissipating design in conjunction with advanced LED technology helps this fixture to achieve an excellent 50,000 hour rated lifespan with 80% lumen retention. This 7.25" diameter LED light is attached to a 21 inch supporting plate which allows the light fixture to hang inside the tank or railcar while the supporting plate rests on the lip of a man-way opening.

The effective and durable manway mount explosion proof LED light from Larson Electronics is approved for use in paint spray booths and is ideal for industrial applications, hazardous work spaces, and areas where gases, vapors and dusts may be present and an effective and durable hazardous location light solution is needed. This lamp can be equipped with seven Edixeon® 3 watt LED emitters to provide a variety of brightness and power options. The lamp housing is waterproof, constructed of heavy cast aluminum, and UL tested to withstand 1490 lbs. per square inch of hydrostatic pressure. Factory sealed and finished in a durable polyester powder coating, this lamp can be ordered with a choice of mounting options and can be configured to operate with 120-240VAC 50/60hz. This fixture is also available in an optional low voltage 9-32 volts DC.

This mounting system provides an extremely versatile lighting option for those working in confined spaces such as rail cars, storage tanks, ship tanks and the like where entry is through a 21" man-way opening. The light is suspended 12" from the lip to lower the light source into the tank.

This light is multi-voltage capable and can be operated with 100-240 VAC, 50/60Hz without any need for a special ballast. The aluminum body and LED lamp give this light excellent durability and resistance to vibration and impacts. The housing is specially designed to dissipate heat which increases the efficiency and lifespan of the LED luminaries. The LED lamp produces 1,750 lumens with a color temperature of 6000K and a color rendering index of 70, which produces colors and details much more accurately than high pressure sodium or mercury vapor luminaries. The MMLP-21W-12P offers excellent convenience and effectiveness with a 21" manhole mounting support bracket that eliminates the need for special mounting fixtures or cumbersome string light systems.

High Quality Features

1. Low power consumption.
2. Instant on/off operation.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy.
4. Superior color rendering compared to HPS, LPS, MV.
5. Retains 80% lumen output after 50,000 operating hours.
6. Powder coated aluminum fixture body.
7. Highly convenient and innovative man-way support bracket provides an excellent alternative to string lights.
8. Low profile - Light weight
9. 1,750 Lumen output from only 21 watts

Superior LED Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LEED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off – No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MMLP-21W-12P

Product ID: 104776

Export Control Classification Number (ECCN): EAR99

Options:

MMLP-21W-12P-Voltage

Example: MMLP-21W-12P-1227

Voltage	
120-240V AC	-1227
12-24V DC	-1224

Links (Click on the below items to view):

- **Wiring Diagram (Oneline)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **Video1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**