Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-48-2L-45D

45 Degree Surface Mount Explosion Proof, Waterproof Fluorescent Lights -Paint Booth, Rigs - 2 Lamp

Product ID: 104873

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-48-2L-45D Explosion Proof
NRTL Listed for United States & Canada

Dimensions: W-11.25" L-52" H-8.5 "

Weight: 65 Lbs

Total Watts: 108 watts*

Voltage: Universal 120V-277V 50/60 Hz

Total Lumens: STD-T5-HO Bulbs 10000

Lamp Life Expectancy: STD-T5-HO Bulbs 20,000 Hours

Efficiency: STD-T5-HO Bulbs83 Lumens per Watt

Ambient Operating Temp Range:-20 C to 70 C*

Beam Angle: N/A

Color Temp: varies with bulb choice

Mounting: Extended Adjustable Surface Mount Bracket

Wiring Hub: 1/2 inch threaded

Operating Temp Rating: T6 Rated

Minimum Operating Temp: -30 C

Maximum Case Temp: 90 C

***Wattage totals are lamps only and may vary with different lamps.

Ratings

Class 1 Division 1, Groups C and D

Class 1 Division 2, Group A,B,C,D

Class II Division 1- 2, Groups E,F,G

NRTL Certified to UL 844, 924

NRTL Certified to UL 1598 Marine Type

NRTL Certified to UL 595 Outdoor Marine Type (Saltwater)

Listed for Paint Spray Booths*

California Title 24 Compliant

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Made in the USA

The Larson Electronics EPL-48-2L-45D Explosion Proof Fluorescent Light Fixture is NRTL Listed for United States and Canada, rated Class 1 Division 1 and Class 1 Division 2 for hazardous locations where flammable chemical/petrochemical vapors exist or have the potential to exist. The unit carries a T6 temperature rating, it is also approved for Paint Spray Booths.

The EPL-48-2L-45D fixture is a 4 foot long, 2 lamp, Class 1 Division 1 and Class 2 Division 1 & 2 explosion proof fluorescent light which is also approved for use in paint spray booth applications. This T6 temperature rated fixture comes standard with two fluorescent lamps. Lamp choices include T5HO, T12HO, and T8. The lamps are protected by heat and impact resistant Pyrex tubes and the fixture is constructed of copper free aluminum alloy. The lamp reflectors are corrosion resistant heavy gauge aluminum and coated with a high gloss reflective finish. This fixture is multi-voltage capable and is available with a variety of lamp options. The EPL-48-2L-45D provides operators in hazardous locations with a reliable and affordable lighting solution that provides the best explosion proof protection available without sacrificing light quality or fixture durability.



SURFACE MOUNT (STANDARD)


Click Image to Enlarge



Click Image to Enlarge




Click Image to Enlarge



PENDANT MOUNT (OPTIONAL)





We offer a choice of bulbs with all of our explosion proof fluorescent fixtures. However, we standardize on the T-5HO bulbs mostly for longevity and high output. However, many of our customers, including Naval bases, shipyards, oil rigs and petrochemical processing plants operate in very cold conditions, and T-12HO bulbs operate well in those environments. Larson Electronics offers a T12VHO lamp option, 110 watt Very High Output lamps make this fixture an ideal replacement for 400 watt metal halide surface mount fixtures in hazardous location areas requiring Class 1 Division 1 rated lights. *However, the 110 watt T12VHO lamp configuration is not appropriate for paint spray booth applications.

	T5HO	T8	LED
Wattage	108 watts	64 watts	48 watts
Amp Draw @ 120V AC	0.9 amps	0.54 amps	0.4 amps
Amp Draw @ 277V AC	0.39 amps	0.24 amps	0.18 amps
Amp Draw @ 12V DC	9 amps	5.34 amps	4 amps
Amp Draw @ 24V DC	4.5 amps	2.67 amps	2 amps
Lamp Life Expectancy	20,000 hours	24,000 hours	50,000 hours
Color Temperature	5000K / 4100K	4100K	5300K
Operation cost per year (8hs/day @ 11c/kWh)	$34.69	$20.56	$15.42

Mounting Options: This fixture ships with extended surface mount brackets for increased angling after installation. For our standard surface mount bracket or our pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit), please see our EPL-48-2L standard explosion proof light fixture. Additional mounting configurations can be customized to meet the requirements on the application. Please contact us for special mounting configurations.

Adjustable Surface Mount Brackets: Each bracket is cinched to the bracket mounting peg on each side of the light. The angle of the bracket is set by tightening two cap screws on either side of the bracket. The cap screws act as a set screw. The bracket itself is mounted via a single bolt hole at the top the bracket. There are two brackets, one on each end of the light. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be removed from the brackets by loosening the cap screws that hold the bracket to the mounting peg.

The included mounting brackets extend the fixture out and away from the mounting surface, allowing operators to pivot the light up to 45° in either direction after installation. This is ideal for paint spray booths in wall mount applications to ensure effective and even lighting on all sides of the objects to be painted.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture, where other models may only offer one or three choices.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy.
4. Over-sized, finned ballast housing for 800 mA fixtures provides more heat dissipation and extends ballast life. Larger ballast box accommodates High Output lamp ballasts. Ballast housing easily accessible and externally mounted. Top and bottom covers secured with nuts and bolts, instead of threaded through holes, which can be damaged with dirt.
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. A wrench is used to unscrew the end caps for relamping the fixture, while other models require the “tap and knock off” method to loosen the end cap.
7. Explosion proof, impact and heat resistant Pyrex tubes provide lamp protection.

Lamp Options

F54-T5/850/HO – 54 watt, 5000 lumens per bulb, 20,000 hours life, 5000 Kelvin color, CRI 85 RHA-UNV-254-LT5 Ballast is THD<10% and HPF .98 (Suffix –50KT5)
F54-T5/841/HO - 54 watt, 5000 lumens per bulb, 20,000 hours life, 4100 Kelvin color, CRI 85 (Suffix -41KT5)
F48-T12/HO – 60 watt, 4050 lumens per bulb, 12,000 hours life, 4100 Kelvin color (Suffix –T12HO)
F32-T8/841 – 32 watt, 2950 lumens per bulb, 24,000 hours life, 4100 Kelvin color (Suffix –T8)
T12HB with magnetic ballast for high heat configurations ("hot box" explosion proof light applications) - 60 watt, 4050 lumens per bulbs - This bulb, ballast and wiring configuration is designed for applications to 165 degrees C.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPL-48-2L-45D

Product ID: 104873

Export Control Classification Number (ECCN): EAR99

Options:

EPL-48-2L-45D-Lamp

Example: EPL-48-2L-45D-50KT5HO

Lamp	
54W 5000K-T5HO	-50KT5HO
32W T8	-T8
60W T12HO	-T12HO
54W 4100K-T5HO	-41KT5HO
T12DL	-T12DL
28W T5	-T5

Links (Click on the below items to view):

- **MSDS (Material Safety Data Sheet**
- **Operations Manual**
- **SpecSheetSpanish**
- **Video1**
- **Video2**
- **Video3**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**