Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 105151

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image:

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

Specifications / Additional Information

LEDT8-24-D 23 watt T-series Dimmable LED Tube

Lamp Type: LED Tube
Dimensions: 48"
Weight: 390 grams
Watts: 11 watts
Total Lumens: 1,375
Lumens Per Watt: 125
Lamp Life Expectancy: 50,000+ Hours
Beam angle: 160 degrees
Color temperature: 3000K, 4500K (clear) or 5600K (light frost)
CRI: 80
Voltage: 90 to 132 VAC
Dimmable: Yes
Power Efficiency: 90%
Power Factor: >0.95
Operating Temp: -25°C to +45°C
Materials: Aluminum Body / Polycarbonate Lens

Ratings/Approvals

Listed for United States and Canada
UL-1993
CAN/CSA C22.2 No 1993
125 lm/w efficiency
IP20 Rated
80% Lumen Retention @ 50,000+ Hours
Internal Driver
Single End Powered
Works with Lutron or Leviton electronic dimmers

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail:sales@larsonelectronics.com

The Larson Electronics LEDT8-24-D 11 watt T-series Dimmable LED tube lamp is an excellent choice for upgrading existing T8 dimming fluorescent lamp fixtures to LEDs as well as a direct replacement for our own LED light fixtures.

This 11 Watt T-series LED Bulb works with any T8 fluorescent light fixtures, can be configured for any T series fluorescent bulb fixture and requires no ballast for operation. Internally, you simply bring the black wire to one pin and the white wire to the other. Power for this dimmable LED tube is single ended, meaning line and neutral voltage are applied to the same end. The polycarbonate lens diffuses the light and makes this bulb ideal for food safe environments as there is no glass. The aluminum housing serves as a heat sink and provides rigidity and strength for this LED bulb.

In fluorescent light fixtures with electronic ballasts, the operator needs to bypass the ballast and wire the power directly to one end of the LED tube (black wire to one pin and white wire to the other). Thus, this is an ideal upgrade for 2 foot fixtures with failed ballasts. These multi-voltage LED bulbs run directly off any voltage ranging from 90 volts to 132 volts AC, including 110 volts, 115 volts, and 120 volts AC.



Click Photo to Enlarge



Click Photo to Enlarge

These are the first generation of our dimmable 11 watt LED tubes. Lumen output is 125 lumens per watt for a total of 1,375 lumens per bulb. This LED lamp features rotating pins, allowing operators to adjust the direction of light dispersion after installation. While fluorescent lamps are omni-directional and illuminate 360°, the LED style replacement lamps are directional and offer a 160° beam spread. While this is more efficient than traditional fluorescent lighting, the pin alignment in retrofits may not always line up. With the rotating pins offering 300° of adjustability, operators can install the LED lamp, then rotate the center of the tube to the desired positioning.

This dimming LED tube uses electronic silicon control dimming. We have tested this lamp on all Lutron and Leviton electronic dimmers, such as the Leviton 6633-PLW. When using electronic dimmer switches, fixtures equipped with the LEDT8-24-D LED bulb will dim from 0% up to 100% via the user provided dimming switch. This lamp will not work on voltage outside of the 90-132V AC range and internal damage may occur when higher voltage is applied to the lamp.

These LED fluorescent tube replacements can be used as upgrades or replacements to our own explosion proof fluorescent lights, explosion proof paint spray booth lights as well as any other T series light fixture the operator already has in house. We have specially designed these for our explosion proof light fixtures, however, they can be used as replacements in standard fluorescent light fixtures. In our facilities, we replaced worn or spent fluorescent bulbs with these LED bulbs by removing the ballasts and bringing the white wire to one end and the black wire to the other end of the LED tube.

LED Lamp Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LEED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off – No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.
15. Brings out natural appearance of products in sales or manufacturing applications.
16. Preserves integrity of retail products... no heat damage to formulations or thermal fade of branded packaging in display cases.
17. Unlimited indoor applications for overhead lighting, retail fixtures, signage, custom lighting accents, manufacturing and general area illumination.
18. Easily retrofit existing conventional light fixtures, simplifies troffers since no ballasts. needed Durable enough for portable use in exhibitions and tradeshows.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image:

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Product ID: 105151

Harmonized System (HS) Code: 9405.41.84.10
Export Control Classification Number (ECCN): EAR99

Options:

-Voltage-Option 2
Example: -120V-3000K

Voltage	
120V	-120V
24V	-24V

Option 2	
3000K	-3000K
4500K	-4500K
5600K	-5600K

Links (Click on the below items to view):

- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**(https://www.larsonelectronics.com//images/product/CECCert/105151.PDF)
- **Operations Manual**(https://www.larsonelectronics.com//images/product/Manual/105151.PDF)
- **USA NEC Certificate (Commonly referred to as UL Certificate)**(https://www.larsonelectronics.com//images/product/NECCert/105151.PDF)
- **HigResPic1**(https://www.larsonelectronics.com//images/product/HigResPic1/105151.JPG)
- **HigResPic2**(https://www.larsonelectronics.com//images/product/HigResPic2/105151.JPG)
- **HigResPic9**(https://www.larsonelectronics.com//images/product/HigResPic9/105151.JPG)
- **Video1**(https://www.youtube.com/watch?v=12Quu_Q_Hml)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)