Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDLB-24E-IR-10HZ-DIMM

72 Watt Dimmable Infrared LED Light Bar - 24 LEDs - 10hz IR Strobe - 900'L x 100'W Beam - Extreme

Product ID: 105282

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

LEDLB-24E-IR-10HZ-DIMM LED Light Bar

LEDs: 24 Edixeon® 3 Watt IR LED Emitters
Dimensions: 8.25"-L 5.27"-H 3.57"-D
Watts: 72
Voltage: 9-42 VDC
Weight: 7.4 Lbs
Beam Configuration: 10° Spot or 35° Flood
Lighting Configuration: 10hz Strobe
Mounting: Stud Bracket
Wiring: Deutsch IPD / LADD DT04-2P connector
Amps: 6 (on 12 volts) 3 (on 24 volts)
LED Light Color: Infrared- 750Nm, 850Nm or 940Nm
LED Life Expectancy: 50,000 hours
Optics Efficiency: 90%
Materials: Aluminum Housing, Polycarbonate Lens
Housing Colors: Black or White
Spot Beam: 900`L x 100`W
Flood Beam: 300`L x 280`W

3 year warranty replacement on this LED light. After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the

LEDLB LED Features

Edixeon® 3 Watt IR LED Emitters
LEDs Driven At 80%
-40 C~ +80C Operating Temp Range
RoHS Compliant
70% Lumen Retention @65,000 hours
LED Chip Op Temp -40C to +110C
IP68 Rated Waterproof to 3 Meters
Dimmable / Tunable
CE Certified

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

customer. When the failed light is returned, we will ship a new replacement.

Buy American Compliant

The Larson Electronics LEDLB-24E-IR-10HZ-DIMM Dimmable Infrared LED Strobe Light offers high infrared strobing light output and extreme durability for demanding operating conditions. This IP68 rated infrared strobe LED light is waterproof to three meters and produces a 10hz infrared strobe light beam uo to 900` long by 100` wide light that can only be seen through the use of night vision goggles. 850Nm versions have a very slight red glow around the LED emitters when veiwed from a certain angle while 940Nm versions are completely invisible to the naked eye. This light can run on any voltage from 9 to 42 volts and provides an extremely rugged infrared lighting solution that is ideal for use in commercial and industrial security applications as well as military environments.


The LEDLB-24E-IR-10HZ-DIMM dimmable infrared strobe LED light bar produces a 10hz strobe light in the infrared 850Nm or 940Nm end of the light spectrum depending upon the version selected. In spot configuration this infrared LED emitter produces a 900` long by 100` wide infrared beam of light with a tight focus and moderate beam spread. In flood configuration this infrared LED light produces a wide spread infrared beam concentrated much closer to fixture. Twenty-four Edison Edixeon® 3 watt infrared emitters are arranged in rows and paired with high purity 10 degree optics to produce a tightly focused spot beam with limited spread or light spillage.

We offer optional floodlight versions of this light that have 35 degree optics to produce a wider beam spread and more light over a larger area nearer the fixture. These LED light bars are IP68 rated and waterproof to 3 meters, sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications. The entire LEDLB series are constructed of extruded aluminum and feature heavier housings, rubber isolated mounts and unbreakable polycarbonate lenses to provide increased durability against vibrations, impacts, waves, hard rains, sand and high winds.

LEDLB-24E-IR-10HZ-DIMM
35° Flood Beam (Opt)



LEDLB-24E-IR-10HZ-DIMM
10° Spot Beam (Stnd)



Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated Edison Edixeon® Emitters. The end result is more light and longer LED life with higher average intensity maintenance after 50,000 hours.

Voltage Control: These units are able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These LEDLB series light bars can operate on current ranging from 9 to 42VDC without any modifications necessary as a result. This multi-voltage capability makes these units ideal for mobile and stand alone applications such as those found on boats, heavy equipment and vehicles where power systems don't always operate with 12 volts and external generators, transformers or inverters are impractical.

Durability: The LEDLB-E series of LED light bars from Larson Electronics offer

IP68 rated construction that is designed to withstand extremes of environmental and operating conditions. The LED lights with the 'E' part number designationare are designed for extreme durability and are larger and heavier than the standard LEDLB series lights and are nearly twice as heavy as their standard counterparts. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three meters and resist ingress of dust, dirt and humidity. The housings are formed from thick extruded aluminum and the lenses are unbreakable polycarbonate. The Edixeon® LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance. We recommend these LED lights for high stress - high vibratory conditions, high humidity climates, very cold areas and rough saltwater conditions. They are also well suited to environments where equipment is used in one temperature extreme and stored in another temperature extreme.

Mounting: LEDLB series light bars are equipped standard with aluminum mounting blocks which slide within the aluminum housing to allow users to adjust their positioning to match existing or user drilled mounting holes. Each aluminum mounting block has an integrated rubber bushing to absorb vibrations and shocks. To secure the lights in place users simply slide the mounting bolts through the aluminum mounting block and rubber isolator, through the mounting surface, then secure the bolt with a locking nut on the opposite side of the mounting surface. This mounting system enables mounting to flat or round surfaces and allows for minimal 7 degrees of flexibility of angle placement of the light. We also offer a BC-2 bar clamp mounting system you can view here for even greater mounting versatility.

Note: Most LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

LEDLB-24E-IR-10HZ-DIMM

Product ID: 105282

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

LEDLB-24E-IR-10HZ-DIMM-Beam Config-Wavelength

Example: LEDLB-24E-IR-10HZ-DIMM-SP-750nm

Beam Config	
SPOT	-SP
FLOOD	-FL

Wavelength	
750NM	-750nm
850NM	-850nm
940NM	-940nm

Links (Click on the below items to view):

- CE Certificate
- Dimensional Drawing 2D
- Eye Safety Information/Certificate
- Military Specification Certificate 1
- MSDS (Material Safety Data Sheet
- RoHS Certificate (Restriction of Hazardous Substances)
- Spectrum Curve (Wavelength Graph)
- STEP File (3D CAD Model)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map