

Class 1 Division 2 Hazardous Location LED Light - NO LAMPS - Corrosion Resistant for Marine Use

HALP-48-2L-LED-NL



1HALP-48-2L-LED-NL Hazardous Area LED Offshore Light

1UL Listing: 1United States - Canada

1Dimensions: 1 W-8.25" x L-52" x H-7"

1Weight: 18 Lbs

1Total Watts: 1N/A

1Total Lumens: 1N/A

1Voltage: 1N/A

1Lamp Life Expectancy: 1N/A

1Luminous Efficiency: 1N/A

1Temp Range: 1 N/A

1Beam Angle: 1 150°

1Color Temp: 1 N/A

141Minimum Operating Temp: 1 -30 C

141Maximum Case Temp: 190 C

1Mounting: 1 Flange Type Surface Mount or Pendant Mount

1Wiring Hub: 1 1/2" or 3/4" threaded

1Warranty: 1 YES 1- 3 Years*

1U.L. Approval: [blank#0000ffU.S Certificate](#) [blank#0000ffCanada Certificate](#)

1U.L. Ratings

1Class I Division 2, Groups A, B, C, D

1Class II, Division 2, Groups F, G

1UL 844

1UL 1598A Marine Type (Salt water)

1California Title 24 Compliant

1T4A Temperature Rated

1Special Orders- Requirements

1Contact us for special requirements

1Toll Free: 1 1-800-369-6671

1Intl: 11-903-498-3363

1E-mail: 1 sales@larsonelectronics.com

Options:

HALP-48-2L-LED-NL-Mount-Hub Config

Example: HALP-48-2L-LED-NL-SFC-SFC

Mount	
SURFACE MOUNT	-SFC
PENDANT MOUNT	-PND

Hub Config	
1/2IN	-SFC
3/4IN	-PND

Links (Click on the below items to view):

- [Addpic1large](#)
- [Addpic2large](#)
- [Addpic3large](#)
- [Addpic4large](#)
- [DimensionalDrawing](#)
- [large](#)
- [Manual](#)
- [medium](#)
- [SpecSheet](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)