

EPL-48-216-EYM-10C-EPP

Low Profile Surface Mount Explosion Proof Fluorescent Light - 20,000 Lumens - 10' Cord w/ EXP Plug

Product ID: 105418

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPL-48-216-EYM-10C-EPP Explosion Proof Fluorescent Light Fixture

NRTL Listed for United States - Canada

Dimensions: W-11.25" x L-52" x H-8.5 "

Weight: 70 Lbs

Voltage: Universal 120-277VAC 50/60 Hz

Total Watts: 216W

Total Lumens: 20,000

Lamp Life Expectancy (Hrs): 20,000 (T5HO)

Luminous Efficiency (Lm/W): 95.59 (T5HO)

Color Temp: 5000K or 41000K

Beam Angle: 150°

Ambient Operating Temp Range: -20°C to +70°C

Operating Temp Rating: T6 Rated

Minimum Operating Temp: -30°C

Maximum Case Temp: +90°C

Housing Material: Cast Aluminum End Caps, Aluminum Reflectors - Copper Free

Lens Material: Hardened Borosilicate Glass Tubes

Gasket Material: Buna Rubber O-Rings

Mounting: Surface Standard - Pendant Optional

Wiring: 10` 16/3 SOOW w/ EYM Seal Off & Cord Cap

Cord Cap: 5-15, 5-20, or 6-20 - C1D1 Rated

Ratings/Approvals

Class I Division 1, Groups C and D T6

Class I Division 2, Group A,B,C,D

Class II, Division 1 & 2, Groups E,F,G

NRTL Certified to UL 595 Marine Type (Saltwater)

NRTL Certified to UL 844

NRTL Certified to UL 1598 Marine Type

Certified Canadian Standards

Listed for Paint Spray Booths

ABS Certified

California Title 24 Compliant

IP67 Rated - Waterproof

T6 Temperature Rating

NEMA 4X

Approved for Confined Spaces

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

The Larson Electronics EPL-48-216-EYM-10C-EPP Explosion Proof Fluorescent Light Fixture is NRTL Listed for United States and Canada and rated Class 1 Division 1 and Class 1 Division 2 for hazardous locations where flammable chemical/petrochemical vapors exist or have the potential to exist. The unit carries a T6 temperature rating, it is also approved for Paint Spray Booths. This unit is equipped with 10` of SOOW cable and terminated in an explosion proof plug for easy connection to electrical sources within the hazardous environments.

The EPL-48-216-EYM-10C-EPP fixture is a 4 foot long, 4 lamp, Class 1 Division 1 and Class 2 Division 1&2 explosion proof fluorescent light which is also approved for use in paint spray booth applications. This T6 temperature rated fixture comes standard with four T5 high output fluorescent lamps. The lamps are protected by heat and impact resistant Pyrex tubes and the fixture is constructed of copper free aluminum alloy. The lamp reflectors are corrosion resistant heavy gauge aluminum and coated with a high gloss reflective finish. This fixture is multi-voltage capable and is available with a variety of lamp options. The EPL-48-216-EYM-10C-EPP provides operators in hazardous locations with a reliable and affordable lighting solution that provides the best explosion proof protection available without sacrificing light quality or fixture durability.

[This light is also available with LED bulbs instead of fluorescent bulbs. Click here to view.](#)

[Click Photo to Enlarge](#)

[Click Photo to Enlarge](#)

[Click Photo to Enlarge](#)

Mounting Options: Unless otherwise specified, our standard, most popular configuration is the bracket end mounting shown enlarged below. We also offer a pendant mount for those needing to suspend the fixture away from the ceiling surface (i.e. suspend from pipe or conduit). Additional mounting configurations can be customized to meet the requirements on the application. Please contact us for special mounting configurations.



SURFACE MOUNT (STANDARD)



PENDANT MOUNT (OPTIONAL)

[Click Photo to Enlarge](#)

[Click Photo to Enlarge](#)

Adjustable Surface Mount Brackets: Each bracket is cinched to the bracket mounting peg on each side of the light. The angle of the bracket is set by tightening two cap screws on either side of the bracket. The cap screws act as a set screw. The bracket itself is mounted via a single bolt hole at the top the bracket. There are two brackets, one on each end of the light. Once the brackets are mounted to a surface (ceiling, floor or wall), the light fixture can be removed from the brackets by loosening the cap screws that hold the bracket to the mounting peg.

Suspension Mounting: Pendant mount fixtures hang from the ceiling and are suspended by rigid pipe. Each fixture features a 1/2" NPT junction box on one end, and a 1/2" NPT adjustable L-bracket on the other end of the fixture. Operators bring rigid pipe down to the threaded mounting hubs. Wiring is fed down through the rigid pipe to the junction box and tied in to the fixture's lead wires, completing the electrical connection. The adjustable L-shape mounting bracket provides support for the opposite end of the fixture.

[Click Photos to Enlarge](#)



5-15 Straight Blade Plug



5-20 Straight Blade Plug



6-20 Straight Blade Plug

Wiring & Plug: The EPL-48-216-EYM-10C-EPP explosion proof light fixture is NRTL Listed for United States and Canada for use in paint spray booths. This fixture is equipped with a seal off and 10` of 16/3 chemical and abrasion resistant SOOW cable terminated in an explosion proof cord cap. Plug options include explosion proof 5-15 15 amp straight blade plug, explosion proof 5-20 20 amp straight blade plug, or explosion proof 6-20 20 amp straight blade plug. Alternatively, we can provide flying leads with no plug for hard wire applications or for operators who prefer to wire in user provided cord caps. Please choose pigtail option below for flying leads with no plug.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture, where other models may only offer one or three choices.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy.
4. Over-sized, finned ballast housing for 800 mA fixtures provides more heat dissipation and extends ballast life. Larger ballast box accommodates High Output lamp ballasts. Ballast housing easily accessible and externally mounted. Top and bottom covers secured with nuts and bolts, instead of threaded through holes, which can be damaged with dirt.
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. A wrench is used to unscrew the end caps for relamping the fixture, while other models require the "tap and knock off" method to loosen the end cap.
7. Explosion proof, impact and heat resistant Pyrex tubes provide lamp protection.

Lamp Options

F54-T5/850/HO – 54 watt, 5000 lumens per bulb, 20,000 hours life, 5000 Kelvin color, CRI 85 RHA-UNV-254-LT5
Ballast is THD<10% and HPF .98 (Suffix –50KT5)
F54-T5/841/HO - 50 watt, 4450 lumens per bulb, 20,000 hour life, 4100 Kelvin color, CRI 85 (Suffix -41KT5)



Frequently Asked Questions (FAQ)









EPL-48-216-EYM-10C-EPP

Product ID: 105418

Export Control Classification Number (ECCN): EAR99

Options:

EPL-48-216-EYM-10C-EPP-Cord Cap-Lamp-Mount

Example: EPL-48-216-EYM-10C-EPP1523-50KT5HO-SFC

Cord Cap	
5-15	1523
5-20	2023-125V
6-20	2023-250V
PIGTAIL	-Pigtail

Lamp	
54W-5000K T5HO	-50KT5HO
54W-4100K T5HO	-41KT5HO

Mount	
SURFACE	-SFC
PENDANT	-PND

Links (Click on the below items to view):

- [MSDS \(Material Safety Data Sheet\)](#)
- [SpecSheetSpanish](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [Video1](#)
- [Video2](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)