Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

GAU-36-25W-LED-1227

25 Watt General Area Use LED Light Fixture - 36" Light Bar - 120-277V AC

Product ID: 105844

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

GAU-36-25W-LED-1227 LED Bar

Lamp Type: LED

Dimensions: Lamp 35.88"-L 2.68" -W 1.69"- D

Weight: 2.1lb | 0.9 k g
Watts: 25.2 W
Voltage: 120-240V AC

Lumens: 1812

Lamp Life Expectancy: 100,000 Hours
CRI: 75

Amps: 1.3 A @12 VDC | 0.66 A @ 24 VDC

Light Color: 6500K
Beam Type: 100° Flood
Mounting: Standard Triangle End Brackets
Temp Range: -40°C – +85°C
Wiring: 5Ft Lead | White: + Black: -

GAU-36-25W-LED-1227 Ratings

IP54 Ingress Protection

T3 Temperature Rating

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Buy American Compliant

The Larson Electronics GAU-36-25W-LED-1227 is a low profile lighting solution approved for use in wet locations. This powerful 36" long LED strip light produces 1812 lumens, operates from 120V through 240V AC, and is suitable for a variety of applications.

The GAU-36-25W-LED-1227 is designed to provide a high output and ruggedly durable lighting solution. This low profile strip light can be operatedon 120

through 240V AC current and includes 6 feet of connecting lead with standard two wire configuration. This light is constructed of powder coated extruded aluminum for excellent strength and durability and is rated IP54 for protection against exposure to splashing water and limited dust ingress. These units are configured in a 36" long strip or "bar" profile for installation in locations where wide dispersal and a low profile is preferred. The high output, cool running operation, and good color rendering properties of this light make it an ideal replacement for older, bulkier, and less reliable HID and halogen light fixtures.

Durability/Mounting: The GAU-36-25W-LED-1227 LED light is constructed of extruded aluminum with a tough powder coat finish for high strength and durability. The housing is IP54 rated, providing limited ingress protection against dusts, and basic protection against splashing water such as rain. This design is weather resistant, suitable for indoor or outdoor applications, and ideal for areas where wetness or dusty conditions are commonly encountered.
The LEDs in this unit are Cree X-Lamp XR-E units that have been chosen for their high lumen per watt ratio and extreme long life. These Cree LEDs provide over 90 lumens per watt output and have a 70% lumen retention at 50,000 hours, giving them better efficiency and operational life than comparable LEDs.
Mounting for this unit is provided by two standard adjustable end brackets that allow operators to mount the light to flat surfaces and then adjust the light 170° vertically for the best placement. The entire assembly weighs 2.1 lbs and measures 35.88 inches in length and 2.68 inches wide and 1.69" deep, making it ideal for mounting in areas where space is limited and a low profile fixture is more readily installed.
Wiring/Power: These hazardous area LED lights are equipped with 5 feet of cord containing a standard three wire connecting configuration. These lights operate from 120 to 240 volt AC current.
Versatility: This unit carries an IP54 water resistant rating ensuring protection against limited ingress from dusts, dirt, and basic protection against light water spray landing directly on the fixture. This light is ideal for indoor or outdoor applications and industrial operations with hazardous location classification where dusty or wet conditions are commonly encountered.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

GAU-36-25W-LED-1227

Product ID: 105844

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

GAU-36-25W-LED-1227-Beam Config-Cord Cap

Example: GAU-36-25W-LED-1227-SP-5.15

Beam Config	
SPOT	-SP
FLOOD	-FL

Cord Cap	
5-15 STRAIGHT	-5.15
6-15 STRAIGHT	-6.15
L5-15 TWIST	-L5.15
L6-15 TWIST	-L6.15
UK BS1363	-BS1363
INTL SCHUKO	-SCHUKO
PIGTAIL	-PIGTAIL

Links (Click on the below items to view):

- **Dimensional Drawing 2D**
- **STEP File (3D CAD Model)**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**