Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-13-8W-LED-STRB-2HZ

10 Watt Strobing LED Light Fixtures for Hazardous Location Illumination - 2Hz Flash Rate - C1D2

Product ID: 105865

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-13-8W-LED-STRB-2HZ Hazardous Location LED Lighting

Lamp Type: LED

Dimensions: Lamp 13.38"-L x 2.68"-W x 1.69"-D

Weight: 0.7 lb | 0.3 kg

Watts: 10

Voltage: 12 V DC (11-16 V DC) - 24 V DC (22-28 V DC)

Lumens: 1300

Luminous Efficacy: 130 Lm/W

Lamp Life Expectancy: 100,000 Hours

CRI: 75

Frequency: 2 HZ

Amps: 0.83 A @ 12 V DC | 0.41 A @ 24 V DC

Light Color: 6500K

Beam Type: 100° Flood or 30° Spot

Mounting: 1/4" - 20 Screws /Aluminum 1" Yoke

Temp Range: -40°C – +85°C

Wiring: 6' Lead | White: + Black: -

Cord Cap: 5-15 15A Straight Blade Plug - Explosion Proof

ETL Listed

Class I Division 2 Groups A,B,C,D

NRTL Certified to CSA 22.2 No. 250.0

NRTL Certified to UL 1598

IP54 Ingress Protection

T3 Temperature Rating

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

The HAL-13-8W-LED-STRB-2HZ from Larson Electronics is a Low Voltage Hazardous Location LED Strobe Light that is approved for Class I Division

2 environments and U.L. 1598 compliant for use in wet locations. This powerful LED strip light produces 1,300 lumens while drawing only 10 watts, operates from 12 or 24 V DC, flashes at a frequency of 2HZ, and is suitable for a variety of applications.

The HAL-13-8W-LED-STRB-2HZ is designed to provide a high strobing output and ruggedly durable lighting solution for applications where Class I Division 2 compliance is required. This low voltage hazardous area light can be operated with either 12 or 24 volt DC (choose below) current and includes 6 feet of connecting lead with standard two wire configuration. This light is constructed of powder coated extruded aluminum for excellent strength and durability and is rated IP54 for protection against exposure to water spray and limited dust ingress. These units are configured in a 13" long strip or "bar" profile for installation in locations where wide dispersal and a low profile is preferred. The high output, cool running operation, and good color rendering properties of this light make it an ideal replacement for older, bulkier, and less reliable incandescent and halogen light fixtures.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Durability/Mounting: The HAL-13-8W-LED-STRB-2HZ hazardous location LED light is constructed of extruded aluminum with a tough powder coat finish for high strength and durability. The housing is IP54 rated, providing limited ingress protection against dusts, and protection against light water spray such as rain. This design is weather resistant, suitable for indoor or outdoor applications, and ideal for areas where wetness or dusty conditions are commonly encountered.

The LEDs in this unit are Cree X-Lamp XR-E units that have been chosen for their high lumen per watt ratio and extreme long life. These Cree LEDs provide over 130 lumens per watt output and have a 70% lumen retention at 50,000 hours, giving them better efficiency and operational life than comparable LEDs. These fixtures are offered with a clear or frosted lens. The frosted lens helps diffuse the light, providing a more even spread. The clear lens will provide no diffusion.

Mounting for this unit is provided by two standard adjustable end brackets that allow operators to mount the light to flat surfaces and then adjust the light vertically for the best placement. The entire assembly weighs 0.7 lb and measures 13.4 inches in length and 2.68 inches wide and 1.69" deep, making it ideal for mounting in areas where space is limited and a low profile fixture more readily installed.

Wiring/Power: These hazardous location LED lights are equipped with 6 feet of cord containing a standard two wire (White+ Black-) connecting configuration and terminated in an explosion proof 5-15 15A straight blade plug. These lights are not multi-voltage; each light is preconfigured for 12 or 24 volt DC current at 10 watts .83 amps on 12 V DC and .41 amps on 24 V DC.

Versatility: The HAL-13-8W-LED-STRB-2HZ is ETL approved for Class I Division 2 groups A, B, C and D locations. This unit carries an IP56 waterproof rating ensuring protection against limited ingress from dusts, dirt, oils, and full protection against water sprayed at high pressure directly on the fixture. This light

is ideal for indoor or outdoor applications and industrial operations with hazardous location classification where dusty or wet conditions are commonly encountered. At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364







Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-13-8W-LED-STRB-2HZ

Product ID: 105865

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

HAL-13-8W-LED-STRB-2HZ-Diffusion-Finish

Example: HAL-13-8W-LED-STRB-2HZ-CW-N-BLK

Diffusion	
COOL W-SPOT	-CW-N
COOL W-FLOOD	-CW-W
COOL W-SPOT FROST	-CW-NF
COOL W-FLOOD FROST	-CW-WF
NEUTRAL W-SPOT	-NW-N
NEUTRAL W-FLOOD	-NW-W
NEUTRAL W-SPOT FROST	-NW-NF
NEUTRAL W-FLOOD FROST	-NW-WF
WARM W-SPOT	-WW-N
WARM W-FLOOD	-WW-W
WARM W-SPOT FROST	-WW-NF
WARM W-FLOOD FROST	-WW-WF
CUSTOM-SPOT	-CUS-N
CUSTOM-FLOOD	-CUS-W
CUSTOM-SPOT FROST	-CUS-NF
CUSTOM-FLOOD FROST	-CUS-WF

Finish	
BLACK	-BLK
WHITE	-WHT

Links (Click on the below items to view):

- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**
- **Dimensional Drawing 2D**
- **MSDS (Material Safety Data Sheet**
- **USA NEC Certificate (Commonly referred to as UL Certificate)**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**