Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-31L-LV-100DP

31 Watt Low Voltage LED Fixture for Hazardous Location Lighting - C1D2 Approved - 100' Cable

Product ID: 105963

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HAL-31L-LV-100DP Hazardous Location LED Light

Lamp Type: LED
Lamp Dimensions (w/o Bracket): 6.9" Diam"- 2.9"-Depth
Lamp Dimensions (w/ Bracket): 4.63"-H 7.25" W"

Weight: 4.5lb | 2.05 k g
Watts: 31.6 W @ 12 VDC | 33.6 W @ 24 VDC
Voltage: 12-28V DC
Lumens: Spot: 2334 - Flood: 1996

Lamp Life Expectancy: 100,000 Hours
CRI: CW: 75, NW: 75, WW: 80
Amps: 2.64 A @12 VDC - 1.4 A @ 24 VDC
Light Color: CW: 6500K, NW: 4300K, WW: 3500K
Beam Type: 30° Spot or 100° Flood
Mounting: 1/4" - 20 Screws /Aluminum 1" Yoke
Materials: Machined aluminum housing - acrylic lens
Housing Finish: Clear anodized finish
Temp Range: -40°C – +85°C
Typical Case Temperature: ~20°C above ambient temperature
Wiring: 100Ft cable w/ Turck Connector & DT04-2P Deutsch Connector
3 year warranty replacement on this LED light. After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, we will ship a new replacement.

ETL Listed

Class 1 Division 2 Groups A,B,C,D
CSA 22.2 No. 250.0
UL 1598

IP66 Ingress Protection

T3 Temperature Rating
LM-80 > 60,500 hrs

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
E-mail: sales@larsonelectronics.com

Buy American Compliant


The HAL-31L-LV-100DP is a low voltage hazardous location lighting solution approved for Class 1 Division 2 environments and UL 1598 compliant for use in wet locations. This powerful LED light produces 2334 lumens, operates from 12 or 24 VDC, and is available in a variety of configurations to allow tailoring to the specific requirements of various applications.

The HAL-31L-LV-100DP is designed to provide a high output and ruggedly durable lighting solution for applications where Class 1 Division 2 compliance is required. This low voltage explosion proof light can be operated with either 12 or 24 volt DC current and includes 100 feet of connecting lead with standard two wire configuration and terminated in a 2-pin Deutsch connector. This light is constructed of precision machined aluminum for excellent strength and durability, clear anodized for corrosion resistance, and is IP66 rated for ingress protection against dust and direct exposure to high pressure water spray.

The HAL-31L-LV-100DP is also available in a 30 degree spotlight beam configuration for distance and a 100 degree configuration for wide area illumination. The light output is offered in 6500K cool white, 4300K neutral white, and 3500K warm white color temperatures for maximum illumination. The high output, cool running operation, and good color rendering properties of this light make it an ideal replacement for older, bulkier, and less reliable metal halide and high pressure sodium lamps.



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge

Durability: The HAL-31L-LV-100DP hazardous location LED light is constructed of machined aluminum for high strength and durability with a clear anodized finish for increased corrosion resistance. The housing is IP66 rated, providing protection against intrusion into the housing from dusts, dirt, oils and water directly sprayed on the housing at high pressure. This LED light is equipped with an impact resistant acrylic lens for increased safety compared to glass lenses. This design is weather resistant, suitable for indoor or outdoor applications, and ideal for areas where wetness or dusty conditions are commonly encountered.

High Output LEDs: The LEDs in this unit are Cree X-Lamp XR-E units that have been chosen for their high lumen per watt ratio and extreme long life. These Cree LEDs provide over 90 lumens per watt output and have a 70% lumen retention at 100,000 hours, giving them better efficiency and operational life than comparable LEDs. These lights are available in a 30 degree spotlight configuration for long beam length or 100 degree flood configuration for wide area coverage. The HAL-31L-LV-100DP has multiple color temperature options and is offered in 6500K cool white with a color rendering of 75, 4300K neutral white with a color rendering of

75, and 3500K warm white with a color rendering of 80.
Mounting: Mounting for this unit is provided by an included aluminum yoke that allows vertical adjustment of the light once installed. The mounting yoke is 1 inch wide and pre-drilled with two ¼ inch holes spaced 2 inches apart for easy and secure mounting to flat surfaces. The entire assembly weighs 4.5 lbs and measures only 6.9 inches in diameter and 3 inches deep, making it ideal for mounting in areas where space is limited and a heavy fixture cannot be installed due to lack of support.
Wiring/Power: These hazardous location LED lights are equipped with 100 feet of cord containing a standard two wire (White+ Black-) connecting configuration and terminated in a DT04-2P female Deutsch connector. These lights operate from 12 to 24 volt DC current and draw 31 watts 2.64 amps on 12 VDC and 33 Watts 1.4 amps on 24 VDC.
Versatility: The HAL-31L-LV-100DP is ETL listed for Class 1 Division 2 groups A,B,C and D locations, certified to CSA 22.2 No. 250.0, and conforms to UL 1598. This unit carries an IP66 waterproof rating ensuring protection against ingress from dusts, dirt, oils and water sprayed at high pressure directly on the fixture. This light is ideal for indoor or outdoor applications, food processing, and industrial operations with hazardous location classification where dusty or wet conditions are commonly encountered.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

HAL-31L-LV-100DP

Product ID: 105963

Export Control Classification Number (ECCN): EAR99

Options:

HAL-31L-LV-100DP-Beam Config

Example: HAL-31L-LV-100DP-SP

Beam Config	
SPOT	-SP
FLOOD	-FL

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Links (Click on the below items to view):

- **Canadian CEC Certificate (Commonly referred to as CSA Certificate)**
- **MSDS (Material Safety Data Sheet**
- **USA NEC Certificate (Commonly referred to as UL Certificate)**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**