Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

HALSS-48-2L-BL-UV

4ft Stainless Steel Ultraviolet Fluorescent Fixture - Hazardous Location Lighting - Glass Lens

Product ID: 106068

Please see last page for supporting documentation for this product (certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Image: HALSS-48-2L-BL-UV

Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

HALSS-48-2L-BL-UV Hazardous Location Lighting

ETL Listing: United States
Dimensions: W-9 1/2" L-54 " H-6 3/4"
Weight: 35 Lbs
Total Watts: 80W*
Voltage: Universal 120-277V AC 50/60 H
Total Intensity: 16.2 W
Lamp Life Expectancy: 5,000 Hours
Radiant Efficiency: 202.5 mW/w
Light Color: Ultraviolet - UVA, UVB, or UVC
Wavelengths: 400-315Nm (UVA), 315-280Nm (UVB), or 280-100Nm (UVC)
Beam Angle: 150°
Ambient Operating Temp Range:-30° C to +70°C
Operating Temp Rating: T4C Rated
Minimum Operating Temp: -30°C
Maximum Case Temp: +90°C
Housing Material: 304 Stainless Steel
Lens Material: Hardened Glass
Mounting: Surface Standard - Pendant Optional
Wiring Hub:1/2" NPT
*Wattage totals are lamps only and may vary with different lamps.

ETL Ratings

Class 1 Division 2, Groups A, B, C, D
UL 595 outdoor marine
UL 1598A Marine Type (Salt water)
Meets US Coast Guard specifications.

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187
Fax: 1-903-765-7664
E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Made in the USA

The Larson Electronics HALSS-48-2L-BL-UV Hazardous Area Fluorescent Ultraviolet Light Fixture is approved Class 1 Division 2 Groups A, B, C and D, UL 1598/A listed and is specifically designed to withstand high vibration locations and the rigors of wet and corrosive marine environments.

The HALSS-48-2L-BL-UV hazardous area ultraviolet fluorescent light fixture is designed for use in wet areas and saltwater-marine environments where corrosion resistance is critical to equipment longevity and safety. This Class 1 Division 2 rated fixture is constructed of non-corrosive materials including a stainless steel housing, a poured in gasket for reliable sealing and a glass diffuser. Corrosion resistant stainless steel latches secure the lamp cover to the housing and provide a firm lock against the poured in seal to prevent drips and water intrusion.

This fixture is 844 rated and Class 1 Division II, Groups A, B, C, D approved. The HALSS-48-2L-BL-UV also carries 1598A and 595 outdoor marine ratings and meets US Coast Guard specifications.



Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge







9 1/2"
(241mm)

This fixture is designed for heavy duty use in applications where intense vibration and corrosive environments may be encountered. Stainless steel construction, high impact acrylic lamp covers, and a Class 1 Division 2 ETL rating make this light ideal for hazardous locations that require illumination with above average dependability.

NOTE ON LAMPS: This fixture comes equipped with ultraviolet lamps that produce radiation in the UV-A, UV-B, or UV-C wavelegth ranges.

Ultraviolet Wavelength Options:
Ultraviolet A Wavelength produces a longer wave between the 400nm - 315nm spectrum.
Ultraviolet B Wavelength produces a shorter wave than the UVA wavelength. These medium sized waves range from 315nm - 280nm.
Ultraviolet C wavelength is reduced exceptionally. Some refer to this wave as the `germicidal` wave. The Ultraviolet C Wavelength ranges from 280nm - 100nm.

Standard Flange Brackets: Stainless steel bracket mounts attached at each end of the

fixture enables it to be simply secured to any surface. The mounts provide flexibility in setting the angle of the fixture. Three through holes provide sufficient mounting for any environment.

Suggested Applications: The HALSS-48-2L is designed for marine wet and damp locations, where corrosion resistant fluorescent lights are required. This lamp is also ideal for locations where heavy vibratory conditions are present. This includes petrochemical facilities, lubrication pits, oil drilling rigs, crew quarters, solvent/cleaning areas, water treatment areas, processing plants and marine loading docks.

Made in USA Quality

1. Each unit dialectically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Flange type stainless steel mounts attached at each end of the fixture enables it to be simply secured to any surface.
3. Fixture housing constructed of 14 gauge stainless steel..
4. Relamping done via stainless steel snap locking latches which allow the operator to remove the door and access the lamps.
5. Lamp cover-diffuser constructed of glass.
6. 1/2 inch, threaded access hole for wiring conduit.

Lamp Options

Lamp options for UV fixtures are determined by UV range.

Operators can specify when ordering- UVA (-A suffix), and UVB,(-B suffix) UVC (-C suffix).

T8 bulbs designed for UV applications are used.

The bulb and ballast in our UV fluorescent fixtures are unique to UV applications.

UVA(-A) 400nm - 315nm
UVB (-B) 315nm - 280nm
UVC (-C) 280nm - 100nm

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664

Frequently Asked Questions (FAQ)

There are no Faqs



Image: HALSS-48-2L-BL-UV

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: HALSS-48-2L-BL-UV

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.765.7664



Image: HALSS-48-2L-BL-UV



Image: HALSS-48-2L-BL-UV

HALSS-48-2L-BL-UV

Product ID: 106068

Warranty: 60 Months.

Export Control Classification Number (ECCN): EAR99

Options:

HALSS-48-2L-BL-UV-Wavelengths
Example: HALSS-48-2L-BL-UV-UVA

Wavelengths	
UVA	-UVA
UVB	-UVB
UVC	-UVC

Links (Click on the below items to view):

- **Dimensional Drawing 2D**(https://www.larsonelectronics.com/images/product/DimensionalDrawing/106068.PDF)
- **MSDS (Material Safety Data Sheet**(https://www.larsonelectronics.com/images/product/Msds/106068.PDF)
- **SpecSheetSpanish**(https://www.larsonelectronics.com/images/product/SpecSheetSpanish/106068.PDF)
- **HigResPic1**(https://www.larsonelectronics.com/images/product/HigResPic1/106068.JPG)
- **HigResPic2**(https://www.larsonelectronics.com/images/product/HigResPic2/106068.JPG)
- **HigResPic3**(https://www.larsonelectronics.com/images/product/HigResPic3/106068.JPG)
- **HigResPic4**(https://www.larsonelectronics.com/images/product/HigResPic4/106068.JPG)
- **HigResPic5**(https://www.larsonelectronics.com/images/product/HigResPic5/106068.JPG)
- **HigResPic6**(https://www.larsonelectronics.com/images/product/HigResPic6/106068.JPG)
- **HigResPic7**(https://www.larsonelectronics.com/images/product/HigResPic7/106068.JPG)
- **HigResPic8**(https://www.larsonelectronics.com/images/product/HigResPic8/106068.JPG)
- **HigResPic9**(https://www.larsonelectronics.com/images/product/HigResPic9/106068.JPG)
- **HigResPic10**(https://www.larsonelectronics.com/images/product/HigResPic10/106068.JPG)
- **Video1**(https://www.youtube.com/watch?v=12Quu_Q_Hml)
- **Video4**(https://www.youtube.com/watch?v=kqVBPI9B704)
- **ISO 9001 Certification**(http://larsonelectronics.com/images/pdfdocs/ISO9001.PDF)
- **Business Certificate**(https://www.larsonelectronics.com/images/pdfdocs/w9.PDF)
- **Shipping Time Map**(https://www.larsonelectronics.com/images/product/ShippingTimeMap/ShippingTimeMap.pdf)