

Infrared LED Light Bar - 20 IR LEDs - 12 Watts 1550NM - Extreme Environment - 800'L X 80'W Spot Beam

Part #: LEDLB-20E-IR-1550NM

**Buy American Compliant**


The Larson Electronics LEDLB-20E-IR-1550NM LED Light Bar offers high infrared light output and extreme durability while drawing only 12 watts of power @1 amp from a 12 volt electrical system. This IP68 rated infrared LED light bar is waterproof to three feet and produces an infrared light beam with a peak in the 1550NM range that can only be seen with night vision equipment. This light can run on any voltage from 9 to 42 volts and provides an extremely rugged infrared lighting solution that is ideal for use in commercial and industrial security applications as well as military environments.

[Click here to see the LED version of this](#)

The LEDLB-20E-IR-1550NM infrared LED light bar from Larson Electronics produces light in the infrared 1550NM end of the light spectrum. Twenty 0.6 watt infrared emitters producing 32mW each are arranged in rows and paired with high purity 10 degree optics to produce a tightly focused spot beam 800' long by 80' wide. We offer optional floodlight versions of this light that have 35 degree optics to produce a wider beam spread and more light over a larger area nearer the fixture. These LED light bars are IP68 rated and waterproof to 3 feet, sealed against intrusion by dust and dirt and very ruggedly constructed to withstand the most demanding environments, conditions and applications. The entire Larson Electronics LEDLB-E series are constructed of extruded aluminum and feature heavier housings, rubber isolated mounts and unbreakable polycarbonate lenses to provide increased durability against vibrations, impacts, waves, hard rains, sand and high winds.

**LEDLB-20E-IR-1550NM 35° Flood Beam
(Opt)**

**LEDLB-20E-IR-1550NM 10° Spot Beam
(Stnd)**



Heat Management: Heat is the single largest factor in premature LED failure and color shifting. As a result, many manufacturers reduce the output of their LEDs to reduce the amount of heat produced. These LED light bars utilize an extruded aluminum housing that incorporates an advanced heat radiating fin design which dissipates heat efficiently to produce the maximum amount of power and longevity from the integrated LED Emitters. The end result is more light and longer LED life with higher average lumen maintenance after 50,000 hours.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Voltage Control: These units are able to monitor and adjust input current to maintain the correct LED voltage levels regardless of input levels across a specific range. These LEDLB series light bars can operate on current ranging from 9 to 42VDC without any modifications necessary as a result. This multi-voltage capability makes these units ideal for mobile and stand alone applications such as those found on boats, heavy equipment and vehicles where power systems don't always operate with 12 volts and external generators, transformers or inverters are impractical.

Durability: The LEDLB-E series of LED light bars from Larson Electronics offer IP68 rated construction that is designed to withstand extremes of environmental and operating conditions. The LED lights with the 'E' part number designation are designed for extreme durability and are larger and nearly twice as heavy as their standard counterparts. These units can withstand rapid temperature changes of -40 degrees Celsius to 85 degrees Celsius, are waterproof to three feet and resist ingress of dust, dirt and humidity. The housings are formed from thick extruded aluminum and the lenses are unbreakable polycarbonate. The LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance. We recommend these LED lights for high stress - high vibratory conditions, high humidity climates, very cold areas and rough saltwater conditions. They are also well suited to environments where equipment is used in one temperature extreme and stored in another temperature extreme.

[Click here to view an article on the Generations of Night Vision and Infrared.](#)

Note: Most Larson Electronics LEDLB, LEDP3W, LEDP10W, and LED10W series LED spotlights and floodlights are terminated with a Deutsch IPD / LADD DT04-2P connector. The mating connector plug is DT06-2S. Most LEDLB and LED10W series lights ship with mating connector as part of a harness or pigtail, depending on the model. Some larger LED lights like the LEDLB-160X2 or LEDLB-200X2 or multiple function LED lights (i.e. high/low beam, modulating, IR/Visible combos) will have different Deutsch connectors.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Specifications / Additional Information**LEDLB-20E-IR-1550NM LED Light Bar****LEDs:** 20 0.6 Watt 1550NM IR LED Emitters**Dimensions:** 12"L x 3"H x 3.57"D**Watts:** 12**Voltage:** 9-42V DC**Spot Beam:** 800`L x 80`W**Flood Beam:** 250`L x 250`W**Weight:** 6.4 Lbs**Lighting Configuration:** 10° Spot or 35° Flood**Amp Draw:** 1 amp @ 12V DC / 0.5 amps @ 24V DC**Mounting:** Stud**Wiring:** Deutsch IPD / LADD DT04-2P connector**Total Intensity:** 640 mW**Wavelength:** 1550NM**LED Life Expectancy:** 50,000 hours**Optics Efficiency:** 90%**Materials:** Aluminum Housing, Polycarbonate Lens**Housing Colors:** Black or White

3 year warranty replacement on this LED light. After 30 days, the customer ships the failed LED light and/or LED bulb to Larson Electronics at their expense. If the failure is a manufacturer defect, we will ship a new replacement to the customer. If failure occurs within 30 days of receipt, Larson Electronics will provide a return label via email to the customer. When the failed light is returned, Larson Electronics will ship a new replacement.

[Scroll Down to Purchase-](#)

[This product does not qualify for free shipping.](#)

[Part #: LEDLB-20E-IR-1550NM \(106155\)](#)

LEDLB LED Features

0.6 Watt IR LED Emitters

LEDs Driven At 80%

-40°C - +80°C Operating Temp Range

RoHS Compliant

70% Lumen Retention @65,000 hours

LED Chip Op Temp -40°C to +110°C

IP68 Rated Waterproof to 3ft

CE Certified**Special Orders- Requirements**

Contact us for special requirements

Toll Free: 1-800-369-6671**Intl:** 1-903-498-3363**E-mail:** sales@larsonelectronics.com

Options:

LEDLB-20E-IR-1550NM- BEAM PATTERN

Example: LEDLB-20E-IR-1550NM-SP

BEAM PATTERN	
Spot	-SP
Flood	-FL









Links (Click on the below items to view):

- [Manual](#)
- [SpectrumChart](#)
- [Hi-Res Image 1 - Infrared LED Light Bar - 20 IR LEDs \(Main\)](#)
- [Hi-Res Image 2 - Infrared LED Light Bar - 20 IR LEDs \(Angle 1\)](#)
- [Hi-Res Image 3 - Infrared LED Light Bar - 20 IR LEDs \(Angle 2\)](#)
- [Hi-Res Image 4 - Infrared LED Light Bar - 20 IR LEDs \(Side 1\)](#)
- [Hi-Res Image 5 - Infrared LED Light Bar - 20 IR LEDs \(Side 2\)](#)
- [Hi-Res Image 6 - Infrared LED Light Bar - 20 IR LEDs \(Mounting Brackets\)](#)
- [Hi-Res Image 7 - Infrared LED Light Bar - 20 IR LEDs \(Top\)](#)