

## EPEXC-25-250V

### Explosion Proof Extension Cord - 25ft - 250 Volt Rated - 2 Pole 3 Wire

Product ID: 106259

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

#### EPEXC-25-250V Explosion Proof Extension Cord

Amp Rating: 20 amp Continuous Service  
Dimensions: Cord length-25 Feet  
Configuration: 2 Pole 3 Wire  
Suitable Plug Cable Diameter: .538" to .639"

#### Receptacle Specs:

Configuration: 2 Pole 3 Wire  
Materials: Copper Free Aluminum  
Dimensions: 3"-W X 5.69"-D X 6.13"-H  
Mating Plugs: EPP-250-2P-20A  
Finish: Epoxy Powder Coat  
[U.L. Certification](#)

#### Plug / Outlet Certifications

Class 1 Div 1 Groups C and D  
Class 2 Div 1 Groups F and G

#### Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: [sales@larsonelectronics.com](mailto:sales@larsonelectronics.com)

## Made in the USA

### Larson Electronics 25` Explosion Proof Extension Cord

The Larson Electronics EPEXC-25-250V Explosion Proof extension cord allows operators to safely extend the range of their explosion proof light or equipment cords beyond the boundaries of the hazardous work area. These units are constructed of 25 feet of 12/3 SOOW explosion proof cord rated at 250 volts. The cord is chemical and abrasion resistant and comes with an explosion proof receptacle installed on one end and an explosion proof plug installed on the other end. We also include an extra matching plug for operators to attach to their

equipment which allows them to avoid any issues with plug and receptacle equipment compatibility with this cord. The plugs on these units are a two pole three wire configuration. To ensure the highest safety, operators should make connections outside of the hazardous area.



[Click Photo to Enlarge](#)

[Click Photo to Enlarge](#)

**Suggested Applications:** Manufacturing, Industrial, Warehouse, Lighting, Explosion Proof Light Fixtures, Grinders, Wet areas or Locations Where Combustible Dust is Present.

---



---

## Frequently Asked Questions (FAQ)



**EPEXC-25-250V**

**Product ID: 106259**

**Export Control Classification Number (ECCN): EAR99**

Links (Click on the below items to view):

- [Canadian CEC Certificate \(Commonly referred to as CSA Certificate\)](#)
- [CE Certificate](#)
- [Certificate 1, Misc](#)
- [Certificate 2, Misc](#)
- [Certificate 3, Misc](#)
- [MSDS \(Material Safety Data Sheet\)](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [SpecSheetSpanish](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)