Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MUL-14-24V

24 Volt Spotlight - 35 Watt HID - 15 Million Candlepower Spotlight - Handheld w/ Magnetic -Coil Cord

Product ID: 1369

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

24 Volt HID spotlight with upright handle, magnetic base and 12 foot coil cord with cigarette plug
1250 foot beam that is 115 feet wide at its widest point. Long tear drop shaped beam pattern.
Weatherproof polycarbonate housing, polycarbonate handle, 3.25 inch diameter, 100 pound grip magnetic base
Lens/housing assembly - 4.5 inches wide by 4.25 inches tall - 6 inches tall with mounting bracket - 5.5 inches deep, weighs 1.4 pounds
Lamp head angle is adjustable
5 inch tall handle contours to hand well
Detachable 12 foot coil cord with heavy duty cigarette plug
100 grip magnetic base sticks to any ferrous metal surface for use, but is can removed for storage or other placement
Precision metal reflectors
35 watt HID Xenon D2 type Lamp
35 watt internal HID ballast - instant on, 15 seconds to full visible power
On 24 Volts DC - 2.4 amps start load on 12 Volts DC - 1.7 amps average draw after 60

seconds
HID color temperature 7000K (bright white)
Borosilicate hardened glass lens
Dust and water resistance (gaskets and seals)
Same unit works on 12 Volts DC and 24 Volts DC - senses voltage and adapts
1P rating: 1P 60
Vibration tolerance: 8.6G RMS
Lumen Output - 3200 lumens +/- 400 lumens
Total Weight: 2 pounds
Total Height: 10 inches
Operating temperature: -40 degrees C to 105 degrees C

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)







Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364



MUL-14-24V

Product ID: 1369

Harmonized System (HS) Code: 8512.20.2080

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- **Operations Manual**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **HigResPic4**
- **HigResPic5**
- **HigResPic6**
- **HigResPic7**
- **HigResPic8**
- **HigResPic9**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**