Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

RNT-EPL-QP-2X150RT-12.3-100

RENTAL 300 Watt Explosion Proof LED Light Tower - Quadpod Mount - C1D1 - 100 foot 12/3 Cord w/ EXP

Product ID: 144138

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

RNT-EPL-QP-2X150RT-12.3-100 Explosion Proof LED Quadpod

Listing: United States & Canada
Lamp Type: Cree LED
Dimensions: 14"-W 16"-H 5"-D- Light Head - 7` to 12` Extendible Tower
Weight: 85 Lbs
Voltage: 120-277V AC 50/60Hz
Total Watts: 300 watts
Total Lumens: 42,000
Luminous Efficacy: 140 Lm/W
Lamp Life: 60,000+ Hours
Color Temp: 5000K, 4000K, 3000K
Color Rendering Index: >75 CRI
Beam Angle: 60° or 125°
Lighting Configuration: Flood Pattern
Power Efficiency: >95%
Power Factor: 0.992
Amperage: 2.5A @ 120V, 1.26 @ 240V, 1.08 @ 277V
Ambient Operating Temp Range: -50° C to +65°C
Operating Temp Rating: T5
Lamp Housing Material: Copper Free Cast Aluminum
Tower Material: Non-Sparking Aluminum Tubing
Lens Material: Hardened Borosilicate Glass
Gasket Material: Silicone
Mounting: Non-Sparking Telescoping Aluminum Tower
Wiring: 100` 12/3 SOOW Cable w/ explosion proof

Ratings/Approvals

Listed for United States and Canada
Class I, Divisions 1 & 2, Groups C and D
Class II, Divisions 1 & 2, Groups E,F,G
Class III, Divisions 1 & 2
Certified to UL 844 Ed. 13
Certified to UL 1598
Certified to C22.2 No. 137 Rev 2009
Certified to C22.2 No. 250.0
T5 Temperature Rating
Paint Spray Booth Approved
IEC 60529 Tested
IP67 Rated Waterproof
LEL Approved
Multiple Driver Banks
80% Lumen Retention after 60,000 Hours
Factory Sealed Light Fixture
100 Foot 12/3 SOOW Cable
Adjustable Tower 7 - 12 Feet
Direct Replacement for 400W MH Towers

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671
Intl: 1-903-270-1187

Cord Cap: 5-15, 5-20, or 6-20


Rental Type: Monthly, Weekly, Daily

Rentals: In an effort to cut back on contracts and various other paper work, Larson Electronics processes rentals like purchases until the product is returned. (Rent to Own Rates) This means, we will charge the customer for the product total and credit back the difference once the fixture is returned. Weekly and Monthly terms are available. Customer must pay shipping to and from the destination. Please contact us at (903) 498-3363 for further information if required.
Rental Prices for the RNT-EPL-QP-2X150RT-12.3-100;;
Monthly...$453.13 USD
Weekly...$302.09 USD
Subtract rental cost from total cost for the amount that will be credited back to customer upon return of product. Customer can choose to convert their rental to a purchase at any time during the rental period. When returned, deductions will also be made for shipping, repairs, and excessive cleaning, if needed.

Fax: 1-903-498-3364
E-mail: sales@larsonelectronics.com


Made in the USA
This unit is for rental
The RNT-EPL-QP-2X150RT-12.3-100 Quadpod Mounted Explosion Proof LED Light Tower from Larson Electronics produces 42,000 lumens of light capable of illuminating an area 14,500 square feet in size. This adjustable Cree LED light tower is designed for portability and durable operation and ideal for use in demanding conditions.
PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS, LIGHT TOWERS, OR QUADPODS*
The RNT-EPL-QP-2X150RT-12.3-100 is a quadpod mounted explosion proof LED lighting system and provides 14,500 square feet of work area coverage with 42,000 lumens of light output. This portable LED light tower has a removable LED light head mounted on top of a four leg durable non-sparking aluminum quadpod equipped with wheels for easy positioning of the unit from one area of the workspace to another. The LED light head on this unit produces a wide flood pattern of light that is ideal for illuminating large workspaces and jobsites. This light is designed for heavy duty use in demanding conditions including emergency services, mining, construction, marine, and industrial operations where durability and reliability is critical.
This portable LED light is comprised of two adjustable explosion proof LED light heads mounted atop a four leg quadpod fabricated from non-sparking powder coated aluminum. This adjustable and collapsible quadpod can be extended to twelve feet, collapsed to seven feet, and includes solid wheels allow the operator to tilt the unit back and simply roll the entire assembly to a new location when fully deployed. The LED light fixture assembly can be removed by releasing the hand knob and sliding the light and mounting bracket off of the center support while the legs can be collapsed, aiding in deployment, storage and transport. The lamp can be easily adjusted vertically and locked into position.


Click Photo to Enlarge


Click Photo to Enlarge


Click Photo to Enlarge







Included with this hazardous location LED light tower is 100 feet of 12/3 SOOW cord

which combined with adjustability offered by the LED light head provides ample length for tower placement and optimal coverage of the workspace. The easy to collapse design of this Class I Division 1 LED work light allows Larson Electronics to avoid pallet freight charges when shipping and deliver these units via UPS next day air service, which in turn improves delivery time and reduces the cost to buyers.
Each LED light head on this tower contains twelve 12.5 watt LEDs producing 140 lumens each. These LEDs are arranged in rows and paired with high purity optics to produce 21,000 lumens and a 60 degree flood beam while only drawing 1.25 amps on 120V, making these units ideal for use as highly efficient yet powerful work and area lights. The RNT-EPL-QP-2X150RT-12.3-100 hazardous location LED light is an ideal replacement for fragile and hot running 400 watt metal halide floodlights.

Click Photos to Enlarge



5-15 Straight Blade Plug



5-20 Straight Blade Plug



6-20 Straight Blade Plug

Wiring & Plug: This explosion proof tower mounted flood lighting system is equipped with 100 feet of 12/3 chemical and abrasion resistant SOOW cord that is fitted with an explosion proof cord cap for easy connection to explosion proof outlets. Plug options include a 5-15 15 amp straight blade plug for use with 120V explosion proof outlets, a 5-20 20 amp straight blade plug for use with 120V explosion proof outlets, or a 6-20 20 amp straight blade plug for use with 220-240V explosion proof outlets.
The LED light head on this unit is small enough to allow it to fit through most standard size manholes and entry points. The LED light head can also be removed from the quadpod, the tower collapsed and the entire assembly passed through a manhole and reassembled once inside. This unit is multi-voltage capable and configured to operate on 120-277 volts 50/60 Hz. This LED light head retains 80% of its lumen output after 60,000 hours of use, far longer than incandescent or fluorescent lamps.

Made in USA Quality

1. Approved Class I Divisions 1 & 2 Class II Divisions 1 & 2
2. Led lamp head requires no lamping and simply slides on the quadpod and is locked into place with a hand tightened set screw.
3. Quadpod constructed of corrosion resistant, non-sparking aluminum with powder coated finish.
4. No ballast box. No ballast to replace.
5. Extreme long life LEDs reduce maintenance and replacement costs.
6. Solid rubber tires. No flats or tube replacements.
7. 25 peel off mylar overspray lamp protectors ship with the unit.
8. 42,000 Lumens produced from only 300 watts.
9. Mercury free shock proof LED lamp light head.

Superior LED Benefits

1. 50,000+ hour lifespan.
2. Can SAVE 50% or more on energy.
3. 100% recyclable.
4. No toxins-lead, mercury.
5. No UV light, infrared radiation or CO2 emissions.
6. Bright, even light maintains consistent color over time.
7. Instant on/off - No flickering, delays or buzzing.
8. Very good color rendering.
9. Vibration/impact resistant.
10. Significantly cooler operation.
11. Less frequent outages, higher output improves workplace safety.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)









Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

RNT-EPL-QP-2X150RT-12.3-100

Product ID: 144138

Export Control Classification Number (ECCN): EAR99

Options:

RNT-EPL-QP-2X150RT-12.3-100-Rental Length-Beam Angle-Cord Cap

Example: RNT-EPL-QP-2X150RT-12.3-100-MR-60DB-1523

Rental Length	
MONTHLY	-MR
WEEKLY	-WR
DAILY	-DR

Beam Angle	
60°	-60DB
125°	-125DB

Cord Cap	
5-15	-1523
5-20	-2023-125V
6-20	-2023-250V

Links (Click on the below items to view):

- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- Certificate 3, Misc
- Dimensional Drawing 2D
- MSDS (Material Safety Data Sheet
- RoHS Certificate (Restriction of Hazardous Substances)
- STEP File (3D CAD Model)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- HigResPic10
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map