Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

MPD-CW1-TB-SE50SZ-NP-1.E33-4.C02-12.L04-M1

50 KVA Portable Power Distribution, 480V-120/240V 1PH, (1) 3100R7W, (4) CS8369, (12) L5-20R

Product ID: 144168

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

MPD-CW1-TB-SE50SZ-NP-1.E33-4.C02-12.L04-M1 -Temporary Power Distribution System

Line-in Cord: Not Included - Requires Minimum Use Wiring 150A Rated Cu @ [600V] (**Customer Provided**)
Line-in Cord Cap: Not Included - Requires Minimum Use Device 150A @ [480V] (**Customer Provided**)
Primary Voltage (V): 480V AC
Primary Phase (PH): 1-Phase (1PH)
Primary Frequency (HZ): 60 Hz (60-cycles)
Primary Panel: -
Primary Breaker: (1) 150A 2P MCCB [480V]; (1) 100A 2P MCCB [480V]
Primary Outlets: (1) 3100R7W 100A Female Pin & Sleeve [480V]
Primary Protection: MCCB Circuit Breaker
Transformer (KVA): 50KVA 480V to 120/240V 1PH N3R
Secondary Voltage (V): 120/240V AC
Secondary Phase (PH): 1-Phase (1PH)
Secondary Frequency (HZ): 60 Hz (60-cycles)
Secondary Panel: 120/240V 1PH 200A MCB N3R
Secondary Breakers: (4) 50A 2P MCB [250V]; (12) 20A 1P MCB [125V]
Secondary Outlets: (4) CS8269 California Standard Twist-Lock Twist-Lock [250V]; (12) L5-20R NEMA Twist-Lock [125V]
Secondary Protection: MCB Circuit Breakers
Form Factor: Blue Powder Coated Steel Closed Cube w/ Casters
Doors: (2)
Frame Material: Steel

Ratings

Max Primary OCP: 150A @ 480V

Max Secondary Output: 200A @ 240V

NEMA 3R Indoor or Outdoor Use
Made in the USA
NRTL Certified to UL 1640
NRTL Certified to CSA C22.2 No. 14

Powder Coat Finish Standards:
Complies with ASTM D-523
Complies with ASTM D-3359
Complies with ASTM D-522
Complies with ASTM D-3363
Complies with ASTM D-2794

Frame Finish: High-strength TGIC Polyester Powder Coated Blue

Cart Handle Orientation: Horizontal

Lifting Eyelet: (4) Top Located

Skid Pockets: (2) Bottom Located

Casters: (4) Locking Casters

Dimensions: 58.5"-L X 33.5"-W X 73.7"-H

Weight: 1650 lbs

Larson Electronics manufactures a wide variety of custom power distribution systems. The pictures displayed for this unit are a general representation of form factor and may not accurately represent this exact configuration in every detail due to being custom builds. The specifics for this configuration are listed in the specification table and one-line diagram.

Special Orders - Special Requirements
Contact us for special requirements

Intl: 1-903-270-1187

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

All grounding shall comply with state and local codes and meet the minimum requirements of the National Electronic Code section 250

Made in Texas

The Larson Electronics MPD-CW1-TB-SE50SZ-NP-1.E33-4.C02-12.L04-M1 Power Distribution Substa converts single-phase 480V AC electrical current to single-phase 120/240V AC. This fully enclosed p distribution unit provides operators the ability to safely tap into and distribute 480V AC power from variety of sources including generators and direct grid power.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO POWER DISTRIBUTION PANELS, TRANSFORMERS, OR SUBSTATIONS*

The MPD-CW1-TB-SE50SZ-NP-1.E33-4.C02-12.L04-M1 temporary power distribution system gives operators th to power their 120 volt equipment from a single system.

Operation:

- Primary Voltage: 1-phase 480V AC
- Primary Receptacles: (1) 3100R7W 100A Female Pin & Sleeve [480V]
- Transformer: 50KVA 480V to 120/240V 1PH N3R
- Secondary Voltage: 1-phase 120/240V AC
- Secondary Receptacles: (4) CS8269 California Standard Twist-Lock Twist-Lock [250V]; (12) L5-20R NEMA Tw [125V]

*See specification table at the top of the page for more information about the power distribution system.

Protective Construction: This temporary power distribution unit is fully enclosed and is ruggedly constructed withstand demanding conditions and industrial applications. The system is accessible via two doors at each end access to breakers on the panels and a center-located door for access to receptacles. The model is equipped wi bottom-located forklift skid pockets and four top-located lifting eyelets, which allows easy lifting with cable or c hooks. Four locking casters at the base provides mobility around work sites.

The power distribution system is constructed of steel with a polyester powder coated blue finish for durability ag dirt, moisture and mild corrosion. This special coating creates a high-strength barrier for protection from accide bumps and scratches. The TGIC polyester powder coat finish offers reliable resistance against chemicals, UV lig light) and degrading elements in outdoor locations. Our powder coating solution ensures robust color retention many years without fading. Custom colors, such as black, grey, desert tan or forest green, and galvanized finis available upon request. Non-standard powder coat colors or galvanized finishes may increase price and lead tim

The transformer and load center/distribution assembly is mounted to a standard steel cube style frame resultin extremely stable, durable and mobile power distribution platform. This temporary power distribution solution ca modified to meet the needs of job-site receptacle requirements. Larger units are available upon request and ca equipped with skids or trailer mounted.

Certification: All units are built in accordance to NFPA 70 (National Electric Code) and certified to UL 1640. All equipment is NEMA 3R rated for indoor and outdoor use and provide a degree of protection against dirt, water, NEMA 4 and NEMA 4X equipment can be equipped upon request.

Grounding: Transformer is grounded to the frame and we provide a grounding lug on the frame for the earth g ~Please check all motor loads for dual rated motors that will work 208 or 240.~

Applications: This power distribution system is ideal for indoor or outdoor use and applications including but n limited to, construction sites, plant maintenance, plant turnarounds, shows, exhibits, and shipyard operations. power distribution systems are popularly used in applications where external power sources are often necessary also offer class rated transformers for use within explosion proof and hazardous location environments.

Custom Built Systems Available: Larson Electronics is a manufacturer and we can build portable power distr systems to your specifications. Although we carry several models of portable power distribution systems in stoc can deliver custom ordered units almost as quickly as our prebuilt units. If this model does not meet your need please contact us at 1-800-369-6671 or sales@larsonelectronics.com to discuss your specific requirements.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364






CAUTION
HIGH VOLTAGE


SIEMENS
ON
OFF
CAUTION

MPD-CW1-TB-SE50SZ-NP-1.E33-4.C02-12.L04-M1

Product ID: 144168

Harmonized System (HS) Code: 8504.21.0040

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- ANSI Certificate 1
- Canadian CEC Certificate (Commonly referred to as CSA Certificate)
- Catalog Page - Product Series
- CE Certificate
- Certificate 1, Misc
- Certificate 2, Misc
- Certificate 5, Misc
- MSDS (Material Safety Data Sheet
- Operations Manual
- RoHS Certificate (Restriction of Hazardous Substances)
- Single Line Diagram (One-Line Diagram)
- USA NEC Certificate (Commonly referred to as UL Certificate)
- Wiring Diagram (Oneline)
- HigResPic1
- HigResPic2
- HigResPic3
- HigResPic4
- HigResPic5
- HigResPic6
- HigResPic7
- HigResPic8
- HigResPic9
- ISO 9001 Certification
- Business Certificate
- Shipping Time Map