

EXP-WRL-TRSM-SLV

Explosion Proof Wireless Signal Receiver - Slave Station

Product ID: 144731

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EXP-WRL-TRSM-SLV Explosion Proof Wireless Signal Receiver

Listing: United States & Canada

Dimensions:

Weight: " W x " D x " H

Voltage: 120-240V AC or 12-24V DC

Housing Material: Non-sparking, Copper Free Aluminum

Operating Temp Rating: T3C

Wiring:

Ratings/Approvals

Class I Divisions 1 & 2 Groups C & D

Class II Divisions 1 & 2 Groups E, F & G

Class III Divisions 1 & 2

IP67 Rated Waterproof

T3C Temperature Rating

New York City Dept. of Buildings Approved

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

XXX

The XP-WRL-TRSM-SLV Explosion Proof Wireless Signal Receiver for the [EPL-TL-2X10W-C-EXWR Signal Light](#) is designed to give operators the freedom and mobility to monitor traffic and processes more effectively. This mobility increases worksite safety by allowing hazards to be detected more quickly by the signal operator, creating a faster response time to potential dangers. Likewise, mobile monitoring produces a more efficient traffic and/or process flow.

The XP-WRL-TRSM-MTR wireless receiver is built to endure harsh conditions and

heavy duty use while providing safe, dependable service to operators. This unit is housed within a rugged IP67 rated copper free, non-sparking aluminum body and features a single push button. To switch between signal colors, the operator simply presses the push button at the top of the device.

The explosion proof wireless remote for this receiver can be found here: [EXP-WRL-TRSM-MTR Explosion Proof Wireless Remote Control](#)

See a demo of the complete light, remote and receiver package here: [EPL-TL-2X10W-C-EXWR Signal Light and Wireless Remote Demo](#)

Mounting: This unit is mounted using the attached trunnion bracket. The bracket comes with three predilled holes and allows for an 180° adjustment range.

Wiring/Power: This unit is designed to operate with 120-240V AC or 12-24V DC.

Suggested Applications: Industrial refueling stations, docks, manufacturing facilities, warehouses

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)









EXP-WRL-TRSM-SLV

Product ID: 144731

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [SpecSheetSpanish](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)