Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPLX-PM-100W-RD2-LED-TRC-100

100W Explosion Proof LED Light - C1D1 - C2D1 - Group B+ ATEX/IECEX - IP68 - A-frame Mount

Product ID: 144747

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPLX-PM-100W-RD2-LED-TRC-100 Explosion Proof LED

Lamp Type: AC LED
Listing: United States, Canada, Europe
Dimensions: 18.09"L x 15.9"W x 23.75"H
Weight: 75 lbs
Voltage: 120V AC, 208V AC, 220V AC or 240V AC
Total Watts: 100W
Lumens: 10,500 (5000K) or 9,500 (3000K)
Luminous Efficacy: 105 Lm/W (5000K) or 95 Lm/W (3000K)
Lamp Life: 60,000+ Hours
Color Temp: 5000K cool white, 3000K warm white
Color Rendering Index: >70 CRI
Beam Angle: 110°
Lighting Configuration: Wide Flood Beam
Power Efficiency: >85%
Power Factor: >0.9
Amperage: 0.83A@120V AC, 0.48A@208V AC, 0.45A@220V AC, 0.41A@240V AC
Ambient Operating Temp Range: -60°C to +100°C
Operating Temp Rating: T6
Housing Material: Copper Free Cast Aluminum
Stand Material: Non-Sparking Aluminum
Lens Material: Hardened Borosilicate Glass
Mounting: Triangular Shaped Aluminum Base Stand (A-frame Mount)
Finish: Powder Coated - Gloss Blue
Wiring: 100` 16/3 SOOW Cord
Cord Cap: 5-15 Straight (120V), 5-20 Twist (120V) or 6-20 Twist (250V) Explosion Proof Plug

Ratings/Approvals

Class I, Division 1, Groups B, C, D
Class II, Division 1, Groups E, F, G
UL 844
UL 60079
UL 1598
IEC Ex d IIB+H2
IEC Ex tb IIIC
IP68 Waterproof
NEMA 6/6P
Factory Sealed Light Fixture
ABS Type Approval

Special Orders - Special Requirements

Contact us for special requirements
Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Warranty: Yes - 5 Years*

E-mail: sales@larsonelectronics.com

The EPLX-PM-100W-RD2-LED-TRC-100 Explosion Proof LED Light from Larson Electronics is a portable, powerful unit that is built to withstand demanding conditions. This luminary features cutting-edge AC LEDs paired with specially designed heat sinks for improved efficiency, thermal management and durability. Available in 5000K cool white and 3000K warm white options, a 110° flood beam provides crisp and bright illumination with broad coverage. This heavy duty Class I Division 1, Class II Division 1 LED lamp is mounted on a sturdy, non-sparking aluminum base that can easily be transported around the hazardous location.

The EPLX-PM-100W-RD2-LED-TRC-100 delivers brilliant illumination and robust performance in a convenient A-frame build. A 110° wide flood beam provides crisp, bright light with broad coverage. This 100-watt unit is listed for use in the United States and Canada and carries IEC Ex and ATEX certifications. Options for voltage includes: 120V AC, 208V AC, 220V AC or 240V AC.

The explosion proof light utilizes AC LEDs paired with a heavy-duty housing and an advanced heat sink that allows for improved efficiency and thermal performance. By eliminating the drivers associated with DC LEDs, space is freed up for more connective surface, accelerating heat dissipation and increasing durability. The specially designed heat sink allows for greater surface area contact with the air as well as a stronger airflow rate. Because this fixture is created for maximum thermal efficiency, it is ideal for applications in which the ambient operating temperature falls into extreme ranges, especially high heat applications. Furthermore, fewer sub-components also means less chances of secondary component failure. The simplified circuit system used within AC LEDs creates greater stability and enhances luminaire lifespan.

The EPLX-PM-100W-RD2-LED-TRC-100 is designed to endure the daily wear and tear inflicted by harsh outdoor conditions such as sun, wind, rain, snow and sleet. as well as to withstand the corrosive effects of saltwater spray in marine environments. Durable IP68 rated construction provides protection against the ingress of dust, dirt and humidity and allows this light to withstand the corrosive elements found within marine environments including saltwater spray.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. Solid state LED lighting is also safer for the environment as LEDs are 100% recyclable. And recycling simultaneously reduces operating costs by eliminating the need for the expensive special disposal services required with traditional gas burning and arc type lamps.

Mounting: This portable LED light is mounted on an A-frame style aluminum base. The portable base stand is fabricated from non-sparking aluminum with a convenient carrying handle built into the top of the stand. The aluminum A-frame is powder coated with glossy blue finish for corrosion resistances and aesthetics. The lamp can be easily adjusted up or down 90 degrees and locked into position by simply loosening the two hand screws located on either side of the light head and retightening them once the desired angle is found.

Click Photos to Enlarge



5-15 Straight Blade Plug



5-20 Straight Blade Plug



6-20 Straight Blade Plug

Wiring/Plug: This explosion proof light is equipped with 100 feet of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an explosion proof cord cap for easy connection to explosion proof outlets. Plug options include a 5-15 15 amp straight blade plug for use with 120V explosion proof outlets, a 5-20 20 amp straight blade plug for use with 120V explosion proof outlets, or a 6-20 20 amp straight blade plug for use with 220-240V explosion proof outlets.
Applications: Oil refineries, petrochemical plants, painting facilities, offshore rigs, marinas, docks, warehouses, garages, commercial buildings and more.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

High Quality Features

1. Each unit dialectically tested.
2. Low power consumption.
3. Instant on/off operation.
4. Fixture constructed of die-cast,corrosion resistant, copper free aluminum alloy.
5. No ballast box. No ballast to replace.
6. Superior color rendering compared to HPS, LPS, MH.
7. Retains 80% lumen output after 60,000 operating hours.
8.Exterior coating rejects dust and buildup.
9. Available in voltages: 120V AC, 208V AC, 220V AC or 240V AC
10. Highly efficient thermal dissipation.
11. Fewer secondary components adds durability and longevity
12. Lighter weight, slimmer, brighter alternative to fluorescent configurations.
13. Explosion Proof / Flame Proof US, CAN, ATEX, IECEx; Rated for use in the United States and Canada

Superior LED Benefits

1. 60,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off - No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)





Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

EPLX-PM-100W-RD2-LED-TRC-100

Product ID: 144747

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

EPLX-PM-100W-RD2-LED-TRC-100-Voltage-Cord Cap-Color Temp

Example: EPLX-PM-100W-RD2-LED-TRC-100-120V-1523-5000K

Voltage	
120V	-120V
208V	-208V
220V	-220V
240V	-240V

Cord Cap	
5-15	-1523
5-20	-2023-125V
6-20	-2023-250V

Color Temp	
5000K	-5000K
3000K	-3000K

Links (Click on the below items to view):

- **Operations Manual**
- **Wiring Diagram**
- **HigResPic1**
- **HigResPic2**
- **HigResPic3**
- **Video1**
- **Video2**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**