Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

RNT-WAL-ML-30-9-4X500LTL-LED-9G

RENTAL 2000W Non-Towable Light Tower w/Wheels-9-30 Feet-(4) 500W LED Lamps - 259,200 Lumens - 9KW

Product ID: 146076

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

RNT-WAL-ML-30-9-4X500LTL-LED-9G 3000VA LED Light Tower

Lamp Type: LED
Cart Dimensions (Transport w/o lights): 46.147"-L x 34.139"-W x 108.825"-H
Cart Dimensions (Deployed w/o lights): 46.147"-L x 47.54"-W x 175.848"-H
Tower Dimensions: Telescoping - 9 - 30`
Voltage: 120-277V AC
Total Watts: 2000 watts
Total Lumens: 259,200
Luminous Efficacy: 129.6 Lm/W
Lamp Life: 80,000 Hours
Ambient Temperature Range: -40°C to +80°C
Lighting Configuration: NEMA 4X4
Lamp Housing Material: Aluminum
Lamp Mounting Bracket Material: Stainless Steel
Optics Material: PMMA
Engine Type: 390CC OHV
Generator: 9KW
Horsepower: 15
Peak Outpit (Surge): 9,000 Watts
Continuous Outpit: 7,000 Watts
Fuel Type: Gasoline
Voltage: 120/240V AC + 12V DC or 220V AC + 12V DC
Outlets: (4) 20A 5-20R, (1) 5-30R, (1) L14-30R, (1) Cigarette Plug Socket

Quick Summary

Extreme Area Coverage

259,200 Total Lumen Output

(4) 500 Watt LED Light Heads

Independently Adjustable Light Heads
Dial-in Adjustability per light head
Powder Coated Steel Construction
IP67 Rated Waterproof
LEL Approved
Gasoline Generator
Adjustable Tower Extends to 30` Above Ground
Vibration & Shock Resistant
Outdoor Approved
Wheeled Cart Base

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Tower Material: Steel
Tower Finish: Powder coated - Gloss blue

Mounting: Adjustable 9 to 30 Foot Wheeled Tower

Wiring: 100` 12/3 SOOW w/ Cord Cap

Cord Cap: L6-20, L14-20

Warranty: Yes - 3 Years

Rentals: In an effort to cut back on contracts and various other paper work, Larson Electronics processes rentals like purchases until the product is returned. (Rent to Own Rates) This means, we will charge the customer for the product total and credit back the difference once the fixture is returned. Weekly and Monthly terms are available. Customer must pay shipping to and from the destination. Please contact us at (903) 498-3363 for further information if required.
Rental Prices for the RNT-WAL-ML-30-9-4X500LTL-LED-9G
Monthly...$2,393.00 USD
Weekly...$1,595.00 USD

Subtract rental cost from total cost for the amount that will be credited back to customer upon return of product. Customer can choose to convert their rental to a purchase at any time during the rental period. When returned, deductions will also be made for shipping, repairs, and excessive cleaning, if needed.

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

Made in the USA

This unit is for rentals.

The RNT-WAL-ML-30-9-4X500LTL-LED-9G 2000 Watt LED Light Tower on Non-Towable Wheeled Cart with 9000 watt Generator from Larson Electronics is an ideal solution for operators who need a fully portable, self contained, easy to operate light system capable of illuminating large areas. Adjustable from 9 to 30 feet in height above the cart deck and equipped with four 500 watt LED lamps, this unit will provide over 259,200 lumens of quality illumination. This portable light tower will run for up to 8 hours uninterrupted on a single tank of fuel.

PLEASE NOTE: ANY FREE SHIPPING OFFERS DO NOT APPLY TO LIGHT MASTS OR LIGHT TOWERS

The RNT-WAL-ML-30-9-4X500LTL-LED-9G light tower with generator is a portable lighting system designed high mobility while providing enough output to illuminate approximately 4 acres of area effectively. Equipped with four 500 watt high output LED lamps, this LED light tower provides operators with an easily deployed lighting system that can provide large scale illumination. This crank-up style light mast allows operators to extend the light mast from 9` to 30` above the deck of the pull around cart, elevating the light heads to heights up to 30` above ground level. This light tower provides operators with an easily deployed lighting system that can provide large scale illumination for up to 8 hours on a single tank of gas.

Click Photo to Enlarge



Click Photo to Enlarge



Click Photo to Enlarge




This portable flood lighting system is comprised of four adjustable LED light heads mounted atop a telescoping light tower mounted to a wheeled cart base. This adjustable and collapsible tower can be extended to thirty feet, collapsed to nine feet, and includes four wheels allow the operator simply roll the entire assembly to a new location when fully deployed. The LED light fixture assembly can be removed by releasing the hand knob and sliding the light and mounting bracket off of the center support, aiding in deployment, storage and transport. The lamp can be easily adjusted vertically and locked into position.
The WAL-ML-30-9-4X1000W-9G light tower features an extendable tower

assembly that can be adjusted from 9 to 30 feet in height for maximum coverage. A single hand crank allows operators to easily raise or lower the tower as needed, and a removable lamp mounting platform allows removal of the lamp assembly for easier transport and storage. The tower is constructed of heavy gauge steel for durability, and a tough powder coat finish provides protection against rust and corrosion. The base of the tower is fitted with two solid wheels to allow easy positioning; the operator can simply tilt the unit back and roll it into the desired location as needed.

Lights: Included with this light tower are four of our wet area suitable GAU-LTL-500W-LED LED fixtures producing approximately 64,800 lumens each, for a combined total of 259,200 lumens at 2,000 watts.

The GAU-LTL-500W-LED LED light from Larson Electronics produces 64,800 lumens of high intensity light while drawing only 480 watts at 5 amps from a 120 volt electrical system. Fourty-Eight CREE® high output LEDs producing 1,350 lumens each are arranged in rows and paired with PMMA high purity optics to produce a well focused 24° wide spot beam that is ideal for providing far reaching concentrated illumination while still covering a substantial amount of area. We also offer optional optics with 10° spot, 38° narrow flood, 60° flood, and 90° wide flood beam spreads. The spot beams are tightly focused and are designed for high elevation mounting to achieve distance, making spot versions ideal for high mast and spots lighting. The flood beams are designed to provide more light over a larger area nearer the fixture, making flood versions ideal for use as dedicated work and area lights.

The GAU-LTL-500W-LED LED light offers intense light output and is ideal for flood lighting, high mast lighting, light towers, as well as industrial and outdoor lighting applications. Producing 64,800 lumens, a 4.25 amp draw at 120V, 80,000 hour service life, 120-277 volt compatibility, and IP67 waterproof rating, this LED flood light provides operators with a rugged and powerful LED alternative to 1500 watt metal halide lamps that uses little power and can withstand rugged use and abusive conditions. GAU-LTL-500W-LED lights are ideal replacements for fragile and hot running 1500 watt metal halide lamps. They offer low power requirements, high durability and a versatile mounting system that makes these LED light emitters a superior lighting solution for demanding applications where power and reliability is critical.



Click Photo to Enlarge

The above image shows the comparison of the traditional (4) 1500 watt metal halides light fixtures mounted to a 30` light tower (left) to (4) GAU-LTL-500W-LED 500 watt LED light fixtures mounted to a 30` light tower. The area being illuminated by each tower is 300` in length and 250` in width. Unlike the metal halide light fixtures, there are no hot spots with these LED fixtures. This high output LED light fixture provides an even beam spread over the targeted work area without overcast, glare, light spillage, and wasted illumination. Color rendering is also increased with LED light plants, providing a more realistic night vision that more closely resembles natural daylight illumination.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases

to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.
LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.
Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units feature individual heat sinks per bank of six LEDs to control heat buildup rather than utilizing a single housing to dissipate heat. This allows for more thorough cooling of the LEDs for extended operating periods. This allows the LEDs to be driven at up to 90% capacity without overheating or visible loss of light output. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 80,000 hours.
Durability: As well as unparalleled heat control, the GAU-LTL-500W-LED series of LED lights from Larson Electronics also offer IP67 rated construction that is designed to withstand extremes of environmental and operating conditions. These units can withstand rapid temperature changes of -40° Celsius to +80° Celsius, are waterproof, and resist ingress of dust, dirt and humidity. The housings are formed from die cast aluminum and the optics are high transmission PMMA with 98% light transmittance. The CREE® LEDs help these units achieve resistance to vibrations and are rated at 70% lumen maintenance after 80,000 hours of use. We recommend these LED lights for use in applications where a lot of vibration, dust, dirt, dampness and abusive working conditions are encountered.
Generator: A single 15 HP, 9000 watt peak, 7000 watt continous power generator is mounted to the base of this tower to provide standalone power for the metal halide lamps and allows for quiet operation and up to 8 hours of run time on a single tank of fuel. This generator also includes four 120V 20A outlets, a 120/240V 30A twist lock outlet, a 120V 30A twist lock outlet, and a 12 volt lead terminal for accessory attachments, allowing operators to run tools and other equipment while also operating the lights. Larson Electronics is a manufacturer and as such offers a variety of custom options including different lamp wattages and types.
At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Made in USA Quality

1. Each unit dialectrically tested.
2. Fixture arrives assembled and lamped to reduce installation time and cost. Adjustable mounting brackets enable the operator to choose any mounting angle for the fixture.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy
4. No ballast box. No ballast to replace. We simply run the black wire to one end of the bulb and white wire to the other.
5. Heavy gauge extruded aluminum reflectors with high gloss reflective finish. Resists dents and corrosion.
6. A wrench is used to unscrew the end caps for relamping the fixture, while some competitive models require the "tap

Superior LED Benefits

1. 50,000 hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LEED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off - No flickering, delays or buzzing.

and knock off" method to loosen the end cap.
7. Explosion proof, impact and heat resistant Pyrex tubes provide lamp protection.

11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.
15. California Title 24 Compliant

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364







Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671

www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

RNT-WAL-ML-30-9-4X500LTL-LED-9G

Product ID: 146076

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

RNT-WAL-ML-30-9-4X500LTL-LED-9G-Rental Length-Beam Angle

Example: RNT-WAL-ML-30-9-4X500LTL-LED-9G-MR-10SP

Rental Length	
MONTHLY	-MR
WEEKLY	-WR
DAILY	-DR

Beam Angle	
10° SPOT	-10SP
24° WIDE SPOT	-24WS
38° NARROW FLOOD	-38NF
60° FLOOD	-60F
90° WIDE FLOOD	-90WF

Links (Click on the below items to view):

- **HigResPic1**
- **ISO 9001 Certification**
- **Business Certificate**
- **Shipping Time Map**