

EPS-2XPB-SG-15C-GAP

Explosion Proof Push Button Stop/Start Switch - Motor Starter Switch - 15' 16/3 SOOW - Gen Cord Cap

Product ID: 146103

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

EPS-2XPB-SG-15C-GAP - C1D1 Explosion Proof Push Button Switch

Listing: United States

Dimensions: 5.1"-L x 5.875"-W x 5.25"-H

Weight: 5 lbs

Voltage Rating: 250 Volts Max

Current Rating: 10 Amps Max @ 250V

Switch Type: Push Button

No. of Switches: 2

Switch Labels: Start / Stop

Materials: Box: Malleable Aluminum / Sealing Chamber: Cast Copper Free Aluminum Alloy

Insulation: Integral Bushings in Conductor Openings

Mounting: External Mounting Lugs on Body

Configuration: Feed Thru / Dead End

Hub: 1/2" or 3/4" NPT

Wiring: 3` 16/3 SOOW Cable

Cord Cap: 5-15, 6-15, 5-20, 6-20, L5-15, L6-15, L5-20, L6-20, BS1363, Schuko, or Pigtail

Warranty: Yes - 3 Years

Ratings/Approvals

Listed for United States

Class I, Divisions 1 & 2, Groups B, C, D

Class II, Division 1, Groups E,F,G

Class II, Division 2, Groups F & G

Class III, Divisions 1 & 2

NEMA 3

NEMA 7, Groups C, D

NEMA 9, Groups E, F, G

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com



Frequently Asked Questions (FAQ)









EPS-2XPB-SG-15C-GAP

Product ID: 146103

Export Control Classification Number (ECCN): EAR99

Options:

EPS-2XPB-SG-15C-GAP-Cord Cap-Hub Config-Termination

Example: EPS-2XPB-SG-15C-GAP-5.15-0.50IN-DE

Cord Cap	
5-15 STRAIGHT	-5.15
6-15 STRAIGHT	-6.15
5-20 STRAIGHT	-5.20
6-20 STRAIGHT	-6.20
L5-15 TWIST	-L5.15
L6-15 TWIST	-L6.15
L5-20 TWIST	-L5.20
L6-20 TWIST	-L6.20
UK BS1363	-BS1363
INTL SCHUKO	-SCHUKO
PIGTAIL	-PIGTAIL

Hub Config	
1/2 HUB	-0.50IN
3/4 HUB	-0.75IN

Termination	
DEAD END	-DE
FEED-THRU	-FT

Links (Click on the below items to view):

- [Operations Manual](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)