

FPM-60-WP60E

60W Low Profile LED Pole Mount Light w/ Glare Shield - Wide Flood Beam - 5' Pole w/ Mounting Bracket

Product ID: 146317

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

FPM-60-WP60E Pole Mounted LED Light

Listing: United States - Canada

Lamp Type: CREE LED

Dimensions: Light Head - W-9" D-3.25" H-6.5" Pole - 5` (60") H

Weight: 10.75 Lbs

Voltage: 120-277 Volts AC

Total Watts: 60

Total Lumens: 5400

Luminous Efficacy: 90 lm/w

LED Life Expectancy: 50,000+ hours

Color Temp: 5600K, 4000K, or 3000K

Color Rendering Index: 80

Beam Angle: 60° Vertical, 75° Horizontal

Lighting Configuration: Flood Beam

Power Efficiency: >95%

Power Factor: 0.992

Amperage: 0.5A @ 120V, 0.25 @ 240V, 0.22 @ 277V

Ambient Temp Range: -25°C to +60°C

Housing Material: Cast Aluminum

Lens Material: Polycarbonate

Mounting: Aluminum Pole Mount w/ Surface Mounting Bracket

Wiring: 25` 16/3 SOOW

Cord Cap Options: 5-15 Straight, 6-15 Straight, L5-15 Twist, L6-15 Twist. UK BS1363, Intl. Schuko, Pigtail

FPM-60-WP60E Features

Waterproof/Vapor Proof

Operates on Standard 120-277V AC

Impact/Vibration Resistant Construction

50,000+ Hour LED Life

Mounted on 5` Aluminum Pole

ETL Approved for Wet Locations

IP68 Waterproof

Surface Mounting Bracket on Pole

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

E-mail: sales@larsonelectronics.com

Larson Electronics LLC
9419 E US HWY 175, Kemp, TX 75143
Phone: 800.369.6671



www.LarsonElectronics.com
Email: sales@LarsonElectronics.com
Fax: 903.498.3364

Frequently Asked Questions (FAQ)

FPM-60-WP60E

Product ID: 146317

Warranty: 36 Months

Harmonized System (HS) Code: 9405.10.8020

Export Control Classification Number (ECCN): EAR99

Options:

FPM-60-WP60E-Color Temp

Example: FPM-60-WP60E-56K

Color Temp	
5600K	-56K
4000K	-40K
3000K	-30K

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)