

25W Blue LED Spotlight - 3.5-10' Aluminum Tripod - 2250 Lumens - IP67 - 120-277V AC - 25' SOOW

Part #: [WAL-TP-LEDWL-25W-BLU-25-1227](#)



The WAL-TP-LEDWL-25W-BLU-25-1227 from Larson Electronics is a Blue LED Spotlight with Aluminum Tripod Mount that produces 2250 lumens of high intensity blue LED light while drawing only 25 watts and offering operators a versatile and flexible lighting solution for a wide variety of tasks. This LED spotlight operates on 120-277V AC that is stepped down to 12V via inline transformer and is equipped with a choice of general area cord caps.

The WAL-TP-LEDWL-25W-BLU-25-1227 is an ideal spotlight for a variety of different tasks and applications that features a convenient on/off switch for simple operation of the 25 watt LED light head. Five 5-watt blue LED producing 450 lumens each are combined with high purity optics to produce a narrow 5° spread spot beam, providing a high intensity center beam which is visible during daytime and nighttime operations. This particular unit is mounted on an adjustable aluminum tripod that can be lowered to 3.5 feet and raised up to 10 feet for ideal illumination patterns in a variety of different non-hazardous locations.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Heat Management: Heat is the single largest factor in premature LED failure and color shifting. These LED units contain advanced drivers which use pulse width modulation to control heat buildup rather than simple voltage regulators which are typically harsh on sensitive electronics and can contribute to early LED failure. These units automatically sense the temperature of each LED and adjust the energy frequency or "duty cycle" accordingly to maintain heat levels within acceptable ranges. This system in essence flashes current at an extremely fast on and off rate to each LED based upon the LED's core temperature. This flash rate is too fast to detect with the human eye, but provides precise control of the current flowing to each LED and thus the heat it generates. This allows the LEDs to be driven at up to 100% capacity without overheating or visible loss of light output. The LEDs are always driven at the same voltage but the duty cycle, however, is changed to alter how long the LEDs are actually on or off. The end result is more light with less heat and longer LED life with an average 70% lumen maintenance after 50,000 hours.

This LED work light is built for durability and comfort with an impact resistant housing, an aluminum tripod mounting system and a light head that can be fully adjusted to suit any mounting location or required lighting angle. The 3.91" wide by 2.36" deep inch diameter light head and lens assembly is protected by a polycarbonate lens that make these LED spotlights waterproof to 1 meter and resist ingress of dust, dirt and humidity. The WAL-TP-LEDWL-25W-BLU-25-1227 is UV resistant, weatherproof, and ruggedly constructed to withstand demanding environments, conditions and applications.

Mounting: This particular unit is equipped with an adjustable aluminum tripod that can reach heights up to 10 feet and be lowered to 3.5 feet for applications where a lower height is required or for storage and transportation. The heavy duty aluminum tripod is durable, lightweight and adjustable to any length between 3.5 feet and 10 feet. A single mounting bracket holds the LED light and allows it to be adjusted and aimed horizontally and vertically. This adjustability allows users to expand the area covered or to focus more intense coverage on a smaller area. The tripod legs can be collapsed and the light head bracket removed with the light still on it for simple portability and deployment. The heavy duty construction of this tripod and the light weight of the LED fixture results in a portable yet very stable lighting platform that will hold its position, even in very windy conditions. The inline transformer on the WAL-TP-LEDWL-25W-BLU-25-1227 is mounted on the center of the tripod mount which reduces ground clutter and tripping hazard while the unit is deployed.

This LED spotlight is built for durability and comfort with an impact resistant housing and a light head that can be adjusted horizontally and vertically. The 3.91" wide by 2.36" deep inch diameter light head and lens assembly is protected by a polycarbonate lens that make these LED hunting spotlights waterproof to 1 meter and resist ingress of dust, dirt and humidity.

Durability: The WAL-TP-LEDWL-25W-BLU-25-1227 series handheld LED hunting lights from Larson Electronics offer IP67 rated construction that is designed to withstand the rigors of demanding of environmental and operating conditions yet are lighter and smaller than other hunting spotlights on the market. This series is designed to provide a low profile, light weight, high performance spotlight. These units can operate in temperatures of -40° Celsius to 80° Celsius, are waterproof to 1 meter and resist ingress of dust, dirt and humidity. The housings are formed from extruded aluminum and the lenses are unbreakable polycarbonate. The LEDs offer inherent LED resistance to shocks and vibrations contributing to these units 15.6Grms rating of vibration tolerance.

[Click Photos to Enlarge](#)



5-15 Straight Blade Plug
15 Amp / 125V Rated



L5-15 Twist Lock Plug
15 Amp / 125V Rated



L6-15 Twist Lock Plug
15 Amp / 250V Rated



UK BS1363 Straight Blade Plug
13 Amp / 250V Rated / Internal Fuse



Intl Schuko 2-Pin Plug
16 Amp / 250V Rated / Grounded



Flying Leads / Pigtail Wires

Wiring/Plug: This general use tripod mounted LED light fixture is equipped with 25 feet of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an industrial grade cord cap for easy connection to common wall outlets. Plug options include standard 5-15 15 amp straight blade plug for 110V wall outlets with ground, standard 6-15 15 amp straight blade plug for 220-240V wall outlets with ground, NEMA L5-15 15 amp twist lock plug for 125V twist lock outlets, NEMA L6-15 15 amp twist lock plug for 240V twist lock outlets, British BS1363 13 amp fused 3-blade plug for United Kingdom outlets, or a two pin 16 amp rated Schuko plug with ground contact and socket for European outlets up to 250V. Alternatively, we can provide flying leads with no plug for hard wire applications or for operators who prefer to wire in user provided cord caps. Please choose pigtail option below for flying leads with no plug.

Versatility: The entire unit weighs only 12 lbs. The light head is mounted to the tripod with an adjustable hinge that allows the head to be adjusted horizontally and vertically. This unit is ideal for hunting and other outdoor operations as well as any application that requires an extremely durable and effective source of portable illumination. The WAL-TP-LEDWL-25W-BLU-25-1227 is also an ideal spotlight for general use in a variety of applications including property maintenance, security, farm operations, search and rescue, and law enforcement.

High Quality Features

Superior LED Benefits

1. Low power consumption.
2. Instant on/off operation.
3. Fixture constructed of extruded corrosion resistant copper free aluminum alloy.
4. Superior color rendering compared to HPS, LPS, MH.
5. Retains 70% lumen output after 50,000 operating hours.
6. Powder coated aluminum fixture body.
7. 3.5-10` adjustable aluminum tripod included
8. Low profile - Light weight
9. 2,250 Lumen output from 25 watts

1. 50,000+ hour lifespan.
2. Can SAVE 50% or more on energy.
3. Qualifies retrofit projects for financial incentives, including utility rebates, tax credits and energy loan programs.
4. Reduces energy use and prolongs life-spans of peripheral cooling units (A/C, refrigeration)
5. 100% recyclable.
6. No toxins-lead, mercury.
7. No UV light, infrared radiation or CO2 emissions.
8. Qualifies buildings for LED and other sustainable business certifications.
9. Bright, even light maintains consistent color over time.
10. Instant on/off - No flickering, delays or buzzing.
11. Very good color rendering.
12. Vibration/impact resistant.
13. Significantly cooler operation.
14. Less frequent outages, higher output improves workplace safety.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Specifications / Additional Information**WAL-TP-LEDWL-25W-BLU-25-1227 Tripod Mount Blue LED Spotlight****Lamp Type:** Blue LED**Dimensions:** 8"-H x 3.91"-W x 3.59"-D**Weight:** 12 lbs**Voltage:** 120-277V AC**Watts:** 25W**Lumens:** 2,250**Luminous Efficacy:** 90 Lm/W**LED Light Color:** Blue**LED Life Expectancy:** 50,000 hours**Led Drive %:** 90%**Lighting Configuration:** 5° Spot Beam**Ambient Operating Temp Range:** -40°C to +80°C**Waterproof Rating:** IP67**Vibration Resistance:** 15.6Grms**Housing Material:** Die Cast Aluminum**Housing Color:** Black**Wiring Options:** 5-15 Straight, 6-15 Straight, L5-15 Twist, L6-15 Twist, UK BS1363, Intl. Schuko, Pigtail**Lens Material:** Polycarbonate**Optics:** PMMA**Mounting:** 3.5-10` Adjustable Aluminum Tripod**Warranty:** Yes - 1 Year***Ratings/Approvals**

IP67 Waterproof to 1 Meter

Impact/Vibration Resistance

Shatterproof Lens

Ambient Op Temp -40°C to +85°C

Available with General Area Cord Cap

Ideal for Hunting and Outdoor Applications

Extremely Durable and Versatile

3.5-10` Adjustable Aluminum Tripod Mount

Special Orders- Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671**Intl:** 1-903-498-3363**E-mail:** sales@larsonelectronics.com[Scroll Down to Purchase-](#)

[This product does not qualify for free shipping.](#)

[Part #: WAL-TP-LEDWL-25W-BLU-25-1227 \(146349\)](#)

Options:WAL-TP-LEDWL-25W-BLU-25-1227- **CORD CAP****Example:** WAL-TP-LEDWL-25W-BLU-25-1227-5.15

CORD CAP	
5-15 Straight	-5.15
6-15 Straight	-6.15
L5-15 Twist	-L5.15
L6-15 Twist	-L6.15
UK BS1363	-BS1363
Intl Schuko	-Schuko
Pigtail	-Pigtail

Links (Click on the below items to view):

- [High Res Image 25W Blue LED Spotlight](#)