

RTPM-GL20004

Rechargeable Remote Control LED Spotlight - 12-24V DC, 5000 Lumens - (1) Wireless Remote - Telescoping Pole Mount - Black Housing

Product ID: 146489

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

RTPM-GL20004 Rechargeable LED Search Light w/ Wireless Remote

Lamp Technology: LED

Light Dimensions: 5.9" x 7.1" x 7.5"

Base Dimensions: 6.06" x 6.06"

Remote Qty: (1)

Spotlight Weight: 4.2 lb

Voltage: 12 V DC or 24 V DC

Total Watts: 50W

Lumens: 5,000

Candela: 550,000

Beam Distance: 4,915 Feet

Luminous Efficacy: 100 Lm/W

LED Life Expectancy: 50,000+ Hours

LED Light Color: White

Correlated Color Temperature: 5,700-6,000K

Beam Angle: 8° Spot

Lighting Configuration: Spot

Light Head Rotation: 360° - Continuous

Elevation Angle: 135°

Rotation Speed: 19° per Second (Fast), 19° per Second (Slow)

Elevation Speed: 11° per Second

Wireless Remote Control Frequency: 433.92 MHz

Remote Controls: On/Off, Up, Down, Left, Right, Speed Control

Wireless Remote Distance: 215'

Wireless Remote Batteries: (2) 23A - Included

Ratings/Approvals

IP68 Rated LED Module

IP56 Rated Housing

FCC Approved

Auto-Home Return

Adjustable Pole

Air Cushioned Chamber (Pole)

Amps: 4 A @ 12 V DC, 2 A @ 24 V DC
Battery Type: Lithium Ion / 12 Cells, 2,200ma Per Cell
Capacity: 8.8 Amp Hours
Battery Voltage: 12 V DC
Switch: Booted On/Off
Battery Recharge Time: 2 Hours
Charging Unit: 110 V AC - 240 V AC, 50/60 Hz Wall Charger
Battery Case Material: CNC Machined Aluminum
Battery Case Color: Black
Ambient Operating Temp Range: -30°C to +70°C
Housing Material: Acrylonitrile Styrene Acrylate (ASA)
Lens Material: Hardened Polycarbonate
Pole Type: Telescoping Equipment/Light Pole
Material: Aluminum
Weight Capacity: 100 lb
Pole Dimensions: Extends from 3' to 8'
Pole Weight: 3 lb
Mounting: Bracket for Equipment/Light Mounting

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

The RTPM-GL20004 from Larson Electronics is a Rechargeable LED Search Light that provides intense output in outdoor locations and is recommended for lighting support during nighttime operations, emergencies, patrolling, and more. This LED light operates on 12 V or 24 V DC and provides 5000 Lumens of output during use. Equipped with a wireless remote, the LED light with black housing features a telescoping pole mount that can be permanently mounted.

The RTPM-GL20004 is a powerful lighting solution for outdoor areas, rugged environments, and remote locations. A total of ten, 5-watt LEDs provide an 8° spot light beam that can reach distances up to 4,915 feet. The low voltage LED search light generates 5000 Lumens of output. During use, this unit rotates at a rate of 19° per second in fast mode and 12° per second in slow mode, as well as elevates at a rate of 11° per second. The LED module carries an IP68 rating and the housing is IP56 rated. Equipped with an acrylonitrile styrene acrylate (ASA) housing, the lens is made out of hardened polycarbonate.

Remote Control: This rechargeable unit comes with one wireless handheld remote control. The wireless handheld remote operates on 433.92 MHz and enables on/off, up, down, left, right, and strobe on/off operation. Powered by two 23A batteries (included), the remote has an operating distance of 213'. Up to four wireless remote controls can be used with the LED light.

LED Benefits: Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation and/or transportation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current is applied, providing instant illumination with no warm up or cool down time before re-striking. Because there is no warm up period, this light can be cycled on and off with no reduction in lamp life.

LED lights run at significantly cooler temperatures than traditional metal halide and high pressure sodium lights and contain no harmful gases, vapors, or mercury, making them both safer and more energy efficient. No extra energy is wasted in cooling enclosed work areas due to external heat emissions from bulb type lights, and the operator risks associated with traditional lighting methods, such as accidental burns and exposure to hazardous substances contained in the glass bulbs, are eliminated. In addition, LEDs are also safer for the environment as they are 100% recyclable, which eliminates the need for costly special disposal services required with traditional gas burning and arc type lamps.

Voltage: The LED search light operates on 12 V DC or 24 V DC.

Rechargeable Battery: The RTPM-GL20004 is outfitted with a rechargeable battery pack that allows for use in remote locations with no access to power. The rechargeable lithium ion battery pack that is screwed into the pole top bracket (T-handle screw can be used to remove the pole's top bracket) provides 12 volts DC with an 8.8 amp hour capacity and can be recharged from a fully discharged state in only two hours. An included wall charging unit allows users to recharge this unit

from any common 110V AC – 240V AC 50/60hz wall outlet. An IP67 waterproof rated housing provides protection against water and dampness and a booted on/off switch provides simple power control.

Telescoping Pole Mount: The rechargeable LED search light is mounted on a telescoping pole that has a bracket for permanent mounting. This unit can easily support up to 100 pounds when fully extended. Any equipment mounted on this aluminum telescoping pole will not become damaged thanks to the air cushioned chamber. The chamber provides a slow and controlled descent of the pole even with heavy equipment or lighting attached. Harsh drops will not happen even if the operator accidentally lets go of the pole during the lowering process. The lowering process on this telescoping aluminum pole is easy to operate. The operator simply lifts up the self-locking collar and allows sections of pole to be lowered into the unit.

The self-locking collar also enables the pole to be extended and remain in the desired position without ever tightening the collar. The bracket on top of the unit is ideal for mounting permanent mount lights. A T-handle screw can be used to remove the pole's top bracket. The convenient maximum height of the aluminum telescoping pole allows for mounted lights to provide maximum area illumination.

Applications: Outdoor locations, vehicles, boats, law enforcement, emergency services, and more.

At Larson Electronics, we do more than meet your lighting needs. We also provide replacement, retrofit, and upgrade parts as well as industrial grade power accessories. Our craftsmen can custom build any lighting system and/or accessories to fit the unique demands of your operation. A commitment to honesty, quality, and dependability has made Larson Electronics a leader in the lighting and electronics business since 1973. Contact us today at 800-369-6671 or message sales@larsonelectronics.com for more information about our custom options tailored to meet your specific industry needs.

Frequently Asked Questions (FAQ)



RTPM-GL20004

Product ID: 146489

Export Control Classification Number (ECCN): EAR99

Links (Click on the below items to view):

- [HigResPic1](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)