

RNT-EPL-SL-10-LED-E2E

***RENTAL* Explosion Proof LED String Lights - 10 lights - Daisy Chain End-2-End Connection - 100ft**

Product ID: 147209

Please see last page for supporting documentation for this product(certificates, CAD files & drawings, IES files, wiring diagrams, etc).



Larson Electronics LLC manufactures a wide variety of products, including custom built to spec designs. The pictures displayed for this unit are a general representation of form factor for the product line and may not accurately represent this exact configuration in every detail due to custom builds and changes between similar products in our standard catalog. The specifics for this configuration are listed in the specification table and supporting documentation (CAD files, Dimensional Drawing, Name Plate Diagram, Wiring Diagram, etc.). This means that specific details (receptacles, plugs, wires, connections, mounting brackets, external finishes, etc.) may not be accurately represented in images vs specifications. Please review specifications and do not order based solely on images.

RNT-EPL-SL-10-LED-E2E

UL Listing: United States

Dimensions- Each Lamp: L-16.5" Diam-5"

Total Watts: 100

Single Lamp Watt: 10 watts

Voltage: 120-277V AC or 12-24V DC

Amps: 0.84 120V AC

Mounting: Handheld / Hanging via Aluminum Hooks

Wiring: 100' 14/3 SOOW Cable - 20A EXP Plug - EXP Outlet

Total Length: 125'

Single Lamp Weight: 6 lbs

Total Weight: 70 lbs

Rental Type: Monthly, Weekly, Daily

YOU CAN RENT THIS UNIT. CONTACT 1-800-369-6671.

Rentals: In an effort to cut back on contracts and various other paper work, Larson Electronics processes rentals like purchases until the product is returned. (Rent to Own Rates) This means, we will charge the customer for the product total and credit back the difference once the fixture is returned. Weekly and Monthly terms are available. Customer must pay shipping to and from the destination. Please contact us at (903) 498-3363 for further information if required.

Rental Prices for the RNT-EPL-SL-10-LED-E2E;

Monthly...\$624.05 USD

Subtract rental cost from total cost for the amount that will be credited back to customer upon return of product. Customer can choose to convert their rental to a purchase at any

U.L. Ratings

Class 1, Divisions 1 & 2, Groups C, D

Class 2, Divisions 1 & 2, Groups, F, G

Class 1, Zone 1, Group IIB

NEMA 4X

Special Orders - Special Requirements

Contact us for special requirements

Toll Free: 1-800-369-6671

Intl: 1-903-270-1187

Fax: 1-903-498-3364

E-mail: sales@larsonelectronics.com

time during the rental period. When returned, deductions will also be made for shipping, repairs, and excessive cleaning, if needed.

Made in the USA

THIS UNIT IS FOR RENTALS

The Larson Electronics RNT-EPL-SL-10-LED-E2E Explosion Proof String Light set is UL Listed Class 1 Division 1 Groups C and D and is ideal for general close work and inspection activities in hazardous locations requiring explosion proof protection.

[Click here to see the Incandescent version of this light](#)

This explosion proof string light set from Larson Electronics contains a total of ten 10 watt work lights equipped with aluminum hooks and connected in series along 100 feet of 14/3 SOOW explosion proof cord. A molded T junction is mounted every ten feet, with 3 feet of 16/3 SOOW cord connecting a single drop light to the backbone. The cord on this unit is terminated with a 20 amp 5-20 or 6-20 Class 1, Division 1 explosion proof plug for complete protection. With this arrangement, each drop light cannot spark if pulled apart or dragged. An 25 foot tail section of main SOOW cord is included to allow ample length for connection to power sources. An explosion proof outlet at the end of the backbone provides the ability to connect multiple units end to end, allowing operators to daisy chain multiple stringers together along the jobsite.



100FT of 14/3 SOOW Explosion Proof Cord



[Click Photo's to Enlarge](#)




Explosion Proof Daisy Chain Outlet



100 Watt Incandescent Bulb



Molded T Connector w/ Hook Ring



With the RNT-EPL-SL-10-LED-E2E

Unlike gas burning and arc type lamps that have glass bulbs, LEDs have no filaments or fragile housings to break during operation. Instead of heating a small filament or using a combination of gases to produce light, light emitting diodes (LEDs) use semi-conductive materials that illuminate when electric current applied and emitting light. With LED lights, there is no warm up time or cool down time before re-striking and provide instant illumination when powered on, adding to the reliability of LED technology. By nature, LED light sources run significantly cooler than traditional lamps, reducing the chance of accidental burns and increased temperatures due to heat emissions. This solid state design of light emitting diodes provides a more reliable, stable, durable, and energy efficient light source over traditional lighting.

This unit incorporates ten explosion proof LED hand lamps connected in series and is suitable for use in areas where petrochemical vapors and various dusts are present. The machined aluminum housings, cast aluminum guard, tempered glass lamp globe, and abrasion resistant cord make this a very durable unit that will resist damage from chemicals, abrasion, vibrations and impacts. This string lighting solution will provide the lighting you require in a flexible, easy to manage configuration. The hand lamps can be moved around and hooked to different points on your scaffold. The lights, however must remain within 10 feet of one other. Each molded T section contains a hook eyelet, allowing operators to

suspend the entire backbone off the ground and out of the work space. This explosion proof string light is equipped with an explosion proof outlet 5` from the last junction point, allowing operators to connect multiple units together end to end. Operators can daisy chain up to 10 units end to end in 120 volt or 20 units in 240 volt configurations. Up to three units in 24 volt AC/DC can be connected end to end.

Stringer Energy Consumption Comparison

	<u>Incandescent</u>	<u>CFL</u>	<u>LED</u>
Wattage	1000 watts	260 watts	100 watts
Amp Draw @ 120V AC	8.34 amps	2.17 amps	0.84 amps
Amp Draw @ 277V AC	3.61 amps	0.94 amps	0.36 amps
Amp Draw @ 12V DC	83.34 amps	21.67 amps	8.34 amps
Amp Draw @ 24V DC	41.67 amps	10.84 amps	4.17 amps
Lamp Life Expectancy	1,500 hours	8,000 hours	50,000 hours
Color Temperature	2800K	4300K	6000K
Operation cost per year (8hs/day @ 11c/kWh)	\$321.2	\$83.52	\$32.12

This stringer light set is Class 1, Division 1 rated for Groups C and D and Class II, Division 1 Groups F and G. This unit is multi-voltage and configured to operate on 120-277V AC or 12-24V DC, please choose your configuration below.

Made in USA Quality

1. Federal Spec Cord.
2. Explosion Proof.
3. Total of (10) 10 watt LED Lamps.
4. Non-sparking aluminum construction.
5. UL Class 1 Div 1 Class 2 Div1
7. 120-277V AC or 12-24V DC Operation
8. SOOW cable.
9. Aluminum Hooks for Convenient Placement.
10. Daisy Chain Connections.

Lamp Features

- 100 watts of LED illumination
- Non-sparking aluminum housings
- Light weight mold T Junctions
- Cast aluminum guard prevent lamp or globe damage
- Tempered Soda-Lime Glass Lamp Globe
- Integrated lamp shock absorbers prevent drop damage
- Swivel hook for hanging and hands free operation
- 14/3 SOOW Abrasion Resistant Cable



Frequently Asked Questions (FAQ)









RNT-EPL-SL-10-LED-E2E

Product ID: 147209

Harmonized System (HS) Code: 9405.41.84.10

Export Control Classification Number (ECCN): EAR99

Options:

RNT-EPL-SL-10-LED-E2E-Rental Length-Voltage-Cord Cap

Example: RNT-EPL-SL-10-LED-E2E-MR-120V-1523

Rental Length	
MONTHLY	-MR
WEEKLY	-WR
DAILY	-DR

Voltage	
120V AC	-120V
240V AC	-240V
24V AC/DC	-24V

Cord Cap	
5-15	-1523
5-20	-2023-125V
6-20	-2023-250V

Links (Click on the below items to view):

- [Canadian CEC Certificate \(Commonly referred to as CSA Certificate\)](#)
- [CE Certificate](#)
- [Certificate 1, Misc](#)
- [Certificate 2, Misc](#)
- [Certificate 3, Misc](#)
- [MSDS \(Material Safety Data Sheet](#)
- [RoHS Certificate \(Restriction of Hazardous Substances\)](#)
- [USA NEC Certificate \(Commonly referred to as UL Certificate\)](#)
- [HigResPic1](#)
- [HigResPic2](#)
- [HigResPic3](#)
- [HigResPic4](#)
- [HigResPic5](#)
- [HigResPic6](#)
- [HigResPic7](#)
- [HigResPic8](#)
- [HigResPic9](#)
- [HigResPic10](#)
- [ISO 9001 Certification](#)
- [Business Certificate](#)
- [Shipping Time Map](#)